Office	State of New Mexico	Form C-103
District I ~ (575) 393-6161	Energy, Minerals and Natural Resources	Revised August 1, 2011 WELL API NO.
1625 N. French Dr., Hobbs, NM 88244 OBBS (District II – (575) 748-1283		30-025-40374
	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
811 S First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd , Aztec, NM 87410 1000 Rio Brazos Rd , Aztec, NM 87410	2012 1220 South St. Francis Dr.	STATE STATE STATE
District IV – (505) 476-3460	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S St Francis Dr , Santa Fe, NM 87505 RECEI	VED	VO-3524
	AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS	TO DRILL OR TO DEEPEN OR PLUG BACK TO A	Berry APN State
DIFFERENT RESERVOIR USE "APPLICATION PROPOSALS")	ON FOR PERMIT" (FORM C-101) FOR SUCH	8. Well Number
	Well Other	2H
2. Name of Operator		9. OGRID Number
Yates Petroleum Corporation		025575
3. Address of Operator		10. Pool name or Wildcat
105 South Fourth Street, Artesia, NM 8	38210	Berry; Bone Spring, North
4. Well Location		
Unit Letter Lot 13 : 2957		660 feet from the West line
Unit Letter Lot 4 330		660 feet from the West line
Section 5	Township 21S Range 34E	NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		
	3723'GR	and the second s
12 Charle Ann	conrigta Roy to Indicate Natura of Notice	Papert or Other Date
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTE	NTION TO: SUE	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK 🗍 PL	LUG AND ABANDON 🔲 REMEDIAL WOI	RK
		RILLING OPNS. P AND A .
<u> </u>	ULTIPLE COMPL	NT JOB
DOWNHOLE COMMINGLE		
OTHER:	OTHER: Interme	ediate casing
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
13. Describe proposed or completed	operations. (Clearly state all pertinent details, and	nd give pertinent dates, including estimated date
of starting any proposed work).	operations. (Clearly state all pertinent details, as SEE RULE 19.15.7.14 NMAC. For Multiple Co	nd give pertinent dates, including estimated date
13. Describe proposed or completed of starting any proposed work). proposed completion or recomp	operations. (Clearly state all pertinent details, as SEE RULE 19.15.7.14 NMAC. For Multiple Co	nd give pertinent dates, including estimated date
of starting any proposed work). proposed completion or recomp	l operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion.	nd give pertinent dates, including estimated date ompletions: Attach wellbore diagram of
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set	operations. (Clearly state all pertinent details, as SEE RULE 19.15.7.14 NMAC. For Multiple Co	and give pertinent dates, including estimated date ompletions: Attach wellbore diagram of 2'. Cemented stage 1 with 360 sx Class "C" +
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 594: D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130	and give pertinent dates, including estimated date ompletions: Attach wellbore diagram of 2'. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9).
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage	l operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 594: D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 22 with 1260 sx Class "C" + 236.92# D013 + 473	and give pertinent dates, including estimated date ompletions: Attach wellbore diagram of 2'. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld)	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 5942 D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 22 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C"	nd give pertinent dates, including estimated date ompletions: Attach wellbore diagram of 2'. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 8.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 594% D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 20 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate	nd give pertinent dates, including estimated date ompletions: Attach wellbore diagram of 2'. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 5942 D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 20 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 5942 D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 22 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi for the second control of the collar. WOC 4 hrs. Tested casing to 1500 psi for the second collar.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 5942 D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 22 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi for the second control of the collar. WOC 4 hrs. Tested casing to 1500 psi for the second collar.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 5942 D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 22 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi for the second control of the collar. WOC 4 hrs. Tested casing to 1500 psi for the second collar.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 5942 D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 22 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi for the second control of the collar. WOC 4 hrs. Tested casing to 1500 psi for the second collar.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" and	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 594. D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 20 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi fond resumed drilling.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 5942 D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 22 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi for the second control of the collar. WOC 4 hrs. Tested casing to 1500 psi for the second collar.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" and	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 594. D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 20 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi fond resumed drilling.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" at	Rig Release Date: REE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 594. D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 20 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi fond resumed drilling.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2'. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi or 30 min. Start 1505 psi, end 1500 psi. WOC
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" at	d operations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 594. D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 20 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi fond resumed drilling.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2'. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi or 30 min. Start 1505 psi, end 1500 psi. WOC
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" at	Rig Release Date: REE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 594. D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 20 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 o cellar. WOC 4 hrs. Tested casing to 1500 psi fond resumed drilling.	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2'. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi or 30 min. Start 1505 psi, end 1500 psi. WOC
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" at	Roperations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 5942 D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 22 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 ocellar. WOC 4 hrs. Tested casing to 1500 psi fond resumed drilling. Rig Release Date:	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2'. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi or 30 min. Start 1505 psi, end 1500 psi. WOC
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" at	Rig Release Date: Rig Reparties and complete to the best of my knowled and resumed drilling. Rig Release Date:	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi or 30 min. Start 1505 psi, end 1500 psi. WOC
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" at Spud Date: 3/26/12 Type or print name Tina Huerta	Roperations. (Clearly state all pertinent details, at SEE RULE 19.15.7.14 NMAC. For Multiple Colletion. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 5942 D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 + 22 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 ocellar. WOC 4 hrs. Tested casing to 1500 psi fond resumed drilling. Rig Release Date:	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 18.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 0.5 sx Class "C" + 105sx D903 with 2% CaCi or 30 min. Start 1505 psi, end 1500 psi. WOC
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" at	Rig Release Date: Rig Release Date: Rig Release Date: Rig Release Tinah@yatespetroleu Bettions. Clearly state all pertinent details, and SEE RULE 19.15.7.14 NMAC. For Multiple Collection. 9-5/8" 36#, 40# N-80 K-55 LT&C casing at 594. D046 + 33.82# D065 + 44.97# D130 + 33,816# 20 + 704.96# D042 + 44.18# D046 + 29.37# D130 2 with 1260 sx Class "C" + 236.92# D013 + 473 1.97, wt 12.9). Tailed in with 200 sx Class "C" 5.19# D903 (yld 1.35, wt 14.8). Did not circulate then cement at 1840'. Ran 1" to 345'. Pumped 1 cellar. WOC 4 hrs. Tested casing to 1500 psi for the design of	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 88.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi or 30 min. Start 1505 psi, end 1500 psi. WOC or 30 min. Start 1505 psi, end 1500 psi. WOC
of starting any proposed work). proposed completion or recomp 4/20/12 – TD 12-1/4" hole to 5942'. Set 67.63# D013 + 1079.25# D042 + 67.63# Class "C" + 44.18# D013 + 883.55# D02 Circulated 285 sx to pit. Cemented stage + 157.53# D130 + 118,461.8# D903 (yld + 18.77# D065 + 24.975# D130 + 18,765 showed cement at 840', a scratchy area, t (yld 1.35, wt 14.8). Circulated 10 bbls to 58 hrs 30 min. Reduced hole to 8-3/4" at Spud Date: 3/26/12 Type or print name Tina Huerta	Rig Release Date: Rig Reparties and complete to the best of my knowled and resumed drilling. Rig Release Date:	and give pertinent dates, including estimated date completions: Attach wellbore diagram of 2. Cemented stage 1 with 360 sx Class "C" + D903 (yld 1.35, wt 14.8). Tailed in with 235 sx 0 + 22,088.69# D903 (yld 1.97, wt 12.9). 88.47# D020 + 3780.69# D042 + 236.92# D046 + 37.53# D013 + 598.89# D042 + 37.53# D046 cement. Ran temperature survey. Survey 05 sx Class "C" + 105sx D903 with 2% CaCi or 30 min. Start 1505 psi, end 1500 psi. WOC or 30 min. Start 1505 psi, end 1500 psi. WOC