

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-40456
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other (P&A)		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Primero Operating, Inc		6. State Oil & Gas Lease No. VB-1183
3. Address of Operator PO Box 1433, Roswell, NM 88202-1433		7. Lease Name or Unit Agreement Name Big Foot
4. Well Location Unit Letter <u>G</u> : 1980 feet from the <u>N</u> line and <u>1650</u> feet from the <u>E</u> line Section <u>20</u> Township <u>18S</u> Range <u>34E</u> NMPM Lea County		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4050 GR		9. OGRID Number 018100
		10. Pool name or Wildcat EK Yates, 7 Rivers, Queen

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Test 8 5/8" surface casing to 1,000 psi for 30 minutes, ok. Drill out with 7 7/8" bit to a TD of 6105'. Run logs and cores. P&A well on 5/10/2012 as follows:

Pump 30 sx cmt plug from 6048 to 5934.
Pump 30 sx cmt plug from 4600 to 4486.
Pump 30 sx cmt plug from 3466 to 3352.
Pump 40 sx cmt plug from 1891 to 1776, across surf csg shoe.
Pump 30 sx cmt plug from 411 to 296.
Pump 20 sx surf plug from 60 to surf.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.emnrd.state.nm.us/oed.

All cmt plugs were Class C neat mixed at 14.8 ppg and 1.33 cu ft per sx yield. Hole was circulated with 9 ppg mud laden fluid before pumping plugs, and plugs were displaced with same fluid. Plug plan was discussed with Paul Kautz on 5/8/2012 and Mark Whitaker with the NMOCD was notified 5/9/2012 before pumping the first plug. Rig will be moved, location cleaned off, and a dry hole marker erected.

Spud Date: 4/22/2012

Rig Release Date: 5/10/2012

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John C Maxey TITLE: Consulting Pet Engr

DATE: 5/8/2012

Type or print name: John C Maxey

E-mail address: jcm@maxeyengineering.com

PHONE: 575-623-0438

For State Use Only

APPROVED BY [Signature] TITLE State Rep

DATE 5-15-2012

Conditions of Approval (if any):

MAY 15 2012