District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Santa Fe, NM 87505

Oil Conservation Division 1220 South St. Francis Dr.

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade ta Type of action: Registration of a pit	ink covered by a "general plan"? Yes X No t or below-grade tank ☐ Closure of a pit or below-gra	ade tank X			
Operator: Yates Petroleum Corporation Telephone: 505-748-4500 e-ma Address: 105 South 4 th Street, Artesia, N.M. 88210 Facility or well name: Anna Belle BBB 1 API #: 30-025-36071 U/L or Qtr/Q County: Lea Latitude 32.9973 Longitude 103.4 Surface Owner: Federal State X Private Indian	Otr <u>P</u> Sec <u>22 T 15S</u> R 3 /4				
Pit Type: Drilling X Production ☐ Disposal ☐ Work over ☐ Emergency ☐ Lined X Unlined ☐ Liner type: Synthetic ☐ Thickness 12 mil Clay ☐ Pit Volume 12,000 bbl	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes				
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) XXXX (0 points)			
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points) XXXX			
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points) XXXX			
	Ranking Score (Total Points)	10 POINTS			
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relaburying in place) onsite X offsite If offsite, name of facility NA (4) Groundwater encountered: No Yes If yes, show depth below ground so Attach soil sample results and a diagram of sample locations and excavations.	. (3) Attach a general description of remedial action surfaceft. and attach sample results.	posal location: (check the onsite box if your are n taken including remediation start date and end date.			
Additional Comments: Closure work plan for drilling pit. The drilling pit contents mil. Synthetic liner on former drilling pit site. Drilling pit contents will then be with a min. of a 3' over lap of the underlying trench areas. The encapsulation to 48 hour notice will be provided to the Oil Conservation Division before pit closure.	emplaced into the encapsulation trench. A 20 mil. Syrrenches will then be backfilled back to grade using a m	nthetic liner will then be placed over the pit contents			
Pit Closure actions to begin by NA. Ending date NA		2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 /			
Your certification and NMOCD approval of this application/closure does not re	Signature	nit or tank contaminate ground wat the otherwise			
endanger public health or the environment. Nor does it relieve the operator of it	ts responsibility for compliance with any other federal,	state, or local laws and or legulations.			
Approval: Printed Name/Title GAR 4 W. WINK STAFF MG	Spirature Hay Www	Date: 4/25/05			

New Mexico Office of the State Engineer Well Reports and Downloads /

Township: 158 Range: 35E Sections: Y: Zone: Search Radius: NAD27 X: Number: Suffix: Basin: County: Non-Domestic Domestic Owner Name: (First) (Last) All Well / Surface Data Report Avg Depth to Water Report Water Column Report Clear Form WATERS Menu Help

AVERAGE DEPTH OF WATER REPORT 04/04/2005

							, ,	(Depth	Water in	Feet)
Bsn	Tws	Rng	Sec	Zone	x	Y	Wells	Min	Max	Avg
L	15s	35Ē	01				3	44	55	50
L	15s	35E	03				2	45	75	60
L	15s	35E	05				1	65	65	65
L	15S	35E	06				1	58	58	58
L	15S	35E	07				6	54	75	60
L	15S	35E	12				4	50	58	54
L	15S	35E	13				4	50	60	57
L	15S	35 E	14				1	48	48	48
L	15S	35E	16				1	65	65	65
L	15S	35E	19				2	56	60	58
L	15S	35E	22				2	55	55	55
L	15S	35E	25				7	52	63	59
L	15S	35E	27				3	46	56	52
L	15S	35E	28				3	55	70	63
L	15S	35E	30				1	60	60	60
L	15S	35E	31				4	65	73	69
L	15S	35E	32				3	65	70	68
L	15S	35E	33				7	50	69	59
L	15s	35E	34				2	54	55	55
L	15S	35E	35		•		14	45	70	58
L	15S	35E	36				11	50	120	71/
Reco	ord Co	ount:	82							1920

