

VACUUM ABO UNIT # 121
N VACUUM ABO FIELD
LEA COUNTY, NM

30-025-22101

ELEV. GL. 4020'
DF: 4032'
KB: 4034'

13-3/8", 48#, H40 CSG. SET TO
368' W/ 325 SX. CMT. CIRC.

ANNULUS CIRC. W/ FW + 1% BY VOL. NL
COAT 1270 PKR FLUID

PARTED 9-5/8" @ 1272', REQUIRES 6 PTS
TRIPPING THROUGH SQZ'D W/ 25 SX
CLASS C CMT. + 2% CACL2

09/23/11: 2-3/8" J-55 TBG-IPC (NEW), 2 JTS 2-3/8",
4.7#, J-55 TBG SUBS (10', 4') (NEW), 258 JTS 2-3/8",
J-55 TBG-IPC (NEW), 2-3/8" ON-OFF TOOL, TL CO2
W/1.50" BAKER "F" PROFILE, J-SLOT, XL (NEW),
OTIS WB PERMANENT PKR, MILL SHOE SEAL
ASSEMBLY (SAME) (3.035 OD). PKR @ 8396' EOT
@ 8400'.

TOL @ 4813'

9-5/8", 36 & 40#, J55 CSG. SET TO 4984',
W/ 2400 SX. CMT. CIRC.

OTIS WB PERMANENT PKR @ 8396' (TOP)

ABO PERFS: 8485-87', 89-94', 96', 97',
98', 8513', 14', 17-19', 21-26', 29-33', 41-
43', 97', 98', 99', 8600', (1-2 JSPF 50
HOLES) (7/1989);
8481-83', 8613-17', 2 JSPF

7" CIBP SET @ 9425 + 25' CMT. CAP

UPPER PENN PERFS: 10,108', 10', 23-25', 41-
43', 49-51', 63-65', 83-85', 1 JSPF 17 HOLES
TOTAL, SQZ'D W/ 140 SX.

GUIBERSON TYPE A PERMANENT PKR @
10,380' + PLUG + 25' CMT. CAP

MIDDLE PENN PERFS: 10,436'-10,474', 1
JSPF- 20 HOLES

7", 23#, S45 & N80 LINER SET TO
10550' W/ 1000 SX. CMT. CIRC

PBTD: 10,502'
TD 10,550'