

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB NO 1004-0137
Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

JUN 04 2012

Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

Name of Operator

Occidental Permian Ltd.

ATTN: Mark Stephens, 19.083, GRWY 5

a Address

P.O. Box 4294, Houston, TX 77210-4294

3b Phone No (include area code)

(713) 366-5158

Location of Well (Footage, Sec T, R, M or Survey Description)

1755' FNL & 977' FWL, Sec. 29, Letter E, T-18-S, R-38-E (SHL)

5 Lease Serial No

LC-032233(A)

6 If Indian, Allottee or Tribe Name

7 If Unit or CA/Agreement, Name and/or No

8 Well Name and No

North Hobbs G/SA No. 625 Unit

9 API Well No

30-025-37213

10. Field and Pool, or Exploratory Area

Hobbs; Grayburg-San Andres

11 County or Parish, State

Lea Co.

NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Fracture Treat☐ New Construction☐ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☐ Other

3 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

1) MI x RU, ND WH x NU BOP.

2) Kill well x POOH with production equipment.

3) RIH with 4-3/4" bit, scraper, and drill collars x clean out to 4383' (PBTD).

4) Circulate clean x POOH.

5) Run 5-1/2" PPI tool with 57' spacing. Acidize the following perf'd intervals with 15% PAD acid as follows:

4255' - 4285' w/1175 gal.

4211' - 4246' w/925 gal.

4142' - 4192' w/1000 gal.

6) POOH with work string x PPI assembly.

7) Contact Nalco for scale squeeze.

8) RBIH with production equipment.

9) ND BOP x NU WH. Turn well over to production.

10) RD x MO x clean location.

4 I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Mark Stephens

Title

Regulatory Compliance Analyst

Date

5/15/12

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Mark Stephens

Title

PETROLEUM ENGINEER

Date

JUN 05 2012

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

JUN 07 2012

BHM

NHU# 29-625
API # 30-025-34870
SURFACE: 1755 FNL & 977 FWL
SEC. 29, T-18-S, R-38-E, Unit Ltr E
LEA COUNTY NEW MEXICO

8-5/8", 24#, J-55, set at 1545' w/750 sx.
(Cement circulated to surface)

PERFORATIONS

**OPEN: 4142-51', 4155-58', 4161-65', 4168-73',
4179-82', 4189-92', 4211-16', 4231-46', 4255-72',
4276-85'**

5-1/2", 15 5#, J-55, set at 4430' w/950 sx
(Cement circulated to surface)

