

District I - (575) 393-6161  
1625 N French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88203  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OCD

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

FEB 06 2012

WELL API NO. 30 025 40077
5. Indicate Type of Lease STATE FEE x
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Howenstine 12
8. Well Number 1
9. OGRID Number 015742
10. Pool name or Wildcat <del>Shipp, Strawn (55695)</del> Dry & Abandon

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR NOTICES TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well: ☒ Gas Well ☐ Other ☐

2. Name of Operator  
Nearburg Producing Company

3. Address of Operator  
3300 N A. St., Bldg 2, Suite 120, Midland, TX 79705

4. Well Location  
Unit Letter B : 500 feet from the North line and 1594 feet from the East line  
Section 12 Township 17S Range 37E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.):  
3449'

12. Check ☒ to indicate Nature of Notice, Report or Other Data

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt of  
C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms, www.emnrd.state.nm.us/oed

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER:

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/18/2011: Notified NMOCD Mark Whitark of plug job.

11/19/2011: RU BJ Services & spot plugs as follows:

60 sx CI H @ 12,200'; 50 sx CI H @ 11,600'; 50 sx CI H @ 11,000'; 50 sx CI H @ 9000'; 50 sx CI H @ 7000'; 50 sx CI C @ 4630' WOC  
4 hrs tag top of cement @ 4445'; 50 sx CI C @ 2100'; 50 sx CL C w/3% CaCl @ 525' WOC for 4 hrs and tagged plug @ 404'. 40 sx CI  
@ 120' to surface, circulated 1 sx cement to surface.

N/D BOPs, cut 13 3/8" 3M & 11" 5M B section spool. Jet & cleaned pits, released rig.

Confidential Log and McVay Drilling Company deviation report attached to filing.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ann Ritchie TITLE Regulatory DATE 01/15/2012

Type or print name Ann Ritchie E-mail address: ann.wtor@gmail.com PHONE: 432 6846381

For State Use Only

APPROVED BY: [Signature] TITLE PERMISSION ENGINEER DATE JUN 06 2012

Conditions of Approval (if any):

JUN 07 2012