Submit 1 Copy To Appropriate District	State of New Mexico	Form C-10:
<u>District I</u> – (575) 393-6161	State of New Mexico State of New Mexico Resources	Revised August 1, 201
1625 N. French Dr , Hobbs, NM 88240 <u>District II</u> – (575) 748-1283		WELL API NO. 30-025-40303
811 S First St , Artesia, NM 88210	1 4 2012 CONSERVATION DIVISION 1220 South St. Francis Dr	5. Indicate Type of Lease
District III – (505) 334-6178 1000 Rio Brazos Rd , Aztec, NM 87410	1220 South St. I fullets D1.	STATE S FEE
	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S St Francis Dr, Santa Fe, NM 87505		VB-1023/VB-1033
SUNDRY NOTI	CES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		Naguss BRN State Com
PROPOSALS)		8. Well Number
	Gas Well Other	1H
2. Name of Operator	/	9. OGRID Number
Yates Petroleum Corporation 3. Address of Operator		025575 10. Pool name or Wildcat
105 South Fourth Street, Artesia, N	M 88210	Wildcat; Bone Spring
4. Well Location		, and a part of the part of th
i .	660 feet from the South line and	330 feet from the West line
	feet from the South line and	330 feet from the East line
Section 30	Township 21S Range 34E	NMPM Lea County
中的红色 。	11. Elevation (Show whether DR, RKB, RT, GR, etc	
The second secon	3672'GR	
12. Check Ap	propriate Box to Indicate Nature of Notice, F	Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WOR	
TEMPORARILY ABANDON		ILLING OPNS. □ PAND A □
PULL OR ALTER CASING	MULTIPLE COMPL CASING/CEMEN	-
DOWNHOLE COMMINGLE	_	· .
OTHER.	OTHER: Interme	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of		
proposed completion or recompletion.		
proposed compression or recomplished		
6/4/12 – TD 12-1/4" hole to 5538'.		
6/5/12 – Set 9-5/8" 36#, 40# HCK-55 J-55 LT&C casing at 5538'. Cemented stage 1 with 410 sx 35:65:6 Poz "C" + 0.25% D013 +		
7% D020 + 29#/sx D035 + 3#/sx D042 + 5% D044 + 0.2% D046 + 0.3% D112 + 0.125#/sx D130 + 61#/sx D903 (yld 2.10, wt 12.6). Tailed in with 180 sx 35:65:6 Poz "C" + 42#/sx D035 + 3#/sx D042 + 5% D044 + 0.2% D046 + 0.2% D065 + 0.125#/sx D130 +		
47#/sx D903 (yld 1.36, wt 14.2). Circulated 134 sx to pit. Cemented stage 2 with 1650 sx 35:65:6 Poz "C" + 0.25% D013 + 7%		
D020 + 29#/sx D035 + 3#/sx D042 + 5% D044 + 0.2% D046 + 0.3#/sx D112 + 0.125#/sx D130 + 61#/sx D903 (yld 2.10, wt 12.6).		
	+ 42#/sx D035 + 3#/sx D042 + 5% D044 + 0.2% D04	
	27 sx to pit. Tested casing to 1200 psi for 30 min, go	_
8-3/4" and resumed drilling.		DU Tool@??
2/22/4		
Spud Date: 9/29/11	Rig Release Date:	
I hereby certify that the information	bove is true and complete to the best of my knowledg	ge and belief.
MONATURE (1)		
SIGNATURE (TITLE Regulatory Reporting Supervisor DATE June 11, 2012		
Type or print name Tina Hue	ta E-mail address: tinah@yatespetroleum.co	om PHONE: <u>57</u> 5-748-4168
For State Use Only	L-man address. tman@yatespetroleum.co	5/3-/40-4100
APPROVED BY:	TITLE .	DATE JUN 1 5 2012
Conditions of Approval (if any):		محنم