

Submit 1 Copy To Appropriate District  
Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised August 1, 2011

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

HOBS OCD

JUN 18 2012

|                                                                                                     |
|-----------------------------------------------------------------------------------------------------|
| WELL API NO.<br>30-025-34340                                                                        |
| 5. Indicate Type of Lease<br>STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No.                                                                        |
| 7. Lease Name or Unit Agreement Name<br>CARLISLE 7                                                  |
| 8. Well Number<br>1                                                                                 |
| 9. OGRID Number<br>147179                                                                           |
| 10. Pool name or Wildcat<br>SHOE BAR; STRAWN, NE                                                    |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.)<br>3960'                                         |

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
Chesapeake Operating, Inc.

3. Address of Operator  
P.O. Box 18496  
Oklahoma City, OK 73154

4. Well Location  
Unit Letter L : 2238 feet from the SOUTH line and 1087' feet from the WEST line  
Section 7 Township 16S Range 36E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3960'

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt of  
C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms, [www.emnrd.state.nm.us/oed](http://www.emnrd.state.nm.us/oed)  
TEMPORARY  
PULL OR ALTER  
DOWNHOLE COMMINGLE

Appropriate Box to Indicate Nature of Notice, Report or Other Data

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Please find work performed on this well from 6/11/12 through 6/15/12.

6/11/12:

HELD PJSM - PERFORMED PULL TEST ON ANCHORS - MIRU PLUGGING RIG SPOTTED EQUIPMENT AND CONDUCT RIG INSPECTION - SDFN

6/12/12:

HELD PJSM RECIEVED - RACKED/TALLIED (11,000') 2 3/8" L-80 WORK STRING - P/U & TIH WITH TUBING TO 11,000' - SECURED THE WELL & SDFN

CONTINTUED ON PAGE 2

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Regulatory Specialist II

DATE 06/18/2012

Type or print name Bryan Arant

E-mail address: [bryan.arant@chk.com](mailto:bryan.arant@chk.com)

PHONE: (405)935-3782

For State Use Only

APPROVED BY:

TITLE

DATE

Conditions of Approval (if any):

JUN 28 2012

CARLISLE 7 1  
UNIT L, SEC. 7, T-16-S. R-36-E  
LEA CO., NM  
API # 30-025-34340

(P&A CONT.)

6/14/12:

HELD PJSM MIRU WIRELINE - PERF 5 1/2" @ 4,242' - POH W/ WIRELINE - LOADED HOLE - CLOSED BOP & PRESSURED UP TO 1,000# IT HELD FOR 20 MINUTES - CALLED NMOCD & RECIEVED PERMISSION TO SPOT 25 SX PLUG - TIH WITH (137) JTS 2 3/8" TBG, EOT @ 4,293' & SPOTTED 25SX CEMENT WITH 2% CAL - DISPLACED W/ 15.5 BBLS 9.5 MUD - PUH & WOC - TBIH & TAGGED TOC @ 4,040' - POH STANDING BACK (54) JTS LAID LAYED DOWN REST - R/U & RIH WITH WIRELINE & PERF CASING @ 1,600' - POH W/ WIRELINE - LOADED HOLE - CLOSED BOP ESTABLISHED INJECTION RATE @ 2 BPM - TIH WITH TBG & 5 1/2" PAKER - SET @ 1,316' - LOADED THE HOLE & SQZ 40SX CEMENT DISPLACED WITH 9.5 BBLS - SECURED THE WELL & SDFN

6/15/12:

HELD PJSM TIH W/ WIRELINE & TAGGED @ 1,421' - POH W/ WIRELINE - POH LAYING DOWN ALL TBG - RBIH W/ WIRELINE & PERF @ 525', RDMO WIRELINE - LOADED THE HOLE - CLOSED THE BOP & ESTABLISHED 3 BPM PUMP IN RATE - N/D BOP - N/U WH & SQZ'D WITH 135 SXCEMENT W/ 2% CALCIUM CHLORIDE FROM 525' TO BACK TO THE SURFACE - RDMO PLUGGING CREW & EQUIPMENT.  
WELL P&A ON 6/15/2012.

# CURRENT WELLBORE SCHEMATIC

WELL: CARLISLE 1-7  
 COUNTY: LEA STATE: NEW MEXICO  
 LOCATION: 2,238.0 FSL & 1,087.0 FWL SEC 10, BLK ,  
 ELEVATION: 3,960.0 GR -- 3,976.0 RKB  
 TD: 11,750.0 PBD: Original Hole - 11,269.0  
 STATUS: P & A

PROP #: 813856  
 API: 3002534340  
 SPUD DATE: 3/12/1998  
 RIG RELEASE:  
 FIRST SALES: 8/30/1998  
 WELLBORE TYPE: VERTICAL



HOBBS OGD

JUN 26 2012

