<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240

1301 W. Grand Avenue, Artesia, NM 88210

1000 Rio Brazos Road, Aztec, NM 87410

1220 S St. Francis Dr. Santa Fe, NM 87505

District II

District III

State of New Mexico

Energy Minerals and Natural Resources **2012** — Department

Oil Conservation Division RECEIVED 1220 South St. Francis Dr.

\$anta Fe, NM 87505

Form C-144 CLEZ July 21, 2008

For closed-loop systems that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure submit to the appropriate NMOCD District Office.

Closed-Loop System Permit or Closure Plan Application

(that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)

Permit Delosure Type of action:

Instructions: Please submit one application (Form C-144 CLEZ) per individual closed-loop system request. For any application request other than for a closed-loop system that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, please submit a Form C-144.

Please be advised that approval of this request does not relieve the operator of liability environment. Nor does approval relieve the operator of its responsibility to comply with	should operations result in pollution of surface water, ground water or the hany other applicable governmental authority's rules, regulations or ordinances.	
i. Operator: Cimares Energy Co. of Colorado	OCDID# 142492	
Address 600 N. Marienfeld St., Ste. 600, Midland, TX 79701		
Facility or well name Eureka 36 State 001		
API Number. 30-025- 33184 O	CD Parmit Municipal 211594 01-04970	
U/L or Qtr/Qtr <u>F</u> Section <u>36</u> Township <u>16S</u> Range <u>34E</u> County: <u>Lea</u> Center of Proposed Design: Latitude <u>32° 52′ 50 1492″</u> Longitude <u>-103° 31′ 2 5428″</u> NAD: □1927 ▼ 1983		
Surface Owner. Federal State Private Fribal Trust or Indian Allotm		
Surface Owner. Treater & state Trivate Trivat Present Indian Autom	Cit	
∑ Closed-loop System: Subsection H of 19.15 17 11 NMAC	TΑ	
Operation Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent)		
☐ Above Ground Steel Tanks or ☑ Haul-off Bins		
3		
Signs: Subsection C of 19.15.17.11 NMAC 12"\ 24"\ 2" lettering, providing Operator's name, site location, and emergency telephone numbers		
☐ 12 \ 24 \ .2 Tettering, providing Operator's name, site location, and emergency telephone numbers ☐ Signed in compliance with 19.15.3.103 NMAC		
4.		
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are		
Instructions: Each of the following items must be attached to the application. attached.	Please indicate, by a check mark in the box, that the documents are	
Design Plan - based upon the appropriate requirements of 19.15.17.11 NM		
 Operating and Maintenance Plan - based upon the appropriate requirement Closure Plan (Please complete Box 5) - based upon the appropriate require 		
· · · · · · · · · · · · · · · · · · ·		
☐ Previously Approved Operating and Maintenance Plan API Number:		
Wester Demonstration Cleans For Clean Land Continue The Hillian Alexander Continue Translation Continue Translatio		
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC) Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two		
facilities are required.		
Disposal Facility Name: <u>CRI</u>		
Disposal Facility Name		
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future service and operations? Yes (If yes, please provide the information below) No		
Required for impacted areas which will not be used for future service and operations. Soil Backfill and Cover Design Specifications based upon the appropriate requirements of Subsection II of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC		
Site Reclamation Plan - based upon the appropriate requirements of Subsection	Stion G of 19.15.17.13 NMAC	
Operator Application Certification:		
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief		
Name (Print): Paula Brunson	Title: Dulling Tech	
Signature: Ca. Ca. Bunista	Date:6/11/12	
e-mail-address: pbrunson@cimarex.com	Telephone: 432-571-7848	

OCD Approval: Permit Application (including closure plan) Closur	re Plan (only)	
OCD Representative Signature: Majey Stown	Approval Date: 7/11/2012	
Title: Compliance Officer	OCD Permit Number: P1-04900	
Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.		
	☐ Closure Completion Date:	
9. Closure Report Regarding Waste Removal Closure For Closed-loop Syste Instructions: Please indentify the facility or facilities for where the liquids, a two facilities were utilized.		
Disposal Facility Name: Disp	osal Facility Permit Number:	
Disposal Facility Name: Disposal Facility Permit Number:		
Were the closed-loop system operations and associated activities performed or Yes (If yes, please demonstrate compliance to the items below) No		
Required for impacted areas which will not be used for future service and open Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	rations:	
Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requi		
Name (Print):	Title:	
Signature:	Date: 6/11/12	
e-mail address:	Telephone:	

Cimarex Energy Co. of Colorado – Closed-Loop System Design Plan

Equipment List

- Primary Shakers
- Mud Cleaner hydro-cyclones
- 1 or 2 Centrifuges (depending on well depth)
- De-watering system with pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing (may not be necessary for shallower wells)
- Drying Augur
- Sump Drying Augur
- Sump
- Cuttings Boxes
- Reserve Fluids Tank Farm
- Wire Mesh Trash Enclosure (spent motor oils kept in separate containers and later sent to approved landfill)

Operation and Maintenance

The Cimarex Zero Discharge system is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This ensures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.

These closed loop operations can be monitored by our service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and tested for all regulated toxic materials. If found they are removed and disposed of per regulatory requirements.

Closure Plan

During drilling operations, all liquids, drilling fluids, and cuttings will be hauled off via CRI (Controlled Recovery Incorporated, Permit R-9166).

Point C-141 CTC/ Oil Conservation Division Page 3 of 4



Closed Loop with Drying Auger and Dewatering System

