Form 3160-5 (August 2007)

HOBBS OCD **UNITED STATES** OCD Hobbs DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

5. Lease Serial No. NMI C-0031741A

Ĉ-	6. If Indian, Allottee or Tribe Name					
SI D:0866	0. If Illulall, Allottee	of Tribe Name				
Abandon	ed well. Use Form	posals to drill or to re-enter and 3160-3 (APD) for such proposals				
	RIPLICATE Other in	7. If Unit of CA/Agreement, Name and/or No. WBDU NM120042X				
1. Type of Well	Gas Well	8. Well Name and No. WEST BLINEBRY CORINKARD UNIT #107 <37346>				
2. Name of Operator APACHE C	ORPORATION <873>	9. API Well No. 30-025-40481				
3. Address		3b. Phone No. (include area Code)	The state of the s			
	AIRPARK LN, #3000 , TX 79705	432-818-1117 / 432-818-1198	117 / 432-818-1198 EUNICE; BLI-TU-			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Parish, State			
330' FNL & 1650' FWL, UL: C, SEC 8, T21S, R37E, NMPM			LEA COUNTY, NM			
12. CHECK 7	THE APPROPRIATE BO	X(ES) TO INDICATE NATURE OF NOTICE	CE, REPORT OR OTHE	R DATA		
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of IntentSubsequent ReportFinal Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Facture Treat Reclam New Construction Recom	olete arily Abandon	Water Shut-Off Well Integrity Other DRILLING OPS: CASING & CEMENT REPORT		
If the proposal is to deepen direct Attached the Bond under which the following completion of the invol	nonal or recomplete horizont ne work will be performed o ved operations. If the opera Abandonment Notices mus	pertinent details, including estimated starting date of ally, give subsurface locations and measured and to provide the Bond No. on file with BLM/BIA. Rotion results in a multiple completion or recompletion to the filed only after all requirements, including recompletion.	rue vertical depths of all pert equired subsequent reports m on in a new interval, a Form	tinent markers and zones. nust be filed within 30 days 3160-4 must be filed once		
		un & set 8-5/8" 24# J-55 STC csg to 1				
		5% CF, 3#/sx LCM-1, 0.005 gps FP-6L, 4% 17 psi 24 hr – 700 psi 72 hr – 1278 p		, 1.75 yld)		
<u>Tail:</u> 300 sx 0	Class C w/1% CaCl, 0.13	3 #/sx CF, 0.005 gps FP-6L (14.8 ppg,	1.33 yld)			
Com	pressive Strenaths: 12	hr – 875psi 72hr – 1466 psi				

***Circ 179 sx cmt to surf *** Surface Casing Pressure Test: 1200 psi/30 min – OK

6/1/2012 – DRL F/6115' – T/ 7163' TD. CIRC & COND Hole, RU Schlumberger Loggers.

any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

REPORT CONTINUED ON PAGE 2.

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)				_						
, , , , , , , , , , , , , , , , , , , ,	Title	DRILLING TECH	100	רחדרה	בטס סבי	2000				
Signature Vicki Brown	Date	7/9/2012	AUU	EFIED	FUR KE	שלעולי				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE										
Approved by	Title			Date	7 auz					
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to condition operations therein.			80		AND MANAGEN FIFED OFFICE					
Title 18 U>S C. Section 1001 and Title 43 H S C. Section 1212 make it a crime for any	nerson k	nowingly and willfully to n	nake to any	denartment or	aveney of the Lin	ted States				

WBDU #107 - Csg & Cmt End of Well Sundry

6/3/2012 - 5-1/2" Production, Hole 7.625": Run & set 5-1/2" 17# L-80 LTC csg to 7163'. Cement with:

Lead: 900 sx (50:50) Poz (Fly ash): Class C w/5% NaCl, 0.13 #/sx CF, 3 #/sx LCM-1, 0.5% FL-52, 0.005 gps FP-6L, 10%

Bentonite, 0.2% Sodium Metasilicate (11.8 ppg, 2.46 yld)

Compressive Strengths: **12** hr – 100 psi **24** hr – 200 psi **72** hr – 550 psi

<u>Tail:</u> 400 sx (50:50) Poz (Fly ash): Class C w/5% NaCl, 0.13#/sx CF, 0.2% CD-32, 3 #/sx LCM-1, 0.45% FL-52, 0.005 gps FP-

6L, 2% Bentonite, 0.1% Sodium Metasilicate (14.2 ppg, 1.3 yld)

Compressive Strengths: **12** hr – 500 psi **.24** hr –1600 psi **72**hr —2250 psi

*** Circ 182 sx cmt to surf *** Production Casing Pressure Test: 2500 psi/30 min - OK

6/3/2012 - RR