(August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No 1004-0137 Expires July 31, 2010

5 Lease Serial No. NM 15035

SUNDRY NOTICES AND REPORTS ON WELLSUL $1\,6\,2012$

6. If Indian, Allottee or Tribe Name

Do not use this abandoned well.	form for proposals to Use Form 3160-3 (A	o drill or to re-enter a PD) for such propos	an Asmasa		·		
	IT IN TRIPLICATE - Other		7 If Unit of CA/Agreement, Name and/or No				
1. Type of Well		•		,			
Oil Well Gas	Well Other		8. Well Name and No. Triple A Federal #1				
2. Name of Operator Siana Operating, LLC			9	API Well No. 0-025-24993			
3a Address		3b. Phone No (include area o	code) 10	. Field and Pool or E	Exploratory Area		
P.O. Box 10303 Midland, TX 79702	/.	432-687-6600	A	ntelope Ridge; Wo	lfcamp		
4 Location of Well (Footage, Sec., T.	R, M, or Survey pescription))	11	. Country or Parish,	State		
1580' FNL & 2414' FWL, Sec 10, T-23-S, R-34	-E /		Le	Lea County, New Mexico			
12 CHE	CK THE APPROPRIATE BO	X(ES) TO INDICATE NATU	RE OF NOTICE,	REPORT OR OTHI	ER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent	Acidize	. Deepen	Producti	on (Start/Resume)	Water Shut-Off		
140tice of finent	Alter Casing	Alter Casing Fracture Treat Reclamation		ition	Well Integrity		
Subsequent Report	Casing Repair	New Construction	Recomp	lete	Other Non-Compliance		
Subsequent Report	Change Plans	Plug and Abandon	Tempora	arıly Abandon	Reponse		
Final Abandonment Notice	Convert to Injection	Plug Back	Water D	ısposal			
13 Describe Proposed or Completed C the proposal is to deepen direction Attach the Bond under which the following completion of the invol- testing has been completed. Final determined that the site is ready for	ally or recomplete horizontall work will be performed or pro- ved operations. If the operation Abandonment Notices must be	y, give subsurface locations and wide the Bond No on file with on results in a multiple complet	nd measured and to BLM/BIA Required tion or recompleti	rue vertical depths o uired subsequent rep on in a new interval	of all pertinent markers and zones forts must be filed within 30 days a Form 3160-4 must be filed once	lf	
 Spot 50 sx cmt 8,400' to 8,650'. Spot 70 sxs cmt from 7,050' up top of cement to be at least 6,920'. Circulate hole with 9.5#/gal mud Spot 40 sxs cmt 5,100' to 5,300' Spot 40 sxs cmt 3,700' to 3,900' Spot 40 sxs cmt 950' to 1,150'. Spot 20 sxs from 50' to surface. Cut off wellhead 3' below surface. 	fluid.	See AHAD	ched	Chang]	
	RECLAMATION PROCEDI	IRF			ATTACHED FOR	<i>.</i> .	

ATTACHED

fictitious or fraudulent statements or representations as to any matter within its jurisdiction

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)							
Matthew Doffer	Title Operations Manager						
Signature Mattlew Doffer	Date 04/02/2012						
AHIS SPACE FOR FEE	DERAL OR STATE OFFICE USE						
Approved by fames Q. Comos	Title SEPS Date 7-13-12						
Conditions of approval, if any, are attached Approval of this notice does not warrant that the applicant holds legal or equitable stile to those rights in the subject lease which entitle the applicant to conduct of ordinate the provided in the subject lease which							

Prepared By Dite: 8-4-	Travis Henry
	By: CURRENT WELL BORE 1. API# 30-025-24993 DOFFER Triple "A" Federal #1 wellbore Schematic
MATT	DOFFER Triple "A" Federal #1 wellborg Schematic
<u> </u>	
650	20" 94 # H-40 CSG@ 650' (CMT CIRCU)
650	11/8
;	
-/	
3795	133/8" (SG@ 3795' (CMT CIRC'S)
5200	103/4" CSG set@ 5200' (CMT Circid)
	() () () () () () () () () ()
	Perfs 7019-7029 (9 holes)
11,478	
11,700	
	1-10 1-1 798" CS6@ 11,880" (CMT CIRCU)
11,880	Wolfcamp Perfs 11718-11975 (28 holes)
12,219	Strawn Rifs 12016-12208' (41 holes)
12,231	5" 18# N-80 C56 Liner 11,478-12,231' (CMT to Top of Liner, Drilled to PIP PKR 12262-12266' 12,231' (CMT to Top of Liner, Drilled to
	CMT Plug 12800-13100
13,600	
	TD 13,600'
	PBTD, 11,660'

Dute: 8-4-	الا	ivis hei								
·	T			PRO	POSED	PAA PA	1065			
M.A. Doff				_ (AP	I 30-	025-24	1993	. ,		
4-2-	12			Triple "A" F	edecal =	#1 well	bore Sch	nematic		
			- 					· · · · · · · · · · · · · · · · · · ·	····	
		1000	3	20.	5XS 0-	50'				,
			199	Di L	1					
650'				20" 94	# H-40	CSG@ 1	650' [(MT CTR	ca)	
50-	1 1 15	, 1	- 1 (1	A-1						
		3000	6	40 sx	S CMT	950-1,1	50'			
	افرار		1/4							
			18	· id						
			, , ,	1						
3715	40	ARA		13 3/8" CS	6027	795' (0	MT (TRO		PSKS CM	
	1	200						37	100 - 30	900
· ·			A	r						
		ļ	50						d0	
52001		943		103/4" CS6	set 6	2 5 200	(CMT	circid)	70 sks (MT 2001
	10		١					····	5,140 - ;	D, 5W
	Ė	1 1	5)				•			
	5	8 4		Perfs 7014	1-7029	(9 holes)	70 sxs	6,920	- 7,050	, ,
	CA)	<u>aac</u>	7					2057	SINP	ERFS
	- (-)	PAR "	ہٰإ	50sxs 8,400-	8.650'				· · · · · · · · · · · · · · · · · · ·	
	- 8		1				·			
	1									
, ,,			7			,				
11,478	1 6		10	IBP@ 11,700	" w/ 40"	Cont on To	r (TOC	11,660)	
		\$ P		75/8" CS6@1	_					
11,880				Wolfcamp						
10.00				Strawn Rif	5 12016-	12208'(41 holes)	·		
12,29	***************************************	1	5	" 18# N-80 CS	se Liner	11,478-12	2,231 (CMT. to T	To pof Li	per, Drilledto
			1						12,219	inside (SG)
			4 <	MT Plug 1280	00-13100	0				
13,600	<u></u>		1							
	T	D 13,	60C	<u>5</u>						
	PE	STD II	166	0"		•				
									`	

Siana Operating LLC P. O. Box 10303 Midland, TX 79702

RE: Changes to Plugging Procedure NMNM15035; Triple A Federal 1 1580' FNL & 2414' FWL, Sec. 10, T23S-R34E Lea County, New Mexico

Add plug: TIH and tag PBTD @ 11660'. Spot plug from 11660'-11283 (Liner top and top of Wolfcamp). WOC and tag.

- 1. Spot plug from 8542'-8362' (Bone Spring).
- 2. OK as is.
- 3. OK as is.
- 4. Spot plug from 5250'-4855' (Shoe and top of Delaware). WOC and tag.
- 5. Spot plug from 4037'-3745' (Top of Capitan Reef and shoe). WOC and tag.
- 6. Spot plug from 3645'-3515' (Base of Salt). WOC and tag.
- 7. Spot plug from 1150'-950' (Top of Salt). WOC and tag.
- 8. Spot plug from 700'-600' (shoe). WOC and tag.
- 9. Spot plug from 50'-surface.
- 10. Cut off wellhead3' below surface and install P&A marker. Fill in cellar. Clear location of all flowlines and other production material.

If any questions, contact Jim Amos @ 575-234-5909 (office) or 575-361-2648 (cell).

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston Environmental Protection Specialist 575-234-5958

Bobby Ballard Environmental Protection Specialist 575-234-2230

Randy Rust Natural Resource Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922 Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Doug Hoag Civil Engineering Technician 575-234-5979

Tanner Nygren Natural Resource Specialist 575-234-5975

John Fast Natural Resource Specialist 575-2345996