

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OCD Hobbs

FORM APPROVED  
OMB NO 1004-0135  
Expires: July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*5 Lease Serial No  
NMLC061863A

6. If Indian, Allottee or Tribe Name

7 If Unit or CA/Agreement, Name and/or No

**SUBMIT IN TRIPLICATE - Other instructions on reverse side.**

1 Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

8. Well Name and No.

COTTON DRAW 32 STATE FED COM 11

2. Name of Operator

DEVON ENERGY PRODUCTION CO

Contact:

MELANIE A CRAWFORD

Email: melanie.crawford@dev.com

9 API Well No

30-025-40583-00-X1

3a. Address

333 WEST SHERIDAN AVE  
OKLAHOMA CITY, OK 73102

3b Phone No (include area code)

Ph: 405-552-4524

10 Field and Pool, or Exploratory

PADUCA

Delaware N

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 32 T24S R32E NESE 2310FSL 660FEL

11 County or Parish, and State

LEA COUNTY, NM

JUL 27 2012

## 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

RECEIVED

## TYPE OF SUBMISSION

## TYPE OF ACTION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Fracture Treat☐ New Construction☐ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☒ Other

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Devon Energy Production Co, LP respectfully requests the following.

We will plug back the pilot hole as follows:

A two plug job-

Plug 1: From pilot hole TD to 11,700' (250' fill). Set via 5" 19.50# drill pipe-balanced plug. Cement with 89 sks Class H Cement + 0.2% bwoc R-3 @ 15.60 ppg and 1.18 ft<sup>3</sup>/sk.

POOH and P/U bit to tag plug; tag plug to confirm top.

POOH and P/U cemented whip with ~700' 2-7/8" 6.5 # tubing below.

Set whip at 7900' (KOP)

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct

Electronic Submission #143882 verified by the BLM Well Information System

For DEVON ENERGY PRODUCTION CO LP, sent to the Hobbs

Committed to AFMSS for processing by KURT SIMMONS on 07/25/2012 (12KMS0962SE)

Name (Printed/Typed) MELANIE A CRAWFORD

Title REGULATORY ANALYST

Signature

(Electronic Submission)

Date 07/25/2012

## THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By CHRISTOPHER WALLS

Title PETROLEUM ENGINEER

Date 07/25/2012

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Hobbs

PETROLEUM ENGINEER

JUL 27 2012

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\*

JUL 30 2012

**Additional data for EC transaction #143882 that would not fit on the form**

**32. Additional remarks, continued**

Plug 2: Cement from 8600' to 7800' (100' above whip) with 283 sks  
Class H Cement + 0.2% bwoc R-3 @ 15.60 ppg and ft?/sk.

Thank you

**Conditions of Approval**  
**Cotton Draw 32 State Fed Com 1H**  
**30-025-40583**  
**7/25/12**

Pilot hole is required to have a plug at the bottom of the hole. If two plugs are set, the BLM is to be contacted (575-393-3612) prior to tag of bottom plug, which must be a minimum of 220' in length. Operator can set one plug from bottom of pilot hole to kick-off point and save the WOC time for tagging the first plug.