

Submit To Appropriate District Office Two Copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised August 1, 2011 1. WELL API NO. 30-041-20924 Type of Lease <input checked="" type="checkbox"/> STATE <input type="checkbox"/> FEE <input type="checkbox"/> FED/INDIAN 3 State Oil & Gas Lease No. LH 6324 0000						
WELL COMPLETION OR RECOMPLETION REPORT AND LOG										
4 Reason for filing: <input type="checkbox"/> COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) <input checked="" type="checkbox"/> C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33, attach this and the plat to the C-144 closure report in accordance with 19.15 17 13.K NMAC)				5. Lease Name or Unit Agreement Name Mesa 26 State 6 Well Number. 1						
7 Type of Completion <input type="checkbox"/> NEW WELL <input type="checkbox"/> WORKOVER <input type="checkbox"/> DEEPENING <input type="checkbox"/> PLUGBACK <input type="checkbox"/> DIFFERENT RESERVOIR <input checked="" type="checkbox"/> OTHER P&A										
8. Name of Operator GeoSurveys, Inc.				9. OGRID 220247						
10 Address of Operator 218 South Leggett Drive, Abilene, Texas 79605				11 Pool name or Wildcat Wildcat (Montoya)						
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	L	26	2N	29E		1400	S	1100	W	Roosevelt
BH:	L	26	2N	29E		1400	S	1100	W	Roosevelt
13 Date Spudded 11-12-06	14 Date T.D. Reached 12-09-06	15 Date Rig Released 12-11-06		16. Date Completed (Ready to Produce)		17 Elevations (DF and RKB, RT, GR, etc.) 4248 GL				
18 Total Measured Depth of Well 7062'		19 Plug Back Measured Depth 7062'		20 Was Directional Survey Made? No		21 Type Electric and Other Logs Run DLL, LSS, DSN				
22 Producing Interval(s), of this completion - Top, Bottom, Name None										
23 CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
13 3/8"		48		358'		17 1/2"		400 sx 'C'		0
8 5/8"		28		2715'		12 1/4"		300 sx 'C'		0
5 1/2"		17		7010'		7 7/8"		400 sx 'C'		4835'
24 LINER RECORD										
SIZE	TOP	BOTTOM	SACKS CEMENT		SCREEN					
4"	6895'	7062'	50							
25 TUBING RECORD										
SIZE	DEPTH SET		PACKER SET							
26 Perforation record (interval, size, and number)						27 ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.				
2550'-2601' (Swab dry) (36 holes)						DEPTH INTERVAL				
7040'-7055' (Swab salt water) (30 holes)						AMOUNT AND KIND MATERIAL USED				
						2550'-2601' A/ 2000 gal 15% NeFe				
						7040'-7055' A/ 1500 gal 15% Ne Fe				
28 PRODUCTION										
Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod or Shut-in)				
						Dry Hole				
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl	Gas - Oil Ratio			
Flow Tubing Press	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)				
29. Disposition of Gas (Sold, used for fuel, vented, etc.)						30 Test Witnessed By				
31 List Attachments Plan of Pit, Logs										
32 If a temporary pit was used at the well, attach a plat with the location of the temporary pit. attached										
33. If an on-site burial was used at the well, report the exact location of the on-site burial:										
Latitude Longitude NAD 1927 1983										
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief										
Signature Calvin Donaghey		Printed Name Calvin Donaghey		Title President			Date 8-6-2012			
E-mail Address gsurveys@bitstreet.com										

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt	T. Atoka 6780'	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres 2470'	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash 6994'	T. Dakota	
T. Tubb 4205'	T. Delaware Sand	T. Morrison	
T. Drinkard	T. Bone Springs	T. Todilto	
T. Abo 4764'	T.	T. Entrada	
T. Wolfcamp 5530'	T.	T. Wingate	
T. Penn 6160'	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
 No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0'	68'	68'	Surface caliche, sand, clay	5530'	5920'	390'	limestone, shale
68'	120'	52'	sand and gravel, clay	5920'	6160'	240'	shale and limestone
120'	320'	200'	sand, red bed, gravel	6160'	6780'	620'	Limestone, shale
320'	1100'	780'	red beds, sandy, gyp	6780'	6970'	90'	limestone, conglomerate
1100'	1650'	550'	anhydrite, rb, sand	6970'	6994'	24'	sand
1650'	2200'	550'	anhydrite, sand, salt	6994'	7062'	68'	granite wash
2200'	2900'	700'	anhydrite, dolomite, rb, sd				
2900'	3150'	250'	anhyd., salt, sand, rb				
3150'	3280'	130'	anhyd, salt, rb, sand				
3280'	3500'	220'	anhyd, salt, sand, rb				
3500'	3800'	300'	anhyd, salt, rb, dolomite				
3800'	4090'	290'	salt, anhyd, sand				
4090'	4250'	160'	salt, anhyd, dolomite, sd				
4090'	4250'	160'	salt, anhyd, dolomite, sd				
4250'	4670'	420'	anhyd, salt, sand				
4670'	4760'	90'	anhyd, dolomite, gray shale				
4760'	4970'	210'	red beds, sand				
4970'	5170'	200'	sand and shale				
5170'	5300'	130'	red bed, shale, sand				
5300'	5530'	230'	sandy shale				