

Submit 1 Copy To Appropriate District

Office

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM

87505

State of New Mexico

Energy, Minerals and Natural Resources

Form C-103

Revised August 1, 2011

HOBBS OGD
AUG 21 2012
RECEIVED

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-40513
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-1193
7. Lease Name or Unit Agreement Name Adder BSE State
8. Well Number 1H
9. OGRID Number 025575
10. Pool name or Wildcat Wildcat; Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter	B	:	175	feet from the	North	line and	2200	feet from the	East	line
Unit Letter	O	:	330	feet from the	South	line and	2200	feet from the	East	line
Section	31		Township	24S	Range	33E	NMPM	Lea	County	

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3547'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Intermediate casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/6/12 - TD 12-1/4" hole to 5090'.

8/7/12 - Set 9-5/8" 36#, 40# HCK-55 J-55 LT&C casing at 5090'. Cemented with 1290 sx 35:65:6 Poz "C" + 0.3% D112 + 0.125%/sx D130 + 6% D20 + 5% D44 + 0.2% D46 + 5#/sx D42 (yld 1.99, wt 12.8). Tailed in with 360 sx 50/50 Poz "C" + 0.125% D130 + 5% D44 + 0.2% D65 + 0.2% D46 + 3#/sx D42 + 0.1% D201 (yld 1.37, wt 14.2). Circulated 214 sx to pit. WOC 22 hrs 30 min. Reduced hole 8-3/4" and resumed drilling.

Spud Date:

6/28/12

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Regulatory Reporting Supervisor

DATE

August 20, 2012

Type or print name

Tina Huerta

E-mail address:

tinah@yatespetroleum.com

PHONE: 575-748-4168

For State Use Only

APPROVED BY:

TITLE

Petroleum Engineer

DATE

AUG 23 2012

Conditions of Approval (if any):