

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87409
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

Revised August 1, 2011

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

HOBBS OCD

AUG 15 2012

RECEIVED

WELL API NO.
30-025-09431

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.
33820

7. Lease Name or Unit Agreement Name

George Etz

8. Well Number 002

9. OGRID Number
142624

10. Pool name or Wildcat
Yates Seven Rivers

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well. Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Roca Production, Inc.

3. Address of Operator

P O Box 10139 Midland, Texas 79702

4. Well Location

Unit Letter L 1650 feet from the South line and 330 feet from the West line

Section 27 Township 23S Range 36E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3437'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MI and RU equipment.
2. Set CIBP @ 3360, - tag w/tubing, circ mud & cap w/25 sxs CI C cmt.
3. Spot 25 sxs CI C cmt at 3040' at the base of the salt & tag.
4. Spot 30 sxs CI C cmt at 1250' at the base of the salt & shoeplug & tag.
5. Perf & squeeze CI C cmt from 60' to surf & must verify.
6. Cut off wellhead, install P&A marker, cut off anchors, cover cellar, clean loc, move out.

*5 1/2" csg cemented temp survey 460' from surface.

Oil Conservation Division - Hobbs office **Must be Notified**
24 hours prior to the beginning of Plugging Operations begin

Release Date.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steve Douglas TITLE Engineer DATE 8/13/12

Type or print name Steve Douglas E-mail address: steve@ogxresources.com PHONE: 432-685-1287

For State Use Only

APPROVED BY [Signature] TITLE Dir/M&E DATE 8-28-2012

Conditions of Approval (if any):

AUG 28 2012

Roca Production, Inc.

Georae Etz #2

API No. 30-025-09431

TOC behind 460' →
5 1/2" csg by
temp. survey

Spud 5/5/49

Complete 5/21/49

per & sq 25 sx cmt
cmt to surface

1205' 8 5/8", 22.55 #
1250' Cmt to surface
w/ 450 sx

25 sx cmt @ 3040'

3360 CSBP cap w/ 25 sx
Circ - MLF

Seven Rivers
Perfs

3388'

3394'

3410' 5 1/2", 14 #, J-55,
Cmt 600 sx