

Subnat 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

HOBBS OCD
AUG 27 2012

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR APPLICATIONS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30- 025-26905
1. Type of Well: Oil Well ☐ Gas Well ☐ Other <u>Injection</u>		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator OXY USA WTP Limited Partnership		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 50250 Midland, TX 79710		7. Lease Name or Unit Agreement Name Myers Langlie Mathis Unit
4. Well Location Unit Letter <u>A</u> : <u>660</u> feet from the <u>north</u> line and <u>660</u> feet from the <u>east</u> line Section <u>31</u> Township <u>23S</u> Range <u>37E</u> NMPM County <u>Lea</u>		8. Well Number <u>59</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>3311</u>		9. OGRID Number 192463
		10. Pool name or Wildcat Langlie Mathis TRQB

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

Approved for plugging of well bore only Liability under bond is retained pending receipt of C-103 (Specifically for Subsequent Report of Well Plugging) which may be found at OCD web page www.emnrd.state.nm.us/oed	ATTENTION TO: AND ABANDON ☐ THIS ☐ Plugging ☐ under forms ☐ www.emnrd.state.nm.us/oed	SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTERING CASING ☐ COMMENCE DRILLING OPNS. ☐ P AND A ☒ CASING/CEMENT JOB ☐	OTHER: ☐
--	--	--	---------------------------------

13. Describe proposed or complete (or starting any proposed work). See proposed completion or recompletion.

14. NMAC. For Multiple Completions: Attach wellbore diagram of

8/16/12 MIRU PU, NDWH, NU BOP, unset pkr, POOH w/ bg. RIH w/ CIBP & set @ 3500'

8/17/12 RIH & tag CIBP @ 3500', Circ hole w/ 10# MLF. Test csg to 500#, held OK, Mark Whitaker-NMOCD approved eliminating WOC & tag on plugs, if casing had integrity. M&P 25sx CL C cmt @ 3500', Calc TOC 3251'. PUH to 2784', M&P 25sx CL C cmt, calc TOC 2537'. PUH to 1280', M&P 25sx CL C cmt, calc TOC 1033'. PUH to 580', M&P 50sx CL C cmt, calc TOC 85', POOH w/ tbq, WOC.

8/20/12 RIH w/ WL & perf @ 55', EIR, circ through ground, csg hole @ 7', RDBOP, circ 25sx CL C cmt to surf. RDPU.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Regulatory Advisor DATE 8/23/12

Type or print name David Stewart E-mail address: david.stewart@oxy.com PHONE: 432-685-5717
For State Use Only

APPROVED BY: David Stewart TITLE DIST. MGR DATE 8-28-2012
Conditions of Approval (if any):

AUG 28 2012