

HOBBS OGD

AUG 30 2012

## OIL CONSERVATION DIVISION

2220 South St. Francis Dr.

Santa Fe, NM 87505

RECEIVED

WELL API NO.

30-025-40511

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name

Taylor D

8. Well Number

1

9. OGRID Number

229137

10. Pool name or Wildcat

Maljamar; Yeso, West 44500

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

COG Operating LLC

3. Address of Operator

600 West Illinois Ave., Midland, TX 79701

4. Well Location

Unit Letter J : 1650 feet from the South line and 2310 feet from the East line

Section 9 Township 17S Range 32E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4076' GR

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
 DOWNHOLE COMMINGLE ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
 COMMENCE DRILLING OPNS. ☐ P AND A ☐  
 CASING/CEMENT JOB ☐

OTHER: ☐OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/26/12 Test csg to 5000 psi for 30 mins. Ok.

6/27/12 Perf Lower Blinebry @ 6505 - 6730 w/ 1SPF, 26 holes.

6/28/12 Acidize w/3,250 gals acid. Frac w/116,624 gals gel, 145,211# 16/30 ottawa sand, 31,582# 16/30 SLC.

CBP @ 6475. Perf Middle Blinebry @ 6220 - 6445 w/1 SPF, 26 holes.

Acidize w/2,250 gals acid. Frac w/119,575 gals gel, 150,451# 16/30 ottawa sand, 31,112# 16/30 SLC.

CBP @ 6190. Perf Upper Blinebry @ 5935 - 6160 w/1 SPF, 26 holes

Acidize w/2,437 gals acid Frac w/116,850 gals gel, 144,744# 16/30 ottawa sand, 30,192# 16/30 SLC.

CBP @ 5712. Perf Paddock @ 5520 - 5682 w/1 SPF, 19 holes.

Acidize w/1,500 gals acid. Frac w/97,046 gals gel, 99,540# 16/30 ottawa sand, 14,252# 16/30 SLC.

7/2/12 Drill out plugs. Clean out to PBDT 7054.

7/5/12 RIH w/200jts 2-7/8" J55 6.5# tbg, EOT @ 6670.

7/6/12 RIH w/2-1/2"x2"x24' pump. Hang on well.

Spud Date:

6/2/12

Rig Release Date:

6/13/12

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Regulatory Analyst

DATE

8/28/12

Type or print name

Chasity Jackson

E-mail address:

cjackson@concho.com

PHONE:

432-686-3087

For State Use Only

APPROVED BY:

TITLE

Petroleum Engineer

DATE

SEP 06 2012

Conditions of Approval (if any):

SEP 06 2012