

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

OCT 22 2012

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-05352
1. Type of Well: Oil Well ☐ Gas Well ☒ Other Water Injection ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Chevron Midcontinent, L.P.		6. State Oil & Gas Lease No.
3. Address of Operator 15 Smith Road Midland, TX 79705		7. Lease Name or Unit Agreement Name Lovington San Andres Unit
4. Well Location Unit Letter <u>K</u> : <u>1650</u> feet from the <u>South</u> line and <u>1960</u> feet from the <u>East</u> line Section <u>31</u> Township <u>16-S</u> Range <u>37-E</u> NMPM County <u>Lea</u>		8. Well Number: <u>15</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3824' DF		9. OGRID Number: <u>150661</u> <u>241333</u>
		10. Pool name or Wildcat Lovington Graybrg San Andres

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD- 5110' PERFS - 4531' - 5110' OH
13" 40# csg @ 295' w/200 sx, 17-1/4" hole, TOC: 159' - CALCULATED
9-5/8" 40# csg @ 2998' w/400 sx, 12" hole, TOC: 1818' - CALCULATED
7" 23# csg @ 4531' w/200 sx, 8-3/4" hole, TOC: 3840' - BOND LOG

- MIRUWSU. NDWH. NUBOP.
- Circulate well with 9.5 PPG plugging mud. Pressure Test casing to 500 psi and record/report findings.
- Set CIBP @ 4431' w/35 sx of C cement.
- Perf & Sqz 50 sx of C cement @ 3048' - 3148', CTOC. WOC & TAG - Base of Salt
- Perf & Sqz 50 sx of C cement @ 2248' - 2148, CTOC. WOC & TAG - Top of Salt
- Perf & Circulate 150 sx of C cement @ 345' to Surface.
- Cut off wellhead and anchors 3' below grade. Weld on dry hole marker. Clean location.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Representative

DATE

10/22/12

Type or print name
For State Use Only

Robert Holden

E-mail address:

rholden@keyenergy.com

PHONE:

432-523-5155

APPROVED BY:

TITLE

DATE

10-22-2012


Conditions of Approval (if any).

OCT 22 2012

Oil Conservation Division - Hobbs office Must be Notified
24 hours prior to the beginning of Plugging Operations begin

Apr. 15

use: Johnston San Augusts Unit.



use: San Andres Unit

16 15

Proposed

9 5/8" CG HEAD 11' BELOW G.L.
13" CG HEAD 15' BELOW G.L.
7-1186 INSTALL SURF (SALT) & INTERM
(OTHER) RISERS IN HEADS

- 3 3/4" 820 HEAD

8' KB

INSTALL NEW 7" 13" X 10" CSG
ABOVE 9 5/8" HEAD 7-10-86
NEW LARKIN 7" X 2 1/8" CSG HEAD

IFS + Circle 345 w/1505x
TO SURFACE

IFS + Sqz @ 2248' 505x
WOC / TAG

Perf + Sqz @ 3048 505x
WOC / TAG

13" 40" SET @ 215'

TR 159' CAG 17 3/4" HS.

→ Top of salt @ 2198'

9 5/8" 40" SET @ 2778

TR 188' CAG 12" HS.

Bottom of salt @ 2998'

2 3/4" x 1 1/2" x 16' RJAC
135-34 RODS 3375
64-7/8 RODS 1100

1 31' x 2 3/4" APMA
2 3' x 2 3/4" PS
3 2 3/4" SN
4 165 JTS 2 3/4" TBS
BOTTOM OF MA 17' OF TD

CIBP @ 4431' 355x

7" 22" SET @ 4531'

TR 3840 BY BOND R 3/4" HS.

TDP 4531

DELL NEW 6 1/4" DA 4772-SID 7-86
SAN ANTONIO

6 3/4" DA 4531-SID

BOTTOM SID

TD SID

RA 1650 PSI 1650 BWL SEC 31 165 37E

L.M. LEHMAN 7-22-86