Form 3160-5 (March 2012)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No 1004-0137

Expires October 31, 2014 5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter accented

NMNM67111 6. If Indian, Allottee or Tribe Name

a	bandoned well.	Use Form 3160-3 (APD) for	such proposal	s.					
	SUBMI	T IN TRIPLICATE – Other instruction	7. If Unit of CA/Agreement, Name and/or No.						
1. Type of Wel			N/A .						
\square			8. Well Name and No. GERONIMO FEDERAL #9						
2. Name of Op WAGNER OII			9. API Well No. 30-025-32133						
3a. Address 500 COMMERCE	No. (include area cod	OFFICIAL AND FILE							
FORT WORTH, T	2222	GERONIMO; DELAWARE 11. County or Parish, State							
4. Location of 2275' FSL & 960' (· .		MEXICO						
	12. CHEC	CK THE APPROPRIATE BOX(ES) TO	INDICATE NATURE	E OF NOTIC	CE, REPORT OR OTHE	ER DATA			
TYPE OF SUBMISSION			TY	TYPE OF ACTION					
Notice o	f Intent		Deepen	_	uction (Start/Resume)	Water Shut-Off			
			Fracture Treat New Construction	_	mation mplete	Well Integrity ☐ Other			
✓ Subsequ	ent Report		Plug and Abandon		porarily Abandon	C Other			
. Final Abandonment Notice			Plug Back		r Disposal				
Attach the following testing has	Bond under which the v completion of the involved been completed. Final d that the site is ready fo	ally or recomplete horizontally, give sub work will be performed or provide the Bo yed operations. If the operation results in Abandonment Notices must be filed only r final inspection.) BOP, RIH w/tbg 158 jts 4950'	ond No. on file with B n a multiple completion	LM/BIA. R	equired subsequent repo- letion in a new interval, reclamation, have been	orts must be filed within 30 days a Form 3160-4 must be filed once completed and the operator has			
	RECLAMAIN								
08-16-12	Circulate gel water 9	90 bbls, Shut down for repairs on cmt pump, down 8-17, 8-18, & 8-19-12 DUE 2-23-13							
08-20-12	Fix cmt pump, spot 4	40sxs CI C cmt @ 4950' WOC overn	ight		,				
08-21-12	Tag TOC @ 4639' - Haston. Tag good.	639' - notify BLM - Kaston, lay down 21 jts & spot 30sxs Cl C cmt @ 4275', WOC - 4 hrs. Tag TOC @ 4029', notify BLM - Kathy good. PUH 25 jts 3489' & spot 25sxs Cl C cmt 3% CaChl, PUH WOC							
08-22-12	Tag TOC @ 3186', F	3186', POOH w/tbg, NDBOP & WH. Cut 5 1/2" csg @ 2950'. Pull, lay down 67 jts & 2 pieces, NUBOP & WH, SDFN							
08-23-12	RIH w/tbg, 99 jts = 3092', spot 200sxs CI C cmt, POOH w/tbg & WOC, Tag @ 2343' & spot 200sxs CI C cmt neat @ 2343', POOH w/tbg std back 18 jts = 562' & lay down rest, SDFN, WOC overnight, Kathy Haston (BLM) on location								
08-24-12									
08-27-12	WOC overnight 08-27-12 Tag TOC @ 404', ND BOP, spot 200sxs cmt 60' to surface, dig out cellar, cut off WH 4' below ground level, weld dry hole marker, RDMO dig up 4 anchors & back fill cellar, Well P&A								
14 I hereby cer	tify that the foregoing is to	rue and correct Name (Printed/Typed)		<u> </u>					
Sabrina Bonner			Title Regulato	Title Regulatory Analyst					
Signature	Date 10/04/20	Date 10/04/2012 ACCEPTED FOR RECORD							
	,	THIS SPACE FOR FE	DERAL OR STA	ATE OFF	ICE USE				
Approved by						POT 1 4 2012			
that the applicant	holds legal or equitable to ant to conduct operations		ch would Office		BUZEVII	OF LAND MANAGEMENT			
Title 18 U.S.C. S	section 1001 and Title 43	U.S.C. Section 1212, make it a crime for ai	ny person knowingly an	d willfully to	makello any department	or agency of the United States any false.			

fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Geronimo Federal #9 PRESENT COMPLETION PERMANENT WELL BORE DATA			FIELD Geronimo (Delaware)	Lea County, NM.	
			RECOMMENDED COMPLETION	API# 30-025-32133	
				DATA ON THIS COMPLETION	
Spud:	08/21/93	17-1/2" Hole		Spot 20 sx cmnt plug @ 60-surf	8/27/12
Elevation:	3,589' KB 3,571' GL	13-3/8" @ 505' Cmnt w/ 525 sx		Spot 40 sx cmnt plug @ 562-404', tagged	8/27/12
Rustler (base o	of fresh water)	12-1/4" Hol	le	TOC @ 1,470' Spot 60 sx @ 1760-1,470', tagged	8/24/12 8/24/12
				Tagged TOC @ 1,775	8/24/12
Solid plug thru Potash DV Tool @ 2,90			Spot 200 sx cmnt plug @ 2,343', displaced Spot 200 sx cmnt plug @ 3,092-2,343', tagged	8/23/12 8/23/12	
		Cmnt 1,250 s	×	Cut & pull 5-1/2" @ 2,950'	8/22/12
Yates				Minimum 9 ppg mud between all plugs required	
Top Reef	Sqz csg Re-sqz w/ 150 Aug-03	TOC @ 3,200' (CBL) leak 3,377-3,406' w/ 200 sx Spot 50 sx & sqz 1 bbl	× P	Tagged TOC @ 3,186' 25 sx cmnt plug @ 3,489-3,186', displaced	8/22/12 8/22/12
-	8-5	/8" 32# K-55 STC @ 4,205 Cmnt 700 sx		TOC @ 4,029' . 30 sx cmnt plug @ 4,275-4,029', tagged	8/20/12
Base Reef Delaware		7-7/8" ł perf 4,872	TO 40:	C @ 4,639' sx cmnt plug @ 4,950-4,639', tagged c w/ 17,755# 9/11/03	8/20/12 9/8/03
		perf 5,270-	0-80' no:	frac	9/4/03
Delaware		perf 7,591-7,	600' frac	SP @ 7,000' w/ 20' cmt s w/ 8,000# 10/5/93 - PBTD @ 7,680'	8/22/03 10/1/93
		perf 7,727-32' & 7,735	5-42' frac	: w/ 109,360# 9/29/03	3/2/00 · 9/25/93
		5-1/2" 17# N-80 LTC @ 7,9 Cmt w/ 1,000	965' 0 sx TD 7,960'	TD 7,847'	

. .