

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

RECEIVED
NOV 05 2012
HOBBSDOCD
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-06864
5. Indicate Type of Lease STATE ☒ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name EUNICE KING
8. Well Number: 24
9. OGRID Number:
10. Pool name or Wildcat PENROSE SKELLY GRAYBURG
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3470' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other Water Injection ☒ SWD

2. Name of Operator
Chevron USA INC.

3. Address of Operator
15 Smith Road Midland, TX 79705

4. Well Location
Unit Letter E: 2086' feet from the North line and 760' feet from the West line
Section 28 Township 28-S Range 37-E NMPM County Lea

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD- 8022' PERFS - 4150' - 4500' OH
13-3/8" 48# csg @ 312' w/300 sx, 17-1/2" hole, TOC: SURFACE
9-5/8" 36# csg @ 2800' w/1300 sx, 12-1/4" hole, TOC: 380' Temp Survey
8-3/4" 26# csg @ 7909' w/800 sx, 8-3/4" hole, TOC: 2590' - Temp Survey

1. MIRUWSU, NDWH, NUBOP.

TAG CIBP. Spot 25 sx cmf.

2. Circulate well with 9.5 PPG plugging mud (Pressure Test casing to 500 psi and record/report findings.)

3. Set CIBP @ 4050' w/45 sx of C cement.

4. 60 sx of C cement @ 2900' - 2700'

5. Perf & Sqz 55 sx of C cement @ 1750' - 1650', CTOC, WOC & TAG - Base of Salt @ 2500'

6. Perf & Sqz 55 sx of C cement @ 1561' - 1461', CTOC, WOC & TAG - Top of Salt @ 1265'

7. Perf & Circulate 245 sx of C cement @ 362' to Surface.

8. Cut off wellhead and anchors 3' below grade. Weld on dry hole marker. Clean location.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief

SIGNATURE Robert Holden TITLE Representative DATE 11/01/12

Type or print name Robert Holden E-mail address: rholden@keyenergy.com PHONE: 432-523-5155

For State Use Only

APPROVED BY: Mark White TITLE Compliance Officer DATE 11-05-2012

Conditions of Approval (if any):

Oil Conservation Division - Hobbs office. Must be Notified 24 hours prior to the beginning of Plugging Operations begin.

Location:

2086' FNL & 766' FWL
 Section. 28
 Township 21S
 Range 37E
 County Lea State NM

Elevations:

GL 3470'
 KB 3483'
 DF 3482'

Current
Wellbore Diagram

Well ID Info.

Cheyno FA7961
 API No 30-025-05864
 L5/L6 U491600
 Spud Date 8/3/50
 Compl Date 10/4/50

Surf. Csg: 13 3/8" 48#, H-40
 Set: @ 312' w/ 300 sks
 Hole Size: 17 1/2"

Circ: Yes TOC: Surface
 TOC By: Circulated

Interm. Csg: 9 5/8", 36#, J-55
 Set: @ 2800' w/ 1300 sks
 Hole Size: 12 1/4"
 Circ: No TOC: 380'
 TOC By: Temperature Survey

Perfs:

4150-4200'
 4370-4400'
 4420-50'
 4470-4500'

Status:

San Andres - Open
 San Andres - Open
 San Andres - Open
 San Andres - Open

CIBP @ 5070'
 (18' cmt on top)

5090-5104' Paddock - Cmt Sqzd
 5146-60' Paddock - Cmt Sqzd
 5194-5208' Paddock - Cmt Sqzd
 5238-48' Paddock - Cmt Sqzd

CIBP @ 5490'
 (18' cmt on top)

5501-03 Blinbry - Below CIBP
 5562-64' Blinbry - Below CIBP
 5604-06' Blinbry - Below CIBP
 5670-72' Blinbry - Below CIBP

CIBP @ 5755'
 (No cmt on top)

5788' Blinbry - Below CIBP
 5819' Blinbry - Below CIBP
 5842' Blinbry - Below CIBP
 5873' Blinbry - Below CIBP
 5886' Blinbry - Below CIBP

CICR @ 7100'
 (12' cmt on top)

7147-57' Abo - Below CIBP
 7173-78' Abo - Below CIBP
 7183-93' Abo - Below CIBP
 7200-06' Abo - Below CIBP
 7210-20' Abo - Below CIBP

CIBP @ 7299'
 (6' cmt on top)

Milled CICR @ 7290'

7662-85' McKee - Below CIBP
 7700-7815' McKee - Below CIBP
 7830-60' McKee - Below CIBP

FOC @ 7675

COTD: 5052'
 PBTD: 5052'
 TD: 8022'

Updated, 11/1/04

By: A. M. Howell

Prod. Csg: /, 23 & 26#, J-55 & N-80
 Set: @ 7909' w/ 800 sks
 Hole Size: 8 3/4"
 Circ: No TOC: 2590'
 TOC By: Temperature Survey

PROPOSED

Perf 4 Circulate
45 sx of Cement
362' To Surface

Well Eunice King # 24SWD

Field Penrose Skelly

Reservoir San Andres

Location:
2085' FNL & 766' FWL
Section 28
Township 21S
Range 37E
County Lea State NM

Elevations:
GL 3470'
KB 3483'
DF 3482'

Current
Wellbore Diagram

Well ID Info.
Crevno FA7961
API No 30-025-06864
L5/L6 U491600
Spud Date 8/3/50
Compl Date 10/4/50

Surf. Csg: 13 3/8", 48#, H-40
Set: @ 312' w/ 300 sks
Hole Size: 17 1/2"
Circ: Yes TOC: Surface
TOC By: Circulated

Interm. Csg: 9 5/8", 36#, J-55
Set: @ 2800' w/ 1300 sks
Hole Size: 12 1/4"
Circ: No TOC: 380'
TOC By: Temperature Survey

Top of Salt 1561' - 1461'

55 sx of Cement, CTOL

WOC + TAG

2900' - 2700' 60 sx cement

base of Salt

Perf + Sqz 1750' - 1650' 55 sx, CTOL
WOC + TAG

Set CIBP @ 4050'
45 sx of cement

Perfs:	Status:
4150-4200'	San Andres - Open
4370-4400'	San Andres - Open
4420-50'	San Andres - Open
4470-4500'	San Andres - Open

CIBP @ 5070'
(18' cmt on top)

5090-5104'	Paddock - Cmt Sqzd
5146-60'	Paddock - Cmt Sqzd
5194-5208'	Paddock - Cmt Sqzd
5238-48'	Paddock - Cmt Sqzd

CIBP @ 5490'
(18' cmt on top)

5501-03	Blinery - Below CIBP
5562-64'	Blinery - Below CIBP
5604-06'	Blinery - Below CIBP
5670-72'	Blinery - Below CIBP

CIBP @ 5755'
(No cmt on top)

5738'	Blinery - Below CIBP
5819'	Blinery - Below CIBP
5842'	Blinery - Below CIBP
5873'	Blinery - Below CIBP
5886'	Blinery - Below CIBP

CICR @ 7100'
(12' cmt on top)

7147-57	Abo - Below CIBP
7173-78	Abo - Below CIBP
7183-93	Abo - Below CIBP
7200-06'	Abo - Below CIBP
7210-20'	Abo - Below CIBP

CIBP @ 7299'
(6' cmt on top)

Milled CICR @ 7290'

7662-85'	McKee - Below CIBP
7700-7815'	McKee - Below CIBP
7830-60'	McKee - Below CIBP

TOC @ 7872'

COTD: 5052'
PBTD: 5052'
TD: 8022'

Updated: 11/1/04

By A M Howell

Prod. Csg: 7" 23 & 26#, J-55 & N-80
Set: @ 7909' w/ 800 sks
Hole Size: 8 3/4"
Circ. No TOC 2590'
TOC By: Temperature Survey