

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88201
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

RECEIVED

OIL CONSERVATION DIVISION

NOV 08 2012
220 South St. Francis Dr.
Santa Fe, NM 87505

HOBBSUCD

WELL API NO. 30-025-03909
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name WEST LOVINGTON UNIT
8. Well Number: 46
9. OGRID Number: 241333
10. Pool name or Wildcat Lovington, Upper San Andres, West

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other Water Injection ☐

2. Name of Operator
Chevron Midcontinent, L.P.

3. Address of Operator
15 Smith Road Midland, TX 79705

4. Well Location
Unit Letter A : 660 feet from the North line and 660 feet from the East line
Section 8 Township 17-S Range 36-E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD: 5100' Perfs: 4730'-5095' 306'
10-3/4" 40.5# csg @ 350' w/200 sx, 13-3/4" hole, TOC - SURFACE
7-5/8" 24# csg @ 2000' w/600 sx, 9-7/8" hole, TOC - SURFACE
5-1/2" 14# csg @ 5099' w/500 sx, 6-3/4" hole, TOC - 1709' Calc

- MIRUWSU. NDWH. NUBOP.
- TIH tubing. Circulate well with 9.5 PPG plugging mud. Pressure Test casing to 500 psi and record/report findings.
- Set CIBP @ 4630' w/25 sx C cement, CTOC.
- 45 sx of C cement @ 3260' - 2955', CTOC.
- 25 sx of C cement @ 2038' - 1938', CTOC. WOC & TAG
- Perf & Circ 100sx C cement @ 356' - Surface.
- Cut off wellhead and anchors 3' below grade. Weld on dry hole marker. Clean location.

The Oil Conservation Division Must be notified
24 hours prior to the beginning of plugging operations.

Spud Date:

Rig Release

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Representative DATE 11/08/2012

Type or print name Matt Brewer E-mail address: mbrewer01@keyenergy.com PHONE: 432-523-5155

For State Use Only

APPROVED BY: Makey Brown TITLE Compliance Officer DATE 11/9/2012

Conditions of Approval (if any):

Well Name & No West Livingston Unit # 96 Date 10-18-83

DF elev. - 3898
 GL elev. - 3889'

CURRENT

top of cmt calc 1709'

Livingston San Andres West

TD 5100'

← casing size 10 3/4
 Set @ 306'
 Grade H-40 Weight 40.5
 Hole Size 13 3/4
 Cement w/200 sx calc. circulation

← casing size 7 5/8
 Set @ 1988'
 Grade J-55 Weight 24#
 Hole Size 9 7/8
 Cement w/650 sx calc. circ.

4730'-60'

4780'-810'

4870'-86'

4910'-15'

4980'-5040'

5050'-55'

5085'-659' 5110'

5095' Set @

Grade

Hole Size

Cement

5 1/2
5099'
J-55 Weight 14#
6 3/4
w/400 sx

Well Name & No. West Livingston Unit # 46 Date 10-18-83

DF elev. - 3898
 SL elev. - 3889'

Perf & Circ @
 356'-surface
 w/100 sx

PROPOSED

Casing size 10 3/4
 Set @ 306'
 Grade 11-40 Weight 40.5
 Hole Size 12 3/4
 Cement w/200 sx calc. circulation

top of cement calc 1709'

Set plug @
 2038'-1938'
 w/25 sx
 WOC/TAG

Casing size 7 5/8
 Set @ 1988'
 Grade 7-55 Weight 24 7/8
 Hole Size 9 7/8
 Cement w/650 sx calc. circ.

Set plug @
 3260'-2955'
 w/45 sx (both
 salts)

Set CIBP @
 4630' w/25 sx

Livingston San Andres West

4730'-60'
 4780'-610'
 4870'-80'
 4910'-15'

4980'-5040'
 5050'-55'

5065'-559
 5095' Set @
 Grade
 Hole Size
 Cement

5 1/2
5099'
7-55 Weight 14 7/8
6 3/4
 w/400 sx

TD 5100'