

District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S St Francis Dr., Santa Fe, NM 87505

RECEIVED

NOV 13 2012

HOBBSUCD

CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-02208
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name West Vacuum Unit
8. Well Number: 35
9. OGRID Number: 4323
10. Pool name or Wildcat Vacuum Grayburg San Andres
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4041'

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other Water Injection	
2. Name of Operator Chevron U.S.A. INC.	
3. Address of Operator 15 Smith Road Midland, TX 79705	
4. Well Location Unit Letter <u>N</u> : <u>660</u> feet from the <u>South</u> line and <u>1980</u> feet from the <u>West</u> line Section <u>34</u> Township <u>17S</u> Range <u>34E</u> NMPM County <u>Lea</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4041'	

Approved for plugging of well bore only
Liability under bond is retained pending receipt of
C-103 (Specifically for Subsequent Report of Well
Plugging) which may be found at OCD web page
www.emnrd.state.nm.us/oed
TEMPORARY
PULL OR ALTER
DOWNHOLE COMMINGLE

SUBSEQUENT REPORT OF:	
REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐	P AND A ☒
CASING/CEMENT JOB ☐	
OTHER: ☐	OTHER: ☐

13. Describe proposed or completed operations. (state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/9/12 - Tag @ 4070' circ salt gel mud, test casing 500 psi.
3/12/12 - Spot 25 sx class C cement 4070 - 3826. Perf @ 2800', set pkr @ 2283'. Test 1500 psi. No bleed off. Notify NMOCDD.
3/13/12 - Spot 25 sx class C cement 2850'. WOC & TAG plug @ 2450'. Spot 25 sx class C 1610 - 1373.
3/14/12 - Spot 45 sx class C cement 410' - surface. Top off.
3/14/12 - Job Complete.

Spud Date:	Rig Release Date:
---------------------------------	--

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE <u>Matthew Brewer</u>	TITLE <u>Representative</u>	DATE <u>03-26-2012</u>
Type or print name <u>Matthew Brewer</u>	E-mail address: <u>mbrewer01@keyenergy.com</u>	PHONE: <u>432-523-5155</u>

APPROVED BY: <u>[Signature]</u>	TITLE <u>Dist. MGR</u>	DATE <u>11-15-2012</u>
Conditions of Approval (if any):		

NOV 15 2012