

District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

HOBBS OGD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

NOV 14 2012

WELL API NO. 30-025-30664
5. Indicate Type of Lease STATE ☐ FEE ☐ Fed
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Bilbrey 28 A Federal
8. Well Number 1
9. OGRID Number 6137
10. Pool name or Wildcat (96407) Bilbrey; Delaware, North

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other SWD-1325

2. Name of Operator
Devon Energy Production Co, LP

3. Address of Operator
333 W Sheridan Avenue, Oklahoma City, OK 73102

4. Well Location

Unit Letter K : 1980 feet from the South line and 1980 feet from the West line
Section 28 Township 21S Range 32E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3709 KB; 3683 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: SWD Conversion SWD-1325 ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/11/12-10/31/12: MIRU completion rig. POOH w/2-7/8" tubing & rod string. Drill out cement & CIBP @ 11,480'. Clean out & tag bottom @ 13,806'. Spot 25 sx Cl H cmt @ 13,750'. Tagged TOC @ 13,468'. Spot 9 ppg mud between plugs. Spot 70 sx Cl H cmt @ 12,150'. Tag TOC @ 11,404'. Spot 100 sx Cl H cmt @ 8,732'. Tag TOC @ 8,067'. Set CIBP @ 6,035'. Dump bail 35' cmt on top. Tag TOC @ 5,984'. Ran GR/CCL/CBL to surface. TOC @ 4,370'. Perforated Delaware Bell Canyon 2 SPF, .40 EHD, 60 deg phase @ 4785-4830; 4900-4940; 4977-4990; 5011-5073; 5207-5236; 5256-5300; 5700-5740; 5758-5800. TIH w/tubing and packer to 4,709'. Acidized Delaware Bell Canyon from 4785 to 5800 w/10,000 gal 15% HCl. Avg 5 BPM, 2600-2900# PSI. Pumped injection test at 1.01 BPM, 900 PSI, 1.04 BPM, 925 PSI. Shut down. POOH w/ packer and tubing. RIH hole w/148 JTS 2-7/8 tubing and packer. Set packer @ 4,716'. Rig down. Evaluate. Well will not be converted to SWD. Prepare to submit sundry to plug and abandon wellbore.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie Slack TITLE Operations Technician DATE 11-12-12

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dmn.com PHONE: 405-552-4615

For State Use Only

APPROVED BY [Signature] TITLE Dist. Mgr DATE 11-15-2012
Conditions of Approval (if any):

NOV 15 2012

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: BILBREY 28A FEDERAL #1		Field: BILBREY	
Location: 1980' FSL & 1980' FWL; SEC 28-T215-R32E		County: LEA	State: NM
Elevation: 3709' KB; 3683' GL; 26' KB to GL		Spud Date: 10/2/89	Compl Date: 2/2/90
API#: 30-025-30664	Prepared by: Ronnie Slack	Date: 11/8/12	Rev:

CURRENT WELLBORE-11/8/12

17-1/2" Hole
13-3/8", 48#, H40, STC, @ 626'
 Cmt'd w/450 sx C, tail w/250 sx C (circ)

TOC @ 4,360' (CBL-6/1/10)
 TOC @ 4,370' (CBL-10/26/12)

12-1/4" Hole
9-5/8", 40#, K55, STC, @ 4,650'
 Cmt'd w/3400 sx, tail w/200 sx (circ)

Delaware Bell Canyon SWD Perfs
 4785' - 4830'
 4900' - 4940'
 4977' - 4990'
 5011' - 5073'
 (perfed 10/27/12)

Sqzd csq leak @ 5138-5154 w/250 sx (5/26/10)

Delaware Bell Canyon SWD Perfs
 5207' - 5236'
 5256' - 5300'
 5700' - 5740'
 5758' - 5800'
 (perfed 10/26/12)

DELAWARE (6/1/10)
 8571' - 8611, 2 spf.
 acidized w/2000 gals 7.5% HCl, frac w/88K# sand

Top of 4-1/2" Liner @ 11,552'

8-3/4" Hole
7", 26# & 29#, P110 & S95, @ 12,097'
 Cmt'd w/1650 sx. TOC @ 5430' by temp survey

MORROW (3/23/90)
 13,902' - 13,912'

MORROW (2/2/90)
 14,279' - 14,498'

6" hole
4-1/2", 13.5#, J95, LTC, @ from 11,552' to 14,800'
 Cmt'd w/450 sx

