

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-35066
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-10629
7. Lease Name or Unit Agreement Name	Big Flat ASN State Com
8. Well No.	3
9. Pool name or Wildcat	Undesignated

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter 0 : 845 Feet From The South Line and 1980 Feet From The East Line Section 10 Township 16S Range 35E NM PM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3994' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4750'. Reached TD at 9:00 PM 7-17-2000. Ran 106 joints of 9-5/8" 36# & 40# (4756.45') of casing set at 4750'. Regular guide shoe set at 4750'. Float collar set at 4705'. Cemented with 1425 sacks Poz C (65-35), 6% gel, 5#/sack salt and 1/4#/sack celloflake (yield 2.03, weight 12.5). Tailed in with 200 sacks Class C with 1% CaCl2 (yield 1.34, weight 14.8). PD 1:00 PM 7-18-2000. Bumped plug, held okay. Circulated 176 sacks. WOC. Nipped up and tested to 5000# for 30 minutes, OK. Drilled out at 7:00 PM 7-19-2000. WOC 18 hours. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Rusty Klein TITLE: Operations Technician DATE: Oct. 31, 2000

TYPE OR PRINT NAME: Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY: _____ TITLE: _____ DATE: AUG 29 2001

CONDITIONS OF APPROVAL, IF ANY:

