

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-35066
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-10629
7. Lease Name or Unit Agreement Name	Big Flat ASN State Com
8. Well No.	3
9. Pool name or Wildcat	Undesignated

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter <u>0</u> : <u>845</u> Feet From The <u>South</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>10</u> Township <u>16S</u> Range <u>35E</u> NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3994' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, conductor, resume drilling, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 10:30 AM 7-2-2000. Drilled to 40'. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Sylvia w/OCD-Hobbs. Resumed drilling a 17-1/2" hole at 3:30 PM 7-4-2000.

TD 392'. Reached TD at 12:15 AM 7-5-2000. Ran 9 joints of 13-3/8" 48# H-40 ST&C (395.83') of casing set at 392'. 1-Texas Pattern notched guide shoe set at 392'. Insert float set at 350'. Cemented with 200 sacks of Poz C (65-35-6) and 5#/sack gilsonite (yield 1.95, weight 12.5). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.34, weight 14.8). PD 4:30 AM 7-5-2000. Bumped plug to 300 psi, OK. Circulated 72 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 12:30 AM 7-6-2000. WOC 20 hours. Reduced hole to 12-1/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Oct. 31, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY _____ TITLE Orig. Signed by Paul Kautz Geologist DATE AUG 29 2001

CONDITIONS OF APPROVAL, IF ANY:

