	t State of New Mexico	Form C-103
District I 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resource	well api No. 30-025-36-209
District II	OIL CONSERVATION DIVISION	30-253-674 9
1301 W. Grand Ave., Artesia, NM 8821 District III	1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	STATE X FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		0.0000000000000000000000000000000000000
SUNDRY NO (DO NOT USE THIS FORM FOR PRO DIFFERENT RESERVOIR. USE "APP PROPOSALS.)	OTICES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO PLICATION FOR PERMIT" (FORM C-101) FOR SUCH	
1. Type of Well: Oil Well X	Gas Well Other	8. Well Number 002
2. Name of Operator Chesapeal	se Operating, Inc.	9. OGRID Number 147179
3. Address of Operator P. O. E. Midlan	Box 11050 d, TX 79702-8050	10. Pool name or Wildcat D-K;Drinkard
4. Well Location		D-K,Dilikald
Unit Letter C	: 660 feet from the North line a	nd 1650 feet from the West line
Section 36	Township 20S Range 38E	NMPM CountyLea
	11. Elevation (Show whether DR, RKB, RT, G 3565 GR	R, etc.)
Pit or Below-grade Tank Application Pit type Depth to Groun	or Closure dwaterDistance from nearest fresh water well	Distance from nearest surface water
		bls; Construction Material
12 Check	Appropriate Box to Indicate Nature of N	
		•
	INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK [TEMPORARILY ABANDON [_ WORK □ ALTERING CASING □ □ CE DRILLING OPNS.□ P AND A □
		_
PULL OR ALTER CASING [EMENT JOB
	. —	_
OTHER: 13. Describe proposed or con	OTHER:Completed operations. (Clearly state all pertinent details	omplete Drinkard and DHC X ails, and give pertinent dates, including estimated date
OTHER: 13. Describe proposed or con	OTHER:Completed operations. (Clearly state all pertinent details	Domplete Drinkard and DHC
OTHER: 13. Describe proposed or completion. 10-21-04 RIH and set CP @ 7,2 and 230 jts. tbg to 7,029', circ 29 RIH w 3 1/8" csg. guns, perforat 10-22-04 RIH w/2 7/8" x 5 1/2' jts 2 7/8" tbg, set pkr @ 6,850', pm BPM, press. broke from 2400# bf flush w/30 bbls 2% KCL. RD C 10-29-04 Frac w/11,000 gals Liflush w/163 bbls 30# linear gel. 11-04-04 POOH w/20 jts. 2 7/8' pkr. RIH w/4 3/4" bit, BS, 6 - 3 2% KCL, clean out 35' sand to 11-05-04 RIH tag @ 7,510' bread 4 3/4" bit, RIH w 2 7/8" MA, 4' in 6,364' SN @ 6,947', ND BOP, so 11-06-04 RIH w/2 1/2" x 1 1/2" 11-07-04 Began testing	oTHER:Completed operations. (Clearly state all pertinent detayork). SEE RULE 1103. For Multiple Completion (10', load csg w/130 bbls 2% KCL, pressure CP to 26 KCL, spot 200 gals inhibited 15% neFe acid. Pose Drinkard 6,955 - 6,972, 6,977 - 6,981, 6,988 -	omplete Drinkard and DHC ails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion 2000# - OK. POOH w/WL, RIH w/ 2 7/8" SN OOH w/tbg and SN, load hole w/2%. RU WL, 2099, 7,004 - 7,012 @ 2 spf (80 holes) L-80 tbg to 6,900', rev. 10 bbls 2% KCL, pull 2 1000#, load tbg w/2 bbls 2% Pump into @ 1.7 neFe acid, launch 120 ball sealers, little ball action, 000 gals sand laden gel w/59,000# 20/40 sand, o kill, rel. pkr, POOH w/224 jts 2 7/8" tbg, SN and 5', RU rev. unit and swivel, break circ w/100 bbls 7,510'. , POOH w/240 tjs. 2 7/8" tbg, 6 - 3 1/2" DCs and 1/8" x 5 1/2" TAC and 208 jts 2 7/8" tbg, PAC @
OTHER: 13. Describe proposed or completion. 10-21-04 RIH and set CP @ 7,2 and 230 jts. tbg to 7,029', circ 29 RIH w 3 1/8" csg. guns, perforat 10-22-04 RIH w/2 7/8" x 5 1/2' jts 2 7/8" tbg, set pkr @ 6,850', pm BPM, press. broke from 2400# leftush w/30 bbls 2% KCL. RD C 10-29-04 Frac w/11,000 gals Lighlush w/163 bbls 30# linear gel. 11-04-04 POOH w/20 jts. 2 7/8" pkr. RIH w/4 3/4" bit, BS, 6 - 3 2% KCL, clean out 35' sand to C 11-05-04 RIH tag @ 7,510' bread 4 3/4" bit, RIH w 2 7/8" MA, 4' 6,364' SN @ 6,947', ND BOP, so 11-06-04 RIH w/2 1/2" x 1 1/2" 11-07-04 Began testing	mpleted operations. (Clearly state all pertinent deta work). SEE RULE 1103. For Multiple Completic 10', load csg w/130 bbls 2% KCL, pressure CP to 6 KCL, spot 200 gals inhibited 15% neFe acid. PC to 7 EP Completion 15% neFe acid. PC to 15%	omplete Drinkard and DHC ails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion 2000# - OK. POOH w/WL, RIH w/ 2 7/8" SN OOH w/tbg and SN, load hole w/2%. RU WL, 2099, 7,004 - 7,012 @ 2 spf (80 holes) L-80 tbg to 6,900', rev. 10 bbls 2% KCL, pull 2 1000#, load tbg w/2 bbls 2% Pump into @ 1.7 neFe acid, launch 120 ball sealers, little ball action, 000 gals sand laden gel w/59,000# 20/40 sand, o kill, rel. pkr, POOH w/224 jts 2 7/8" tbg, SN and 5', RU rev. unit and swivel, break circ-w/100 bbls 7,510'. , POOH w/240 tjs. 2 7/8" tbg, 6 - 3 1/2" DCs and 1/8" x 5 1/2" TAC and 208 jts 2 7/8" tbg, TAC @ Dowledge and belief. I further certify that any pit or belowermit or an (attached) alternative OCD-approved plan
OTHER: 13. Describe proposed or completion. 10-21-04 RIH and set CP @ 7,2 and 230 jts. tbg to 7,029', circ 29 RIH w 3 1/8" csg. guns, perforat 10-22-04 RIH w/2 7/8" x 5 1/2' jts 2 7/8" tbg, set pkr @ 6,850', pm BPM, press. broke from 2400# leftush w/30 bbls 2% KCL. RD C 10-29-04 Frac w/11,000 gals Lighlush w/163 bbls 30# linear gel. 11-04-04 POOH w/20 jts. 2 7/8" pkr. RIH w/4 3/4" bit, BS, 6 - 3 2% KCL, clean out 35' sand to C 11-05-04 RIH tag @ 7,510' bread 4 3/4" bit, RIH w 2 7/8" MA, 4' 6,364' SN @ 6,947', ND BOP, so 11-06-04 RIH w/2 1/2" x 1 1/2" 11-07-04 Began testing	oTHER:Completed operations. (Clearly state all pertinent detayork). SEE RULE 1103. For Multiple Completion (10', load csg w/130 bbls 2% KCL, pressure CP to 26 KCL, spot 200 gals inhibited 15% neFe acid. Pose Drinkard 6,955 - 6,972, 6,977 - 6,981, 6,988 -	omplete Drinkard and DHC ails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion 2000# - OK. POOH w/WL, RIH w/ 2 7/8" SN OOH w/tbg and SN, load hole w/2%. RU WL, 2099, 7,004 - 7,012 @ 2 spf (80 holes) L-80 tbg to 6,900', rev. 10 bbls 2% KCL, pull 2 1000#, load tbg w/2 bbls 2% Pump into @ 1.7 neFe acid, launch 120 ball sealers, little ball action, 000 gals sand laden gel w/59,000# 20/40 sand, o kill, rel. pkr, POOH w/224 jts 2 7/8" tbg, SN and 5', RU rev. unit and swivel, break circ-w/100 bbls 7,510'. , POOH w/240 tjs. 2 7/8" tbg, 6 - 3 1/2" DCs and 1/8" x 5 1/2" TAC and 208 jts 2 7/8" tbg, TAC @ Dowledge and belief. I further certify that any pit or belowermit or an (attached) alternative OCD-approved plan
OTHER: 13. Describe proposed or completion. 10-21-04 RIH and set CP @ 7,2 and 230 jts. tbg to 7,029', circ 29 RIH w 3 1/8" csg. guns, perforat 10-22-04 RIH w/2 7/8" x 5 1/2' jts 2 7/8" tbg, set pkr @ 6,850', pm BPM, press. broke from 2400# bf flush w/30 bbls 2% KCL. RD C 10-29-04 Frac w/11,000 gals Lifeliush w/163 bbls 30# linear gel. 11-04-04 POOH w/20 jts. 2 7/8" pkr. RIH w/4 3/4" bit, BS, 6 - 3 2% KCL, clean out 35' sand to C 11-05-04 RIH tag @ 7,510' brea 4 3/4" bit, RIH w 2 7/8" MA, 4' 6,364' SN @ 6,947', ND BOP, se 11-06-04 RIH w/2 1/2" x 1 1/2" 11-07-04 Began testing I hereby certify that the informating rade tank has been/will be constructed. SIGNATURE	mpleted operations. (Clearly state all pertinent deta work). SEE RULE 1103. For Multiple Completic 10', load csg w/130 bbls 2% KCL, pressure CP to 26 KCL, spot 200 gals inhibited 15% neFe acid. PC to 27 ke Drinkard 6,955 - 6,972, 6,977 - 6,981, 6,988 - 6	pomplete Drinkard and DHC ails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion 2000# - OK. POOH w/WL, RIH w/ 2 7/8" SN DOH w/tbg and SN, load hole w/2%. RU WL, 2099, 7,004 - 7,012 @ 2 spf (80 holes) L-80 tbg to 6,900', rev. 10 bbls 2% KCL, pull 2 1000#, load tbg w/2 bbls 2% Pump into @ 1.7 neFe acid, launch 120 ball sealers, little ball action, 000 gals sand laden gel w/59,000# 20/40 sand, by kill, rel. pkr, POOH w/224 jts 2 7/8" tbg, SN and 5', RU rev. unit and swivel, break circ w/100 bbls 7,510'. POOH w/240 tjs. 2 7/8" tbg, 6 - 3 1/2" DCs and 1/8" x 5 1/2" TAC and 208 jts 2 7/8" tbg, TAC @ Dowledge and belief. I further certify that any pit or belowermit or an (attached) alternative OCD-approved plan . llyst DATE 05/09/2005 Date of the date of t
OTHER: 13. Describe proposed or completion. 10-21-04 RIH and set CP @ 7,2 and 230 jts. tbg to 7,029', circ 29 RIH w 3 1/8" csg. guns, perforat 10-22-04 RIH w/2 7/8" x 5 1/2" jts 2 7/8" tbg, set pkr @ 6,850', pm BPM, press. broke from 2400# bf flush w/30 bbls 2% KCL. RD C 10-29-04 Frac w/11,000 gals Lifeliush w/163 bbls 30# linear gel. 11-04-04 POOH w/20 jts. 2 7/8" pkr. RIH w/4 3/4" bit, BS, 6 - 3 2% KCL, clean out 35' sand to C 11-05-04 RIH tag @ 7,510' bread 4 3/4" bit, RIH w 2 7/8" MA, 4' 6,364' SN @ 6,947', ND BOP, set 11-06-04 RIH w/2 1/2" x 1 1/2" 11-07-04 Began testing I hereby certify that the information of the set of	mpleted operations. (Clearly state all pertinent deta work). SEE RULE 1103. For Multiple Completic 10', load csg w/130 bbls 2% KCL, pressure CP to 26 KCL, spot 200 gals inhibited 15% neFe acid. PC to 27 ke Drinkard 6,955 - 6,972, 6,977 - 6,981, 6,988 - 6	ails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion 2000# - OK. POOH w/WL, RIH w/ 2 7/8" SN DOH w/tbg and SN, load hole w/2%. RU WL, 2999, 7,004 - 7,012 @ 2 spf (80 holes) L-80 tbg to 6,900', rev. 10 bbls 2% KCL, pull 2 1000#, load tbg w/2 bbls 2% Pump into @ 1.7 neFe acid, launch 120 ball sealers, little ball action, 000 gals sand laden gel w/59,000# 20/40 sand, 0 kill, rel. pkr, POOH w/224 jts 2 7/8" tbg, SN and 5', RU rev. unit and swivel, break circ w/100 bbls 7,510'. 0 POOH w/240 tjs. 2 7/8" tbg, 6 - 3 1/2" DCs and 1/8" x 5 1/2" TAC and 208 jts 2 7/8" tbg, PAC @ Dwledge and belief. I further certify that any pit or belowermit □ or an (attached) alternative OCD-approved plan □. Llyst DATE 05/09/2005