

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-36991

5. Indicate Type of Lease
STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____

b. Type of Completion:
NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER

2. Name of Operator
Amerada Hess Corporation

3. Address of Operator
P.O. Box 840 Seminole, Texas 79360

7. Lease Name or Unit Agreement Name
Fred Turner Jr. B

8. Well No.
9

9. Pool name or Wildcat
Skaggs Drinkard (57000)

4. Well Location
Unit Letter L : 1600 Feet From The South Line and 1310 Feet From The West Line

Section 17 Township 20S Range 38E NMPM Lea County

10. Date Spudded 1/9/2005 11. Date T.D. Reached 1/31/2005 12. Date Compl. (Ready to Prod.) 4/13/2005 13. Elevations (DF& RKB, RT, GR, etc.) 3563' 14. Elev. Casinghead

15. Total Depth 7705' 16. Plug Back T.D. 7070' 17. If Multiple Compl. How Many Zones? 18. Intervals Drilled By Rotary Tools Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name 6821'-6935' Skaggs Drinkard (57000) 20. Was Directional Survey Made No

21. Type Electric and Other Logs Run
Platform Express Three Detector Litho-Density Compensated Neutron
Platform Express High Resolution Laterolog Array, CBL 22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	1450'	11"	750 sx Class C	2435'
5 1/2"	17#	7090'	7 7/8"	1500 sx Class C/500 sx Class H	1507'

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	6770'	6761'

26. Perforation record (interval, size, and number)
Perf w/4" csg guns @ 3 SPF Skaggs Drinkard (57000) f/6821'-6823.8', 6841'-6843.9', 6857'-6859.9', 6873'-6875', 6892'-6895', 6917'-6920', 6937'-6935.1'

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
7089'-7705'	Acidized w/5900 gals 15% HCL Skaggs Blend
6821'-6935'	Acidized w/4500 gals 15% HCL
6821'-6935'	136,000 gals Spectra Star Frac 30# XL Borate

28. PRODUCTION & 300,000# 20/40 sand
Date First Production 4/13/2005 Production Method (*Flowing, gas lift, pumping - Size and type pump*) Flowing Well Status (*Prod. or Shut-in*) Producing

Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
4/27/2005	24			140	1145	118	8179
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
1000			140	1145	118	39	

29. Disposition of Gas (*Sold, used for fuel, vented, etc.*) Sold Test Witnessed By

30. List Attachments

C-102, C-103, C-104, Deviation Survey, Logs

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature Carol J. Moore Printed Name Carol J. Moore Title Senior Advisor Date 5/5/2005

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1400'	T. Canyon	
T. Salt	1500'	T. Strawn	
B. Salt	2700'	T. Atoka	
T. Yates		T. Miss	
T. 7 Rivers		T. Devonian	
T. Queen		T. Silurian	
T. Grayburg	3700'	T. Montoya	
T. San Andres	4000'	T. Simpson	
T. Glorieta	5380'	T. McKee	
T. Paddock		T. Ellenburger	
T. Blinbry	5860'	T. Gr. Wash	
T. Tubb	6370'	T. Delaware Sand	
T. Drinkard	6673'	T. Bone Springs	
T. Abo	6974'	T.	
T. Wolfcamp		T.	
T. Penn		T.	
T. Cisco (Bough C)		T.	

Northwestern New Mexico

T. Ojo Alamo_____	T. Penn. "B"_____
T. Kirtland-Fruitland_____	T. Penn. "C"_____
T. Pictured Cliffs_____	T. Penn. "D"_____
T. Cliff House_____	T. Leadville_____
T. Menefee_____	T. Madison_____
T. Point Lookout_____	T. Elbert_____
T. Mancos_____	T. McCracken_____
T. Gallup_____	T. Ignacio Otzte_____
Base Greenhorn_____	T. Granite_____
T. Dakota_____	T. _____
T. Morrison_____	T. _____
T. Todilto_____	T. _____
T. Entrada_____	T. _____
T. Wingate_____	T. _____
T. Chinle_____	T. _____
T. Permian_____	T. _____
T. Penn "A"_____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 3. from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
0	1400	1400	Red Beds
1500	2700	1200	Anhydrite
2700	3700	1000	Salt
3700	4000	300	Dolomite, Sand, Anhydrite
4000	6974	2974	Dolomite

From	To	Thickness In Feet	Lithology

Clear