State of New Mexico

Form C-103

Submit 3 copies to Appropriate District Office Energy, Minerals and Natural Resources Department Revised 1-1-89 DISTRICT I OIL CONSERVATION DIVISION WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-025-20329 DISTRICT II Santa Fe, New Mexico 87504-2088 Indicate Type of Lease P.O. Box Drawer DD, Artesia, NM 88210 STATE 🗸 FEE | DISTRICT III 6. State Oil / Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 B-270 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMI (FORM C-101) FOR SUCH PROPOSALS. VACUUM GLORIETA WEST UNIT OIL 1. Type of Well: ~ WELL WELL OTHER 2. Name of Operator 8. Well No. 46 **CHEVRON USA INC** Address of Operator 9. Pool Name or Wildcat 15 SMITH RD, MIDLAND, TX 79705 **VACUUM GLORIETA** 4. Well Location Feet From The South Line and 1650 990 Feet From The West Unit Letter_ Line Section 25 17S Range 34E NMPM _ Lea COUNTY Township. 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-4005' Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON REMEDIAL WORK PERFORM REMEDIAL WORK ALTERING CASING CHANGE PLANS COMMENCE DRILLING OPERATION PLUG AND ABANDONMENT TEMPORARII Y ARANDON CASING TEST AND CEMENT JOB PULL OR ALTER CASING ISOLATE SECTION IN OPEN HOLE LATERAL OTHER: OTHER: **V** 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 5-03-05: MIRU. SET PIPE RACKS & WS, 198 JTS 2 7/8". PU SHOE. CUT 6" FROM BTM, 3 3/4" JARS, DC'S ON 180 JTS 2 7/8" WS, TAG CIBP @ 5715. INSTL STRIPPER HEAD. 5-04-05: DRILLED IN CIBP @ 5715. TURN LOOSE CIRC. TIH W/80 JTS 2 7/8" WS TO 2500' FOR KILL STRING. 5-05-05: PU BIT, X-O SUB, & 185 JTS 2 7/8" WS TO END OF LATERAL @ 8237. NO FILL. TOH W/WS. WORK BIT & CLEAN UP. LD TBG. TIH W/80 JTS 2 7/8" WS. TOW - 5789. BOW- 5799. END OF LATERAL - 8237. TO ISOLATE VGSAU INTERVAL (OH PKR @ 5895, TOP PKR @ 5709 IN CSG). 5-06-05: TIH W/PKR, TBG, & SN. SET PKR. RU SWAB. KB CORRECTION 6.00'. 183 JTS 2 7/8" TBG 5700.22'. SN @ 5707. 5-09-05: RU SWAB, REL PKR & TOH W/TBG, TIH W/80 JTS 2 7/8" TBG. 5-10-05: WELL PRESS-0#. TIH W/BIT, TBG,. WORK BIT THRU WINDOW. WORK MILL @ 5789 TO 5799. CLEAN UP. TIH TO 5932 W/BIT & TO 5898' W/MILL. NO DRAG. PU PKR & TBG TO 1294. 5-11-05: TI W/146 JTS 2 7/8" TBG. SET PKR. TEST CSG TO 500#-15 MINS - G00D. RU SWAB. SN @ 5696. PROFILE NIPPLE @ 5698. PKR @ 5706. MIDDLE OF 4 1/4" OPEN HOLE PKR SET @ 5865. 5-12-05: RU SWAB. INSTL HANGER FLANGE. SET W/10,000# TENSION. PULLED INTO PKR. TEST CSG TO 500#. GOOD. RIG DOWN. **FINAL REPORT**

Regulatory Specialist TITLE SIGNATURE (DATE 5/16/2005 Telephone No. 432-687-7375 Denise Pinkerton TYPE OR PRINT NAME

APPROVED

OC FIELD REPRESENTATIVE II/STAFF MANAGER

MAY 1 8 2005