

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
March 4, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-36595
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Top Hat 19 State
8. Well Number 1
9. OGRID Number
10. Pool name or Wildcat Hat Mesa, Morrow Gas

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
EOG Resources, Inc

3. Address of Operator
P.O. Box 2267, Midland, TX, 79702

4. Well Location
Unit Letter K : 1902 feet from the South line and 1405 feet from the West line
Section 19 Township 21-S Range 33-E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-144 must be attached)

Pit Location: UL K Sect 19 Twp 21S Rng 33E Pit type Steel Depth to Groundwater 180 Distance from nearest fresh water well Over 1000'
Distance from nearest surface water Below-grade Tank Location UL Sect Twp Rng
1902 feet from the South line and 1405 feet from the West line (Steel Tank)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/> PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: <input type="checkbox"/>

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MI P&A Equip.
2. Spot 35sx Class H CMT @ 13,980'. Tag Toc @ 13,559' 5-5-05. Disp Well W/MLF. 5-5-05
3. Spot 50sx Class H CMT @ 12,150. 5-5-05 Tag Toc @ 11,668. 5-6-05
4. Spot 45sx Class H CMT 8000-7800. 5-6-05
5. Spot 50sx Class H CMT @ 5300. 5-6-05 Tag Toc @ 5079. 5-9-05
6. Cut Csg. @ 4730 Pull Csg Slips est Free Point @ 1500 Spot 550sx Class C CMT @ 4780 5-12-05. Tag @ 1630 5-13-05.

7. Perf @ 1495 -1400. Spot 62sx Class C Cmt @ 1630 5-13-05.
8. Perf @ 1250 M&P 36sx Class C CMT Squeezed 19sx out @ 1250 5-13-05. Tag TOC @ 1173 5-16-05.
9. Perf @ 260 Circ 90sx Class C CMT Down 7" Csg. out @ 260 & up 7x 9 5/8 Ann to Surf. 5-16-05.
10. Tag Toc @ Surf. CMT off W/H Install Dry Hole Marker P&A Complete 5-16-05

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Jimmy Bagley TITLE Consultant DATE 5/16/05
Type or print name Jimmy Bagley E-mail address: sunsetwellsservice@yahoo.com Telephone No. 432-561-8600

(This space for State use)

APPROVED BY Gayle W. Wink TITLE FIELD REPRESENTATIVE II/STAFF MANAGER DATE MAY 24 2005
Conditions of approval, if any

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.