

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-27254
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Mae F. Curry
8. Well Number 1
9. OGRID Number 000778
10. Pool name or Wildcat Eunice Monument Grbg SA

Pit or Below-grade Tank Application ☐ or Closure ☐
Pit type **STEEL** Depth to Groundwater **85'** Distance from nearest fresh water well **>1000'** Distance from nearest surface water **>1000'**
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐
2. Name of Operator
B P America Production Company
3. Address of Operator
P.O. Box 1610, Midland, TX 79702
4. Well Location
Unit Letter **B** : **660** feet from the **North** line and **1980** feet from the **East** line
Section **7** Township **21S** Range **37E** NMPM County **Lea**
11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3508' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: **Replace version from 4/27/05**

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Establish injection rate down tubing and into ports 4010-4267'. Pump 25sx cmt and displace to 3800'. RU WL unit. Tag TOC no deeper than 3910'. Cut 2 7/8" tubing at 3624'. POOH with 2 7/8" tbg. GIN w/ CIBP on 2 7/8" tbg and set at 3600'. Spot 25sx cmt on CIBP. WOC and tag no deeper than 3500'. Displace the hole w/ 9.5# viscous mud. Pick up to 2850' and spot 25sx cement. Pick up to 1380' and spot 30sx cement. WOC and tag no deeper than 1175'. Pick up to 400' and spot 25sx cement. Spot 10sx cmt at surface. cut off wellhead and anchors. Install P&A marker.

TAG

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE **Dan L. Tuffly** TITLE **Consulting Engineer** DATE **5/24/05**

Type or print name **Dan L. Tuffly** E-mail address: **tuffldl@bp.com** Telephone No. **(432) 688-5207**
For State Use Only

APPROVED BY: **Larry W. Wink** TITLE **FIELD REPRESENTATIVE II/STAFF MANAGER** DATE **MAY 31 2005**
Conditions of Approval (if any):

MAY 31 2005

THE OIL CONSERVATION DIVISION MUST
BE NOTIFIED 24 HOURS PRIOR TO THE
BEGINNING OF PLUGGING OPERATIONS.

RKB 3520'
GL 3508'

MAE F. CURRY # 1

Eunice Monument Field

660' FNL & 1980' FEL, Section 7

Unit Letter B

T-21-S, R-37-E

Lea County, New Mexico

API # 30-025-27254

Original Spud 11/1/81
Spud on Deepening
7/1/2002

Completion in Grayburg
San Andres 8/15/02

8 5/8", 24#, K-55 @ 1225'
Cmt w/ 650 sx to surface

112 joints 2 7/8", 6.5#, L-80, IPC, EUE 8rd tubing
2 7/8" x 3 1/2" Changeover screwed into 3 1/2" liner

Top of liner @ 3624'

TOC on 3 1/2" @ 3664'

Yates-Seven Rivers-Queen

3625, 27, 39, 42, 46, 50, 55, 59, 3662' 9 shots

3665' 1 shot

3687, 94, 3701, 04, 07, 12, 15, 28, 36, 3753' 10 shots

5 1/2", 15.5#, K-55 @ 3850'
Cmt w/ 1220 sx to surface

Grayburg-San Andres

4010' 4 shots

4162' 4 shots

4198', 4218', 4267' 12 shots

3 1/2", 9.3#, L-80, EUE 8rd @ 3624-4497'
Cmt w/ 50 sx
TOC 3664' by CBL

TD 4500'

PBTD 4462'