

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-27954
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Mae F. Curry
8. Well Number 2
9. OGRID Number 000778
10. Pool name or Wildcat Eunice Monument Grbg SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐	
2. Name of Operator BP America Production Company	
3. Address of Operator P.O. Box 1610, Midland, TX 79702	
4. Well Location Unit Letter A : 330 feet from the North line and 660 feet from the East line Section 9 Township 21S Range 37E NMPM County Lea	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3526' GR	
Pit or Below-grade Tank Application ☐ or Closure ☐	
Pit type STEEL Depth to Groundwater 85' Distance from nearest fresh water well >1000' Distance from nearest surface water >1000'	
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: **Replace version from 4/27/05** ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

POOH w/tubing. G/H with cement retainer on 2 3/8" tubing and set at 3620'. Establish injection rate into both Grayburg and Yates perms. Squeeze 35 sx cmt below the retainer. Repeat until get walking squeezer. Spot 25 sx cmt on retainer. WOC and tag no deeper than 3520'. Displace the hole with 9.5 # viscous mud. Pick up to 2850' and spot 25 sx cmt. Pick up to 1380' and spot 25 sx cmt. WOC and tag no deeper than 1280'. Pick up to 487' and spot 25 sx cement. Spot 10 sx cmt at surface. Cut off wellhead and anchors. Install P&A marker.
TAG ←

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE **Dan L Tuffly** TITLE **Consulting Engineer** DATE **5/24/05**

Type or print name **Dan L Tuffly** E-mail address: **tuffldl@bp.com** Telephone No. **(432) 688-5207**
For State Use Only

APPROVED BY: **Larry W. Wink** FIELD REPRESENTATIVE II/STAFF MANAGER DATE **MAY 31 2005**
Conditions of Approval (if any):

THE OIL CONSERVATION DIVISION MUST
BE NOTIFIED 24 HOURS PRIOR TO THE
BEGINNING OF PLUGGING OPERATIONS.

RKB 3538'
GL 3526'

MAE F. CURRY # 2

Eunice Monument Field

330' FNL & 660' FEL, Section 7

Unit Letter A

T-21-S, R-37-E

Lea County, New Mexico

API # 30-025-27954

Original Spud 11/18/82
Spud on Deepening
7/1/2002

Completion in Grayburg
San Andres July 2002

8 5/8", 24#, K-55 @ 437'
Cmt w/ 175 sx
Top out to surface w/ 50 sx

2 3/8", 4.7#, J-55 tubing
Rods & pump

Backed off the 3 1/2"
to leave

Top of liner @ 3676'

Yates-Seven Rivers-Queen

3656, 58, 62, 70, 3674'

5 shots

TOC on 3 1/2" @ 3686'

3678, 3685'

2 shots

3690, 94, 98, 3700, 08, 3713'

6 shots

3733, 38, 43, 47, 58, 65, 67, 83, 85, 3802'

10 shots

5 1/2", 15.5#, K-55 @ 3850'
Cmt w/ 1230 sx to surface

Grayburg-San Andres

4032' 4 shots

4138' 4 shots

4206' 4 shots

4226' 4 shots

4259' 4 shots

3 1/2", 9.3#, L-80, EUE 8rd @ 3676-4497'
Cmt w/ 60 sx
TOC 3686' by CBL

TD 4500'

PBTD 4470'