

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-33755
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VA-0492
7. Lease Name or Unit Agreement Name Sawyer AQN State
8. Well Number 2
9. OGRID Number 025575
10. Pool name or Wildcat Sawyer San Andres, West

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Yates Petroleum Corporation	
3. Address of Operator 105 S. 4 th Street, Artesia, NM 88210	
4. Well Location Unit Letter <u>A</u> : <u>810</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>East</u> line Section <u>6</u> Township <u>10S</u> Range <u>37E</u> NMPM Lea County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3984'GR	

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type Steel Depth to Groundwater >100' Distance from nearest fresh water well N/A Distance from nearest surface water N/A

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDON ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Propose to plug & abandon well as follows:

- 1) MIRU WSU. RU safety trailer and ND WH. NU BOP.
- 2) Set 5-1/2" CIBP @ 4850' and dump 35' cement on plug.
- 3) Circulate hole w/9.5# mud.
- 4) Perforate squeeze holes @ 2918' and spot 100' cement plug in and out of casing 2818-2918' w/40 sx. Tag plug.
- 5) Perforate squeeze holes @ 520' and spot 100' cement plug in and out of casing 420-520' w/40 sx. Tag plug.
- 6) Shoot squeeze holes @ 60'.
- 7) Spot 60' cement plug in and out of casing to surface. Tag plug.
- 8) Cut off wellhead and install marker.
- 9) Clean up location as per regulations.

(Proposed schematic attached.)

Yates Petroleum Corporation will use steel pits, and no earth pits.

THE OIL CONSERVATION DIVISION MUST
BE NOTIFIED 24 HOURS PRIOR TO THE
BEGINNING OF PLUGGING OPERATIONS.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Stormi Davis TITLE Regulatory Compliance Technician DATE 5-24-05

Type or print name Stormi Davis E-mail address: stormid@ypcnm.com Telephone No. 505-748-1471

For State Use Only
APPROVED BY: Harry W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE MAY 31 2005

Conditions of Approval (if any):

OPERATOR: Yates Petroleum Corporation

WELL NAME: Sawyer AQN St. # 2

FIELD:

LOCATION: 810' FNL & 660' FEL, Sec 6-10S-37E

COUNTY: Eddy

GL: 3984' ZERO: KB: 3997'


SPUD DATE: 1/10/97 COMPLETION DATE: 4/13/97

COMMENTS: API No. 30-025-33755

CASING PROGRAM

8 5/8" 24# J-55	470'
5 1/2" 15.5# J-55 LT&C	5090'

12 1/4" Hole




Surface Plug (20 sx)
60' to surface In & out of casing

8 5/8" @ 470'
w/ 325 sx

Casing Shoe Plug (40sx)
520'-420' In & out of casing

7 7/8" Hole



Yates Plug (40sx)
2918'-2818' In & out of casing

TOC 4020' CBL


Tops

Rustler	2236'
Yates	2868'
San Andres	4156'

CIBP @4,850' w/ 35' cmt on top

4,900'-4,954' (15)
Acidized w/ 4,000 gallons
Fraced w/ 50,000# sand

5 1/2" @ 5,090'
w/ 250 sx (circ)



PBTD 5,046'
TD 5,090'

Not to Scale