<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144

June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

office

| Pit or Below-Grade | Tank l | Registra | ation o | <u>r Closure</u> |
|--------------------|--------|----------|---------|------------------|
| | | | | |

| Type of action: Registration of a pit | or below-grade tank [Closure of a pit or below-grade tan | tank X | | |
|--|--|--|--|--|
| Operator: Yates Petroleum Company Telephone: 505-748-4500 e-mail a Address: 105 South 4th Street, Artesia, N.M. 88210 Facility or well name: Sand Springs ASU State 3 API #: 30-025-34861 U/L County: Lea Latitude: 33.37707 Longitude: 103. | or Qtr/Qtr <u>J</u> Sec <u>11 T 11S</u> R <u>34E</u> | 31118192027 | | |
| Surface Owner: Federal State _X Private Indian | | | | |
| Pit Type: Drilling X Production □ Disposal □ Work over □ Emergency □ Lined X Unlined □ Liner type: Synthetic □ Thickness 12 mil Clay □ Pit Volume 12,000 bbl | Below-grade tank Volume: bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes | | | |
| Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.) | Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more | (20 points) XXXX (10 points) (0 points) | | |
| Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.) | Yes No | (20 points) (0 points) XXXX | | |
| Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.) | Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more | (20 points) (10 points) (0 points) XXXX | | |
| | Ranking Score (Total Points) | 20 points | | |
| Groundwater encountered: No 🗌 Yes 🛄 If yes, show depth below ground surf | (3) Attach a general description of remedial action taken in accft. and attach sample results. | | | |
| (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: Closure work plan for drilling pit. An encapsulation trencontents will be excavated and emplaced into the encapsulation trench using a cement will be mixed using a track hoe and water added if needed. After completencapsulation trench will then be capped using a 20 mil synthetic liner and back of the made before pit closure action begins. Beginning pit closure date: | nch will be constructed and lined with 12 mil synthetic line mixture of two to one pit material and Class H bulk cemer letion of solidifying pit material in cement and pit contents kfilled to grade using a minimum of 3' of like material and | nt or CKD. The emulsion of pit material and have set in place for a minimum of 24 hours, the | | |
| AMENDMENT TO PREVIOUS C-144 DATED 3/10/05 | | | | |
| I hereby certify that the information above is true and complete to the best of m been/will be constructed or closed according to NMOCD guidelines, a g Date: 05/31/05 Printed Name/Title Dolan / Regulatory Agent Your certification and NMOCD approval of this application/closure does not re endanger public health or the environment. Nor does it relieve the operator of | Signature Signature of liability should the contents of the pi | t or tank contaminate ground water or otherwise | | |
| Approval: Printed Name/Title GARY W. Signature OCTIGINAL SIGNED BY GARY W. WINK OC FIELD REPRESENTATIVE IL/STAFF MANAGER Signature Date: JUN 0 1 2005 | | | | |