

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
New Mexico Oil Conservation Division, District 1
1625 N. French Drive
Albuquerque, NM 88240

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Occidental Permian Ltd.

157984

3a. Address

P.O. Box 50250, Midland, TX 79710-0250

3b. Phone No. (include area code)

432-685-5717

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

680 FNL 808 FEL SESE(A) SEC 22 T24S R37E

5. Lease Serial No.

LC060579

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or
South Mattix Unit Federal

8. Well Name and No.

28

9. API Well No.

30-025-25613

10. Field and Pool, or Exploratory Area
Fowler; Upper Paddock

11. County or Parish, State

Lea NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☒ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☐ Other

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompletable horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zone. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletable in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

See Other Side

Approved as to plugging of the well and
liability under bond is retained until
surface restoration is completed.



14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

David Stewart

Title

Sr. Regulatory Analyst

Date

5/27/05

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

DAVID R. CLARK

Title

PETROLEUM ENGINEER

Date

JUN 06 2005

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

SOUTH MATTIX UNIT FEDERAL #28

05/12/2005 CMIC: Davis

Notified BLM. MIRU Triple N rig #25 & plugging equipment. Set steel pit. Dug out surface casing valve, ND wellhead, NU BOP. POOH w/ 18 jts tbg. RIH w/ 158 jts 2 7/8" workstring, tagged CIBP @ 4,750'. RU cementer and circulated hole w/ mud, POOH w/ 45 jts tbg to 3,399'. Pumped 25 sx C cmt 3,399 - 3,151'. POOH w/ tbg to 2,464' and pumped 25 sx C cmt 2,464 - 2,216'. POOH w/ tbg. RIH w/ wireline and perforated @ 1,068', POOH w/ wireline. RIH w/ packer to 686'. Loaded hole and set packer, established rate of 1 BPM @ 1,200 psi and squeezed 40 sx C cmt w/ 2% CaCl2 @ 1,068', ISIP 400 psi. WOC 3 hrs and RIH w/ wireline, tagged cmt @ 913'. POOH w/ wireline, POOH w/ packer. SDFN.

05/13/2005 CMIC: Davis

RIH w/ wireline and perforated @ 300', POOH w/ wireline. ND BOP and NU wellhead, established circulation via perforations and squeezed 80 sx C cmt 300' to surface, circulating cement. RDMO. BLM rep Jim McCormick witnessed plugs and tags.

RECEIVED
MAY 13 2005

2005 MAY 13 AM 10:25

RECEIVED