

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 9638 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing May 26, 1953

OIL WELL: The production during the first 24 hours was 50 barrels of liquid of which 100 % was
was oil; none % was emulsion; none % water, and none % was sediment. A.P.I.
Gravity 47.1 corrected

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.	2220	T. Devonian	T. Ojo Alamo
T. Salt	2515	T. Silurian	T. Kirtland-Fruitland
B. Salt	2710	T. Montoya	T. Farmington
T. Yates	2785	T. Simpson	T. Pictured Cliffs
T. 7 Rivers		T. McKee	T. Menefee
T. Queen		T. Ellenburger	T. Point Lookout
T. Grayburg		T. Gr. Wash.	T. Mancos
T. San Andres	4040	T. Granite	T. Dakota
T. Glorieta	5486	T.	T. Morrison
T. Drinkard	6929	T.	T. Penn.
T. Tubbs		T.	T.
T. Abo	7672	T.	T.
T. Wolfcamp	8910	T.	T.
T. Bunch (C) Limestone	9616	T.	T.
T. Mm		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	395	395	Sand & Red Bed	9487	9509	22	Lime
395	2220	1825	Red Bed	9509	9616	107	Lime & Shale
2220	2272	52	Anhydrite	9616	9638	22	Lime
2272	3397	1125	Anhydrite & Salt				
3397	4062	665	Anhydrite				
4062	4917	855	Lime				
4917	5284	367	Lime & Shale				
5284	6476	1192	Lime				
6476	6818	342	Lime & Shale				
6818	7444	626	Lime				
7444	7674	230	Lime, Shale, Lime, Gyp				
7674	7700	26	Lime & Shale				
7700	7842	142	Shale				
7842	7908	64	Lime & Shale				
7908	8098	192	Shale				
8098	8161	63	Shale & Lime				
8161	8717	556	Shale & Lime & Shale				
8717	8737	20	Lime				
8737	8765	18	Lime & Shale				
8765	8952	187	Lime				
8952	8966	14	Lime & Chert				
8966	9476	509	Lime				
9476	9487	12	Lime & Shale				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 10, 1953

Company or Operator: Bryan P. Corp. Oil Div.

Address: Drawer H, Seminole, Texas

Name: C. R. Kamm

Position or Title: Superintendent