

New Mexico Oil Conservation Division, District I
1625 N. French Drive
Hobbs, NM 88240

Form 3160-3
(April 2004)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED
OMB No. 1004-0137
Expires March 31, 2007

5. Lease Serial No.
NM-18306

6. If Indian, Allottee or Tribe Name

1a. Type of work: ☒ DRILL ☐ REENTER

7. If Unit or CA Agreement, Name and No.

1b. Type of Well: ☐ Oil Well ☒ Gas Well ☐ Other ☒ Single Zone ☐ Multiple Zone

8. Lease Name and Well No.
Paloma Blanco 20 Federal 1 34880

2. Name of Operator
Devon Energy Production Company, LP 6137

9. API Well No.
30-025-37295

3a. Address 20 North Broadway
Oklahoma City, Oklahoma City 73102-8260

3b. Phone No. (include area code)
405-552-8198

10. Field and Pool, or Exploratory
Bell Red Lake, Morrow, Mid (Gas) 72000

4. Location of Well (Report location clearly and in accordance with any State requirements.)

At surface 660 FSL & 660 FWL

At proposed prod. zone 660 FSL & 660 FWL

11. Sec., T. R. M. or Blk. and Survey or Area

Sec 20, T23S R34E

14. Distance in miles and direction from nearest town or post office*
20 miles west of Jal, NM

12. County or Parish

Lea County

13. State

NM

15. Distance from proposed*
location to nearest
property or lease line, ft.
(Also to nearest drig. unit line, if any)

16. No. of acres in lease

640 acres

17. Spacing Unit dedicated to this well

320 acres

18. Distance from proposed location*
to nearest well, drilling, completed,
applied for, on this lease, ft.

19. Proposed Depth

14,000

20. BLM/BIA Bond No. on file

21. Elevations (Show whether DF, KDB, RT, GL, etc.)
3562' GL

22. Approximate date work will start*

07/01/2005

23. Estimated duration

55 days

24. Attachments

CARLSBAD CONTROLLED WATER BASIN

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).

4. Bond to cover the operations unless covered by an existing bond on file (see item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature

Title

Sr. Staff Eng. Tech

Name (Printed/Typed)

Norvella Adams

Date

05/05/2005

Approved by (Signature)

/s/ Joe G. Lara

Name (Printed/Typed)

/s/ Joe G. Lara

Date

JUN 15 2005

Title

ACTING FIELD MANAGER

Office

CARLSBAD FIELD OFFICE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

APPROVAL FOR 1 YEAR

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on page 2)

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS
AND SPECIAL STIPULATIONS
ATTACHED

DECLARED WATER BASIN 3/8'
CEMENT BEHIND THE 13/8'
CASING MUST BE CIRCULATED

WITNESS

KZ

Additional Operator Remarks:

Devon Energy Production Company, LP proposes to drill a Morrow well to 14,400' for commercial quantities of oil and gas. If the well is deemed noncommercial, the wellbore will be plugged and abandoned per Federal regulations. Programs to adhere to onshore oil and gas regulations are outlined in the following exhibits and attachments.

Approximately 54' of new access road will need to be constructed.

DISTRICT I

1625 N. French Dr., Hobbs, NM 88240

State of New Mexico

Energy, Minerals and Natural Resources Department

Form C-102

Revised March 17, 1999

DISTRICT II

811 South First, Artesia, NM 88210

Submit to Appropriate District Office

State Lease - 4 Copies

Fee Lease - 3 Copies

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 South Pacheco

DISTRICT IV

2040 South Pacheco, Santa Fe, NM 87505

Santa Fe, New Mexico 87504-2088

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 30-025-37295	Pool Code 72000	Pool Name Bell Red Lake, Morrow, Mid (Gas)
Property Code 34880	Property Name PALOMA BLANCO "20" FEDERAL	Well Number 1
GRID No. 6137	Operator Name DEVON ENERGY PRODUCTION CO., L.P.	Elevation 3562'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	20	23 S	34 E		660	SOUTH	660	WEST	LEA

Bottom Hole Location If Different From Surface


UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County

Dedicated Acres 320	Joint or Infill	Consolidation Code	Order No.
-------------------------------	-----------------	--------------------	-----------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	OPERATOR CERTIFICATION I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief. Signature Norvella Adams Printed Name Sr. Staff Eng. Tech. Title May 5, 2005 Date
	SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. APRIL 21, 2005 Date Surveyed. JONES Signature & Seal of Professional Surveyor W.O. No. 5353 Certificate No. Gary L. Jones 7977 BASIN SURVEYS

SECTION 20, TOWNSHIP 23 SOUTH, RANGE 34 EAST, N.M.P.M.,
LEA COUNTY, NEW MEXICO.



Directions to Location:

FROM THE JUNCTION OF CO. RD. E-21 & STATE HWY 128, GO NORTH ON DELAWARE BASIN ROAD FOR 4.9 MILES TO LEASE ROAD; THENCE EAST ON LEASE ROAD FOR 0.8 MILE TO PROPOSED LEASE ROAD.

BASIN SURVEYS P.O. BOX 1786 - HOBBS, NEW MEXICO

W.O. Number: 5334 Drawn By: K. GOAD


Date: 04-25-2005 Disk: KJG CD#4 - 5334A.DWG

DEVON ENERGY PROD. CO., L.P.


REF: PALOMA BLANCO "20" FED. No. 1 / Well Pad Topo

THE PALOMA BLANCO "20" FED. No. 1 LOCATED 660'
FROM THE SOUTH LINE AND 660' FROM THE WEST LINE OF
SECTION 20, TOWNSHIP 23 SOUTH, RANGE 34 EAST,
N.M.P.M., LEA COUNTY, NEW MEXICO.

Survey Date: 04-21-2005 Sheet 1 of 1 Sheets



PALOMA BLANCO "20" FEDERAL #1
 660' FSL AND 660' FWL
 Section 20, Township 23 South, Range 34 East,
 N.M.P.M., Lea County, New Mexico.



P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (505) 393-7316 - Office
 (505) 392-3074 - Fax
 basinsurveys.com

W.O. Number: 5334AA - KJG CD#4

Survey Date: 04-21-2005

Scale: 1" = 2 MILES

Date: 04-25-2005

DEVON ENERGY
 PROD. CO., L.P.

DRILLING PROGRAM

Devon Energy Production Company, LP
PALOMA BLANCO 20 FEDERAL 1
(M) 660' FSL & 660' FWL, Section 20, T-23-S, R-34-E
Lea County, New Mexico

1. **Geologic Name of Surface Formation**

Alluvium

2. **Estimated Tops of Important Geologic Markers**

Rustler	1,050'
Salt	4,454'
Delaware	5,000'
Bone Spring	8,600'
Wolfcamp	10,600'
Strawn	11,900'
Atoka	12,300'
Morrow	12,900'
TD	14,000'

3. **Estimated Depths of Anticipated Fresh Water, Oil or Gas**

The estimated depths at which water, oil and gas will be encountered are as follows.

Water:	None expected in area
Oil	Bone Spring @ 9,100'
Gas:	Upper Morrow @ 13,100'

4. Casing Program

<u>INTERVALS</u>	<u>LENGTH</u>	<u>CASING</u>
<u>Surface</u> 0 – 1075'	1075	13 3/8" 48# H-40 STC
<u>Intermediate</u> 0 – 5000'	5000'	9 5/8" 40#N-80 & HCK-55 LT&C
<u>Production</u> 0 – 11800 12000	11800 12000	7" 26# HCP-110 LTC
<u>Liner</u> 11800 – 14000'		4 1/2" 13.5# P-110 LTC

Cementing Program

<u>HOLE SIZE</u>	<u>DEPTH</u>	<u>CEMENT</u>	<u>TOC</u>	<u>WOC HRS</u>
<u>Surface</u> 17 1/2"	1075'	Lead: 350 sxs 35/65 POZ + 6% gel + 1/4#/sx celloflk (12.7#/gal) Tail: 200 sxs Cl "C" + 2% CaCl ₂	Surf.	12
<u>Intermediate</u> 12 1/4"	5000'	Lead: 1200 sxs 50/50 POZ + 10% gel 5% salt + 1/4#/sx celloflk (12.7#/gal)	Surf.	12
<u>Production</u> 8 3/4"	11,800 12000	Lead: 300 sx Light Tail: 300 sx Class H	6000	24
<u>Liner</u> 6 1/8"	11,800 – 14,000	Cmt w/250 sx Class H		

The cement volumes for the 4 1/2" liner will be revised pending the caliper measurement from the open hole logs.

5. Minimum Specifications for Pressure Control

The blowout preventer equipment (BOP) shown in Exhibit #1 A Blow-out Preventer (5,000/10,000 PSI working pressure) consisting of double ram type preventor and bag type preventer. Units will be hydraulically operated. See Exhibit #2 for Choke Manifold and Closing Unit. Blind rams on top, pipe rams on bottom to correspond with size of drill pipe in use. BOP will be tested as well as choke manifold. BOP will be worked at least once each day while drilling & blind ram will be worked on trips when no drill pipe is in hole. Full opening stabbing valve and upper Kelly cock will be utilized. Anticipated BHP 8000 psi and 190° BHT.

Pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These functional tests will be documented on the daily drillers log. A 2" kill line and 3" choke line will be incorporated in the drilling spool below the ram-type BOP. Other accessory BOP equipment will include a kelly cock, floor safety valve, choke lines and choke manifold having 8000 psi WP rating.

6. Types and Characteristics of the Proposed Mud System

The well will be drilled to total depth brine with starch mud systems. Depths of systems are as follows.

<u>Depth</u>	<u>Type</u>	<u>Weight (ppg)</u>	<u>Viscosity (1/sec)</u>	<u>Water Loss (cc)</u>
0' – 2000'	Fresh Water	8.5	40	No control
2000' – 5200'	Fresh Brine	10	28-30	No control
5200' – 12,000'	Cut Brine	9.0 – 9.2	28-30	No control
12,000' – TD	Cut Brine/Starch	9.8 – 13	38-40	6- 10

The necessary mud products for weight addition and fluid loss control will be on location at all times.

7. Auxiliary Well Control and Monitoring Equipment

A. A kelly cock will be in the drill string at all times.

B. A full opening drill pipe stabbing valve having the appropriate connections will be on the rig floor at all times.

8. Logging, Testing and Coring Program

- A. Drill stem tests may be run on potential pay interval.
- B. The open hole electrical logging program will be as follows.
 - 1) DLL/MSFL/GR from total depth to base of intermediate casing.
 - 2) CNL/LDT/GR from total depth to base of intermediate casing with CNL/GR to surface.
- C. No coring program is planned.
- D. Additional testing will be initiated subsequent to setting the 4 1/2" production liner. Specific intervals will be targeted based on log evaluation, geological sample shows and drill stem tests.

9. Abnormal Pressures, Temperatures and Potential Hazards

No abnormal pressures or temperatures are foreseen. The anticipated bottom hole temperature at total depth is 190 degrees and maximum bottom hole pressure is 8000 psi. No Hydrogen sulfide or other hazardous gases or fluids have been encountered, reported or are known to exist at this depth in this area. No major loss circulation intervals have been encountered in adjacent wells.

10. Anticipated Starting Date and Duration of Operations

Road and location preparation will not be undertaken until approval has been received from the BLM. If approved, this well will be drilled as part of a development project. The drilling operation should require approximately 55 days. If the well is deemed productive, completion operations will require, at minimum, an additional 30 days of testing to ascertain whether permanent production facilities will be constructed.

SURFACE USE AND OPERATING PLAN

Devon Energy Production Company, LP
PALOMA BLANCO 20 FEDERAL 1
(M) 660' FSL & 660' FWL, Section 20, T-23-S, R-34-E
Lea County, New Mexico

1. Existing Roads

- A. The well site and elevation plat for the proposed well are reflected on Exhibit #2. This well was staked by Basin Surveys in Hobbs, NM.
- B. All roads into the location are depicted in Exhibit #3. New construction from the existing lease road will be used to access the location. New construction will conform to the specifications outlined in Item #2 below.
- C. Directions to location: From the junction of Co. Rd. E-21 & State Hwy 128, go North on Delaware Basin Road for 4.9 miles to lease road; thence east on lease road for 0.8 mile to proposed well lease road.

2. Proposed Access Road

Exhibit #3 shows the existing lease road. Access to this location will require the construction of about 54' of proposed access road. All new construction will adhere to the following.

- A. The maximum width of the road will be 15'. It will be crowned and made of 6" of rolled and compacted caliche. Water will be deflected, as necessary, to avoid accumulation and prevent surface erosion.
- B. Surface material will be native caliche. This material will be obtained from a BLM approved pit nearest in proximity to the location. The average grade will be approximately 1%.
- C. No cattle guards, grates or fence cuts will be required. No turnouts are planned.

3. Location of Existing and/or Proposed Facilities

A. In the event the well is found productive, a tank battery would be constructed and the necessary production equipment will be installed at the well site.

- 1) If necessary, the well will be operated by means of an electric prime mover. Electric power poles will be set along side of the access road.
- 2) The tank battery, all connections and all lines will adhere to API standards.

B. If the well is productive, rehabilitation plans are as follows.

- 1) The reserve pit will be back-filled after the contents of the pit are dry (within 120 days after completion, weather permitting).
- 2) The original topsoil from the well site will be returned to the location. The drill site will then be contoured as close as possible to the original state.

5. Location and Type of Water Supply

The proposed well will be drilled using a combination of brine and fresh water mud systems (outlined in Drilling Program). The water will be obtained from commercial sources and will be transported over the existing and proposed roads. No water well will be drilled on the location.

6. Source of Construction Materials

All caliche utilized for the drilling pad and proposed access road will be obtained from an existing BLM approved pit. All roads will be constructed of 6" rolled and compacted caliche.

7. Methods of Handling Water Disposal

- A. Drill cuttings will be disposed into the reserve pit.
- B. Drilling fluids will be contained in steel mud tanks. The reserve pit will contain excess drilling fluid or fluid from the well during drilling, cementing and completion operations. The reserve pit will be an earthen pit roughly 150' x 150' x 8', or smaller, in size.
- C. The reserve pit will be fenced on three sides throughout drilling operations and will be totally isolated upon removal of the rotary rig. The pit will be lined using a 5-7 mil plastic to minimize loss of drilling fluids and saturation of the ground with brine water used during drilling.
- D. Water produced from the well during completion operations will be disposed into a steel tank or reserve pit, if volumes prove excessive. After placing the well on production through the production facilities, all water will be collected in tanks. Produced oil will be separated into steel stock tanks until sold.
- E. A portable chemical toilet will be available on the location for human waste during the drilling operations.
- F. Garbage, trash and waste paper produced during drilling operations will be collected in a contained trailer and disposed at an approved landfill. All waste material will be contained to prevent scattering by the wind. All water, fluids, salt or other chemicals will be disposed into the reserve pit. No toxic waste or hazardous chemicals will be generated by this operation.
- G. All waste material will be removed within 30 days after the well is either completed or abandoned. The reserve pit will be completely fenced until it has dried. At the point the reserve pit is found sufficiently dry, it will be backfilled and reclaimed as per BLM specifications. Only the portion of the drilling pad used by the production equipment (pumping unit and tank battery) will remain in use. If the well is deemed non-commercial only a dry hole marker will remain.

8. Ancillary Facilities

No permanent campsite or other facilities will be constructed as a result of this well.

9. Well Site Layout

- A. The drilling pad is shown on Exhibit #5. The pad, pits and general location of the rig equipment are displayed. Top soil will be stored adjacent to the pad until reclamation efforts are undertaken. Only modest cuts will be necessary to build the pad which will be covered with 6" of compacted caliche.
- B. No permanent living facilities are planned, but temporary trailers for the tool pusher, drilling foreman and mud logger may be on location throughout drilling operations.
- C. The reserve pit will be lined using plastic sheeting of 5-7 mil thickness.

10. Plans for Restoration of Surface

- A. After concluding the drilling and/or completion operations, if the well is found non-commercial, the caliche will be removed from the pad and transported to the original caliche pit or used for other drilling locations. The road will be reclaimed as directed by the BLM. The reserve pit area will be broken out and leveled after drying to a condition where these efforts are feasible. The original top soil will be returned to the pad and contoured, as close as possible, to the original topography.
- B. The pit lining will be buried or hauled away in order to return the location and road to their pristine nature. All pits will be filled and location leveled, weather permitting, within 120 days after abandonment.
- C. The location and road will be rehabilitated as recommended by the BLM.
- D. The reserve pit will be fenced on three sides throughout drilling operations. After the rotary rig is removed, the reserve pit will be fenced on the fourth side to preclude endangering wildlife. The fencing will be in place until the pit is reclaimed.

- E. If the well is deemed commercially productive, the reserve pit will be restored as described in 10 (A) within 120 days subsequent to the completion date. Caliche from areas of the pad site not required for operations will be reclaimed. The original top soil will be returned to the area of the drilling pad not necessary to operate the well. These unused areas of the drilling pad will be contoured, as close as possible, to match the original topography.

11. Surface Ownership

The well site is owned by the Bureau of Land Management.

Road routes have been approved by the BLM.

The surface location will be restored as directed by the BLM.

12. Other Information

- A. The project area is located in a relatively flat area. The top soil at the wellsite is sandy. Vegetation in the area is moderately sparse, with prairie grasses, some mesquite bushes, and shinnery oak. No wildlife was observed but it is likely that deer, rabbits, coyotes, and rodents traverse the area.
- B. There is no permanent water in the immediate area.
- C. Land use is for oil and gas production, grazing and hunting.
- D. A Cultural Resources Examination will be completed by Southern New Mexico Archaeological Services, Inc. and forwarded to the BLM office in Carlsbad, New Mexico.

13. Lessee's and Operator's Representative

The Devon Energy Production Company, L.P. representatives responsible for ensuring compliance of the surface use plan are listed below.

Bill Greenlees
Operations Engineering Advisor

Don Mayberry
Superintendent

Devon Energy Production Company, L.P.
20 North Broadway, Suite 1500
Oklahoma City, OK 73102-8260


Devon Energy Production Company, L.P.
Post Office Box 250
Artesia, NM 88211-0250

(405) 552-8194 (office)
(405) 203-7778 (cell)

(505) 748-3371 (office)
(505) 746-4945 (home)

Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access road; that I am familiar with the conditions that presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Devon Energy Production Company, L.P. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.

Signed: 
Norvella Adams

Date: May 5, 2005

Sr. Staff Engineering Technician

Attachment to Exhibit #1
NOTES REGARDING BLOWOUT PREVENTERS
Devon Energy Production Company, LP
PALOMA BLANCO 20 FEDERAL 1
(M) 660' FSL & 660' FWL, Section 20, T-23-S, R-34-E
Lea County, New Mexico

1. Drilling nipple will be constructed so it can be removed mechanically without the aid of a welder. The minimum internal diameter will equal BOP bore.
2. Wear ring will be properly installed in head.
3. Blowout preventer and all associated fittings will be in operable condition to withstand a minimum 5000/10000 psi working pressure.
4. All fittings will be flanged.
5. A full bore safety valve tested to a minimum 3000 psi WP with proper thread connections will be available on the rotary rig floor at all times.
6. All choke lines will be anchored to prevent movement.
7. All BOP equipment will be equal to or larger in bore than the internal diameter of the last casing string.
8. Will maintain a kelly cock attached to the kelly.
9. Hand wheels and wrenches will be properly installed and tested for safe operation.
10. Hydraulic floor control for blowout preventer will be located as near in proximity to driller's controls as possible.
11. All BOP equipment will meet API standards and include a minimum 40 gallon accumulator having two independent means of power to initiate closing operation.

UNITED STATES DEPARTMENT OF THE INTERIOR
Bureau of Land Management
Roswell Field Office
2909 West Second Street
Roswell, New Mexico 88201-1287

Statement Accepting Responsibility for Operations

Operator Name: **Devon Energy Production Company, LP**
Street or Box: **20 North Broadway, Suite 1500**
City, State: **Oklahoma City, Oklahoma**
Zip Code: **73102-8260**

The undersigned accepts all applicable terms, conditions, stipulations and restrictions concerning operations conducted on the leased land or portion thereof, as described below.

Lease No.: **NMNM18306**
Legal Description of Land: **320 acres 20-T23S-R34E**
Formation(s): **Bell Lake (Morrow)**
Bond Coverage: **Nationwide**
BLM Bond File No.: **CO1104**

Authorized Signature:


Norvella Adams

Title: **Sr. Staff Engineering Technician**

Date: **May 5, 2005**

HYDROGEN SULFIDE DRILLING OPERATIONS PLAN

1. If H₂S is present in this area the following will apply.
2. All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:
 - a. Characteristics of H₂S
 - b. Physical effects and hazards
 - c. Proper use of safety equipment and life support systems.
 - d. Principle and operation of H₂S detectors, warning system and briefing areas
 - e. Evacuation procedures, routes and first aid.
 - f. Proper use of 30-minute pressure demand air pack.
3. H₂S Detection and Alarm System
 - a. H₂S detectors and audio alarm system to be located at bell nipple, end of blooie line (mud pit) and on derrick floor or doghouse.
4. Windsock and/or wind streamers
 - a. Windsock at mud pit area should be high enough to be visible
 - b. Windsock at briefing area should be high enough to be visible
 - c. There should be a windsock at entrance to location
5. Condition Flags and Signs
 - a. Warning Sign on access road to location
 - b. Flags to be displayed on sign at entrance to location. Green flag, normal safe condition. Yellow flag indicates potential pressure and danger. Red flag, danger, H₂S present in dangerous concentration. Only emergency personnel admitted to location.
6. Well Control Equipment
 - a. See Exhibit "E" & "E-1"
7. Communication
 - a. While working under masks chalkboards will be used for communication.
 - b. Hand signals will be used where chalk board is inappropriate
 - c. Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at most drilling foreman's trailer or living quarters.
8. Drill stem Testing
 - a. Exhausts will be watered
 - b. Flare line will be equipped with an electric igniter or a propane pilot light in case gas reaches the surface.
 - c. If the location is near to a dwelling a closed DST will be performed.
9. Drilling contractor supervisor will be required to be familiar with the effects H₂S has on tubular goods and other mechanical equipment.

If H₂S is encountered, mud system will be altered if necessary to maintain control or formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

Well name:	Paloma Blanco 20 Federal 1	
Operator:	Devon Energy	
String type:	Surface	
Location:	New Mexico	

Design parameters:		Minimum design factors:		Environment:	
Collapse		Collapse:			
Mud weight:	8.800 ppg	Design factor	1.125	H2S considered?	No
Design is based on evacuated pipe.				Surface temperature:	75 °F
				Bottom hole temperature:	90 °F
				Temperature gradient:	1.40 °F/100ft
				Minimum section length:	1,000 ft
				Minimum Drift:	2.250 in
Burst		Burst:			
Max anticipated surface pressure:	500 psi	Design factor	1.00		
Internal gradient:	0.080 psi/ft				
Calculated BHP	586 psi				
No backup mud specified.		Tension:		Non-directional string.	
		8 Round STC:	1.80 (J)		
		8 Round LTC:	1.80 (J)		
		Buttress:	1.60 (J)		
		Premium:	1.50 (J)		
		Body yield:	1.60 (B)		
		Tension is based on air weight.		Re subsequent strings:	
		Neutral point: 937 ft		Next setting depth: 5,000 ft	
				Next mud weight: 10.000 ppg	
				Next setting BHP: 2,597 psi	
				Fracture mud wt: 10.500 ppg	
				Fracture depth: 1,075 ft	
				Injection pressure: 586 psi	

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Est. Cost (\$)
1	1075	13.375	48.00	H-40	ST&C	1075	1075	12.59	13332

Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (kips)	Tension Strength (kips)	Tension Design Factor
1	491	740	1.51	586	1730	2.95	51.6	322	6.24 J

Devon Energy

Remarks:

Collapse is based on a vertical depth of 1075 ft, a mud weight of 8.8 ppg. The casing is considered to be evacuated for collapse purposes.

Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Date: June 4, 2002
Oklahoma City, Oklahoma

Engineering responsibility for use of this design will be that of the purchaser.

Well name:	Paloma Blanco
Operator:	Devon Energy
String type:	Intermediate
Location:	New Mexico

Design parameters:

Collapse

Mud weight: 10.000 ppg
Design is based on evacuated pipe.

Minimum design factors:

Collapse:

Design factor 1.125

Burst:

Design factor 1.00

Environment:

H2S considered? No
Surface temperature: 75 °F
Bottom hole temperature: 145 °F
Temperature gradient: 1.40 °F/100ft
Minimum section length: 1,000 ft

Burst

Max anticipated surface pressure: 1,390 psi
Internal gradient: 0.268 psi/ft
Calculated BHP 2,727 psi

No backup mud specified.

Tension:

8 Round STC: 1.80 (J)
8 Round LTC: 1.80 (J)
Buttress: 1.60 (J)
Premium: 1.50 (J)
Body yield: 1.60 (B)

Tension is based on air weight.
Neutral point: 4,256 ft

Estimated cost: 62,357 (\$)

Non-directional string.

Re subsequent strings:

Next setting depth: 11,800 ft
Next mud weight: 10.000 ppg
Next setting BHP: 6,130 psi
Fracture mud wt: 10.500 ppg
Fracture depth: 5,000 ft
Injection pressure 2,727 psi

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Est. Cost (\$)
2	2000	9.625	40.00	N-80	LT&C	2000	2000	8.75	25450
1	3000	9.625	40.00	HCK-55	LT&C	5000	5000	8.75	36907

Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (kips)	Tension Strength (kips)	Tension Design Factor
2	1039	2960	2.85	1925	5750	2.99	200	737	3.68 J
1	2597	4230	1.63	2727	3950	1.45	120	630	5.25 B

Devon Energy

Date: June 4, 2002
Oklahoma City, Oklahoma

Remarks:

Collapse is based on a vertical depth of 5000 ft, a mud weight of 10 ppg. The casing is considered to be evacuated for collapse purposes.
Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Engineering responsibility for use of this design will be that of the purchaser.

Well name:	Paloma Blanco 20 Federal I
Operator:	Devon Energy
String type:	Production
Location:	New Mexico

Design parameters:

Collapse

Mud weight: 10.000 ppg
Design is based on evacuated pipe.

Minimum design factors:

Collapse:

Design factor 1.125

Environment:

H2S considered? No
Surface temperature: 75 °F
Bottom hole temperature: 240 °F
Temperature gradient: 1.40 °F/100ft
Minimum section length: 1,000 ft

Burst

Max anticipated surface pressure: 1,061 psi
Internal gradient: 0.430 psi/ft
Calculated BHP 6,130 psi

No backup mud specified.

Burst:

Design factor 1.00

Tension:

8 Round STC: 1.80 (J)
8 Round LTC: 1.80 (J)
Buttress: 1.60 (J)
Premium: 1.50 (J)
Body yield: 1.60 (B)

Non-directional string.

Tension is based on air weight.
Neutral point: 10,020 ft

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Est. Cost (\$)
1	11800	7	26.00	HCP-110	LT&C	11800	11800	6.151	122661
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (kips)	Tension Strength (kips)	Tension Design Factor
1	6130	7800	1.27	6130	9950	1.62	306.8	693	2.26 J

Devon Energy

Date: June 4, 2002
Oklahoma City, Oklahoma

Remarks:

Collapse is based on a vertical depth of 11800 ft, a mud weight of 10 ppg. The casing is considered to be evacuated for collapse purposes.
Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Engineering responsibility for use of this design will be that of the purchaser.

Well name:

Paloma Blanco 20 Federal 1

Operator: Devon Energy

String type: Liner: Production

Location: New Mexico

Design parameters:**Collapse**Mud weight: 11.500 ppg
Design is based on evacuated pipe.**Minimum design factors:****Collapse:**

Design factor 1.125

Burst:

Design factor 1.00

Environment:H2S considered? No
Surface temperature: 75 °F
Bottom hole temperature: 271 °F
Temperature gradient: 1.40 °F/100ft
Minimum section length: 1,000 ft**Burst**Max anticipated surface
pressure: 2,350 psi
Internal gradient: 0.430 psi/ft
Calculated BHP 8,364 psi

No backup mud specified.

Tension:8 Round STC: 1.80 (J)
8 Round LTC: 1.80 (J)
Buttress: 1.60 (J)
Premium: 1.50 (J)
Body yield: 1.60 (B)Tension is based on air weight.
Neutral point: 13,627 ftLiner top: 11,800 ft
Non-directional string.

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Est. Cost (\$)
1	2200	4.5	13.50	P-110	LT&C	14000	14000	3.795	12327
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (kips)	Tension Strength (kips)	Tension Design Factor
1	8364	10680	1.28	8364	12410	1.48	29.7	338	11.38 J


Devon Energy

Date: June 4, 2002
Oklahoma City, Oklahoma**Remarks:**

For this liner string, the top is rounded to the nearest 100 ft. Collapse is based on a vertical depth of 14000 ft, a mud weight of 11.5 ppg. The Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.


Engineering responsibility for use of this design will be that of the purchaser.



PROPOSED 10-M BOPE AND CHOKE ARRANGEMENT

EXHIBIT

Lea County, New Mexico



*Per
Korone*

170.



Garbage Trailer
Toilet

Trailer

Trailer

Parking Area

300



Devon Energy Production Company, LP
Drilling Pad
Exhibit # D

District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144
June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐Type of action: Registration of a pit or below-grade tank ☒ Closure of a pit or below-grade tank ☐

Operator: Devon Energy Production Company, LP Telephone: 405-552-8198 e-mail address: norvella.adams@devn.com
Address: PO Box 250 Artesia NM 88211
Facility or well name: Paloma Blanco 20 Federal API #: 30-025-37295 U/L or Qtr/Qtr M Sec 20 T 23S R 34E
County: Lea Latitude: NEED THIS INFO Longitude: NEED THIS INFO NAD: 1927 ☐ 1983 ☐
Surface Owner: Federal ☒ State ☐ Private ☐ Indian ☐

Pit

Type: Drilling ☒ Production ☐ Disposal ☐
Workover ☐ Emergency ☐
Lined ☒ Unlined ☐
Liner type: Synthetic ☒ Thickness 12 mil Clay ☐
Pit Volume bbl

Below-grade tank

Volume: bbl Type of fluid:
Construction material:
Double-walled, with leak detection? Yes ☐ If not, explain why not.

Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet	(20 points)
	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	(0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes	(20 points)
	No	(0 points)
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	(20 points)
	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points)
Ranking Score (Total Points)		

If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if you are burying in place) onsite ☐ offsite ☐ If offsite, name of facility . (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No ☐ Yes ☐ If yes, show depth below ground surface ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations.

Additional Comments:

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☒, or an (attached) alternative OCD-approved plan ☐.

Date: 6/13/05Printed Name/Title Norvella Adams / Sr. Staff Eng. TechSignature Norvella Adams

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval:

Printed Name/Title CHRIS WILLIAMS - DIST. SMRSignature Chris WilliamsDate: 6/13/05