	UNITED STAT	25 N. French D	Division, Di rive	FORM	APPROVED
4pni 2004)	1 3160-5 1 2004) UNITED STATES AND AND DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT			FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007	
				5. Lease Serial No.	2011-2
	DRY NOTICES AND RE				530437-A
Do not u abandon	se this form for proposals ed well. Use Form 3160-3	to drill or to re-e (APD) for such pro	enter an oposals.	6. If Indian, Allottee	or Tribe Name
SUBMIT IN	I TRIPLICATE- Other ins	tructions on rever	se side.	-	eement, Name and/or No.
1. Type of Well Gas Well Other				<ul> <li>Caprock Meljaner Unit</li> <li>8. Well Name and No</li> <li>CAPROCK MALJAMAR UNIT #74</li> <li>9. API Well No.</li> </ul>	
2. Name of Operator FOREST OIL CORPORATION					
3a. Address	TE 2200, DENVER, CO. 80202	3b. Phone No. (include 303-812-1607	area code)		5 - 00671
4. Location of Well (Footage	e, Sec., T., R., M., or Survey Description	·			Exploratory Prica
· •	UNIT N, SEC.24, T17S, R32E	, 		11. County or Parish <u> <u> </u> </u>	
12. CHEC	CK APPROPRIATE BOX(ES) T	O INDICATE NATUR	E OF NOTICE,	REPORT, OR OTHE	R DATA
TYPE OF SUBMISSIO	N	TY	PE OF ACTION		i
Notice of Intent	Acidize	Deepen Fracture Treat	Production (S		ter Shut-Off Il Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete		
	Change Plans	Plug and Abandon	Temporarity A		
Final Abandonment No	otice Convert to Injection	Plug Back	Water Dispos		······
following completion or testing has been comple determined that the site 05-19-05 - TAG CII SET 60 S	which the work will be performed or pro- f the involved operations. If the operation ted. Final Abandonment Notices shall is is ready for final inspection.) SP SET AT 3995'. CIRCULATED X CMT PLUG ON CIBP FROM (	ovide the Bond No. on file v on results in a multiple comp be filed only after all require WELL W/ 9.5PPG MUJ 3995' - 3560'. TAG TOO	vith BLM/BIA. Requ sletion or recompletion ments, including recla D LADEN FLUIDS C WITH TUBING .	ured subsequent reports sh n in a new interval, a Form mation, have been comple S MIXED WITH 35 SX AT 3484'.	3160-4 shall be filed once ted, and the operator has SALT GEL.
following completion o testing has been comple determined that the site 05-19-05 - TAG CII SET 60 S 05-20-05 - RIH AN MIX AN RETAIN SET 30 S 05-21-05 PERFOR BELOW REMOVI	which the work will be performed or pro- f the involved operations. If the operation ted. Final Abandonment Notices shall is ready for final inspection.) BP SET AT 3995'. CIRCULATED X CMT PLUG ON CIBP FROM 3	ovide the Bond No. on file v on results in a multiple comp be filed only after all require WELL W/ 9.5PPG MUI 3995' - 3560'. TAG TOO AT 1800'. ESATBLISH W REATINER, RELEA RATE 7" CSG AT 1141' RATIONS UP TO 1041', SHINJECTION RATE ( TIONS, TOC 562, CALC	vith BLM/BIA. Requ letion or recompletion ments, including recla D LADEN FLUIDS C WITH TUBING J INJECTION RAT SE SETTING TOO . UNABLE TO ES . WOC. TAG TOC DF 1BPM AT 600P DLATED. TAG T	ired subsequent reports sh n in a new interval, a Form mation, have been comple S MIXED WITH 35 SX AT 3484'. E OF 1.5BPM AT 1000 OL, SET 25 SX CMT F iTABLISHINJECTION AT 1035'. 'SI. SQUEEZE 40 SX C OC AT 545'. CUT OF	ertinent markers and zones. all be filed within 30 days 3160-4 shall be filed once ted, and the operator has SALT GEL. PSI. ULUG ON 2122324 WRATE 12 SMTS FASD
following completion o testing has been comple determined that the site 05-19-05 - TAG CII SET 60 S 05-20-05 - RIH ANI MIX AN RETAIN SET 30 S 05-21-05 PERFOR BELOW REMOVI REQUIR	which the work will be performed or pro- f the involved operations. If the operation ted. Final Abandonment Notices shall 1 is ready for final inspection.) BP SET AT 3995'. CIRCULATED X CMT PLUG ON CIBP FROM 3 D SET 7" CEMENT RETAINER A D SQUEEZE 250 SX CMT BELO ER FROM 1800' - 1700'. PERFOI X CMT PLUG ACROSS PERFO X CMT PLUG ACROSS PERFO X CMT PLUG ACROSS PERFO X CMT PLUG ACROSS PERFO ATE 7" CSG AT 662'. ESTABLIS PACKER AND OUT PERFORAT E WELLHEAD. SET SURFACE I EMENTS.	ovide the Bond No. on file v on results in a multiple comp be filed only after all require WELL W/ 9.5PPG MUI 3995' - 3560'. TAG TOO AT 1800'. ESATBLISH W REATINER, RELEA RATE 7" CSG AT 1141' RATIONS UP TO 1041', SHINJECTION RATE ( TIONS, TOC 562, CALC	vith BLM/BIA. Requ letion or recompletion ments, including recla D LADEN FLUIDS C WITH TUBING J INJECTION RAT SE SETTING TOO . UNABLE TO ES . WOC. TAG TOC DF 1BPM AT 600P DLATED. TAG T	ired subsequent reports sh n in a new interval, a Form mation, have been comple S MIXED WITH 35 SX AT 3484'. E OF 1.5BPM AT 1000 OL, SET 25 SX CMT F iTABLISHINJECTION AT 1035'. 'SI. SQUEEZE 40 SX C OC AT 545'. CUT OF	ertinent markers and zones. all be filed within 30 days 3160-4 shall be filed once ted, and the operator has SALT GEL. PSI. ULUG ON 2122324 WRATE 12 SMTS FASD
following completion or testing has been completed determined that the site 05-19-05 - TAG CII SET 60 S 05-20-05 - RIH ANI MIX AN RETAIN SET 30 S 05-21-05 PERFOR BELOW REMOVI REQUIR	which the work will be performed or pro- f the involved operations. If the operation ted. Final Abandonment Notices shall 1 is ready for final inspection.) BP SET AT 3995'. CIRCULATED X CMT PLUG ON CIBP FROM 3 D SET 7" CEMENT RETAINER A D SQUEEZE 250 SX CMT BELO ER FROM 1800' - 1700'. PERFOI X CMT PLUG ACROSS PERFO X CMT PLUG ACROSS PERFO X CMT PLUG ACROSS PERFO X CMT PLUG ACROSS PERFO ATE 7" CSG AT 662'. ESTABLIS PACKER AND OUT PERFORAT E WELLHEAD. SET SURFACE I EMENTS.	ovide the Bond No. on file v on results in a multiple comp be filed only after all require WELL W/ 9.5PPG MUI 3995' - 3560'. TAG TOO AT 1800'. ESATBLISH W REATINER, RELEA RATE 7" CSG AT 1141' RATIONS UP TO 1041', SHINJECTION RATE ( TIONS, TOC 562, CALC	vith BLM/BIA. Requ letion or recompletion ments, including recla D LADEN FLUIDS C WITH TUBING J INJECTION RAT SE SETTING TOO . UNABLE TO ES . WOC. TAG TOC DF 1BPM AT 600P DLATED. TAG T	ired subsequent reports sh n in a new interval, a Form mation, have been comple S MIXED WITH 35 SX AT 3484'. E OF 1.5BPM AT 1000 OL, SET 25 SX CMT F TABLISHINJECTION AT 1035'. 'SI. SQUEEZE 40 SX C OC AT 545'. CUT OF L DRYHOLE MARKE	ertinent markers and zones. all be filed within 30 days 3160-4 shall be filed once ted, and the operator has SALT GEL. PSI. LUG ON 2122324 NRATE 22 SMTS FASD
following completion or testing has been completed determined that the site 05-19-05 - TAG CII SET 60 S 05-20-05 - RIH ANI MIX AN RETAIN SET 30 S 05-21-05 PERFOR BELOW REMOVI REQUIR	which the work will be performed or profit the involved operations. If the operation ted. Final Abandonment Notices shall it is ready for final inspection.) BP SET AT 3995'. CIRCULATED X CMT PLUG ON CIBP FROM 100 SET 7" CEMENT RETAINER. D SQUEEZE 250 SX CMT BELO D SQUEEZE 250 SX CMT BELO ER FROM 1800' - 1700'. PERFOI X CMT PLUG ACROSS PERFO ATE 7" CSG AT 662'. ESTABLI: PACKER AND OUT PERFORAT E WELLHEAD. SET SURFACE FEMENTS.	ovide the Bond No. on file v on results in a multiple comp be filed only after all require WELL W/ 9.5PPG MUI 3995' - 3560'. TAG TOO AT 1800'. ESATBLISH W REATINER, RELEA RATE 7" CSG AT 1141' RATIONS UP TO 1041', SHINJECTION RATE ( TIONS, TOC 562, CALC	vith BLM/BIA. Requ letion or recompletion ments, including recla D LADEN FLUIDS C WITH TUBING J INJECTION RAT SE SETTING TOO . UNABLE TO ES . WOC. TAG TOC DF 1BPM AT 600P DLATED. TAG T	ired subsequent reports sh n in a new interval, a Form mation, have been comple S MIXED WITH 35 SX AT 3484'. E OF 1.5BPM AT 1000 OL, SET 25 SX CMT F TABLISHINJECTION AT 1035'. 'SI. SQUEEZE 40 SX C OC AT 545'. CUT OF L DRYHOLE MARKE	ertinent markers and zones. all be filed within 30 days 3160-4 shall be filed once ted, and the operator has SALT GEL. PSI. LUG ON 21222324 WRATE 2021222324 WRATE 202122324 WRATE 202122324
following completion or testing has been completed determined that the site 05-19-05 - TAG CII SET 60 S 05-20-05 - RIH ANI MIX ANI RETAIN SET 30 S 05-21-05 PERFOR BELOW REMOVI REQUIR	which the work will be performed or profit the involved operations. If the operation ted. Final Abandonment Notices shall is ready for final inspection.) BP SET AT 3995'. CIRCULATED X CMT PLUG ON CIBP FROM 1200'. TO SET 7" CEMENT RETAINER AD SQUEEZE 250 SX CMT BELO DER FROM 1800'. 1700'. PERFOX X CMT PLUG ACROSS PERFOX X CMT PLUG ACROSS PERFOX TATE 7" CSG AT 662'. ESTABLIS PACKER AND OUT PERFORATE 2 WELLHEAD. SET SURFACE FOR EMENTS.	vide the Bond No. on file v on results in a multiple comp be filed only after all required WELL W/ 9.5PPG MUI 3995' - 3560'. TAG TOC AT 1800'. ESATBLISH W REATINER, RELEA RATE 7" CSG AT 1141' RATIONS UP TO 1041' SHINJECTION RATE ( TIONS, TOC 562, CALC PLUG FROM 60' TO SU Title R FEDERAL OR S	vith BLM/BIA. Requisition or recompletion ments, including recla D LADEN FLUIDS C WITH TUBING INJECTION RAT SE SETTING TOO UNABLE TO ES WOC. TAG TOC DF 1BPM AT 600P ULATED. TAG TO RFACE. INSTAL	ired subsequent reports sh n in a new interval, a Form mation, have been comple S MIXED WITH 35 SX AT 3484'. E OF 1.5BPM AT 1000 OL, SET 25 SX CMT F TABLISHINJECTION AT 1035'. 'SI. SQUEEZE 40 SX C OC AT 545'. CUT OF L DRYHOLE MARKE	ertinent markers and zones. all be filed within 30 days 3160-4 shall be filed once ted, and the operator has SALT GEL. PSI. LUG ON 21222324 WRATE 2021222324 WRATE 202122324 WRATE 202122324
following completion or testing has been completed determined that the site 05-19-05 - TAG CII SET 60 S 05-20-05 - RIH AN MIX AN RETAIN SET 30 S 05-21-05 PERFOR BELOW REMOVI REQUIR	which the work will be performed or profit the involved operations. If the operation ted. Final Abandonment Notices shall it is ready for final inspection.) BP SET AT 3995'. CIRCULATED X CMT PLUG ON CIBP FROM 100 SET 7" CEMENT RETAINER. D SQUEEZE 250 SX CMT BELO D SQUEEZE 250 SX CMT BELO D SQUEEZE 250 SX CMT BELO D SQUEEZE 250 SX CMT BELO CR FROM 1800' - 1700'. PERFOIX X CMT PLUG ACROSS PERFO. X CMT PLUG ACROSS PERFO. ATE 7" CSG AT 662'. ESTABLIS PACKER AND OUT PERFORATE WELLHEAD. SET SURFACE FOR EMENTS. he foregoing is true and correct ed) May Taylor THIS SPACE FOR GD.) DAVID B. CLARE	vide the Bond No. on file v on results in a multiple comp be filed only after all required WELL W/ 9.5PPG MUI 3995' - 3560'. TAG TOO AT 1800'. ESATBLISH W REATINER, RELEA RATE 7" CSG AT 1141' RATIONS UP TO 1041'. SHINJECTION RATE O FIONS, TOC 562, CALC PLUG FROM 60' TO SU Title Date RFEDERAL OR S	vith BLM/BIA. Requisition or recompletion ments, including recla D LADEN FLUIDS C WITH TUBING INJECTION RAT SE SETTING TOO UNABLE TO ES WOC. TAG TOC DF 1BPM AT 600P ULATED. TAG TO RFACE. INSTAL	ired subsequent reports sh n in a new interval, a Form mation, have been comple S MIXED WITH 35 SX AT 3484'. E OF 1.5BPM AT 100 OL, SET 25 SX CMT H TABLISHINJECTION AT 1035'. SI. SQUEEZE 40 SX C OC AT 545'. CUT OF L DRYHOLE MARKH	ertinent markers and zones. all be filed within 30 days 3160-4 shall be filed once ted, and the operator has SALT GEL. PSI. LUG ON 21222324 WRATE 2021222324 WRATE 202122324 WRATE 202122324
following completion or testing has been completed determined that the site 05-19-05 - TAG CII SET 60 S 05-20-05 - RIH ANI MIX AN RETAIN SET 30 S 05-21-05 PERFOR BELOW REMOVI REQUIR	which the work will be performed or profit the involved operations. If the operation ted. Final Abandonment Notices shall is ready for final inspection.) BP SET AT 3995'. CIRCULATED X CMT PLUG ON CIBP FROM 1200'. TO SET 7" CEMENT RETAINER AD SQUEEZE 250 SX CMT BELO DER FROM 1800'. 1700'. PERFOX X CMT PLUG ACROSS PERFOX X CMT PLUG ACROSS PERFOX TATE 7" CSG AT 662'. ESTABLIS PACKER AND OUT PERFORATE 2 WELLHEAD. SET SURFACE FOR EMENTS.	vide the Bond No. on file v on results in a multiple comp be filed only after all required WELL W/ 9.5PPG MUI 3995' - 3560'. TAG TOC AT 1800'. ESATBLISH W REATINER, RELEA RATE 7" CSG AT 1141' SHINJECTION RATE O TIONS, TOC 562, CALC PLUG FROM 60' TO SU Title REDERAL OR S	vith BLM/BIA. Requisetion or recompletion ments, including recla D LADEN FLUIDS WITH TUBING J INJECTION RAT SE SETTING TOO UNABLE TO ES WOC. TAG TOC DF 1BPM AT 600P ULATED. TAG TOC DF 1BPM AT 600P ULATED. TAG TOC DF 1BPM AT 600P	ired subsequent reports sh n in a new interval, a Form mation, have been comple S MIXED WITH 35 SX AT 3484'. E OF 1.5BPM AT 100 OL, SET 25 SX CMT H TABLISHINJECTION AT 1035'. SI. SQUEEZE 40 SX C OC AT 545'. CUT OF L DRYHOLE MARKH	ertinent markers and zones. all be filed within 30 days 3160-4 shall be filed once ted, and the operator has SALT GEL. PSI. LUG ON $21222324$ WRATE $102122324$ WRATE $102122324$ EASD
following completion or testing has been completed determined that the site 05-19-05 - TAG CII SET 60 S 05-20-05 - RIH ANI MIX AN RETAIN SET 30 S 05-21-05 PERFOR BELOW REMOVI REQUIR	which the work will be performed or profit the involved operations. If the operation ted. Final Abandonment Notices shall it is ready for final inspection.) BP SET AT 3995'. CIRCULATED X CMT PLUG ON CIBP FROM 100 SET 7" CEMENT RETAINER. D SQUEEZE 250 SX CMT BELO D SQUEEZE 250 SX CMT BELO D SQUEEZE 250 SX CMT BELO D SQUEEZE 250 SX CMT BELO CR FROM 1800' - 1700'. PERFOI X CMT PLUG ACROSS PERFO. X CMT PLUG ACROSS PERFO. X CMT PLUG ACROSS PERFO. ATE 7" CSG AT 662'. ESTABLI: PACKER AND OUT PERFORATE WELLHEAD. SET SURFACE FOR THIS SPACE FOR THIS SPACE FOR SD.; DAVID S. GLASS up, are attached. Approval of this notic ds legal or equitable title to those right	vide the Bond No. on file v on results in a multiple comp be filed only after all requires WELL W/ 9.5PPG MUI 3995' - 3560'. TAG TOO AT 1800'. ESATBLISH W REATINER, RELEA RATE 7" CSG AT 1141' RATIONS UP TO 1041'. SHINJECTION RATE O FLUG FROM 60' TO SU Title Date RFEDERAL OR S Ce does not warrant or ts in the subject lease it a crime for any person for	vith BLM/BIA. Requisetion or recompletion ments, including recla D LADEN FLUIDS WITH TUBING WITH TUBING WITH TUBING WOC. TAG TOC DF 1BPM AT 600P ULATED. TAG T	ired subsequent reports sh n in a new interval, a Form mation, have been comple S MIXED WITH 35 SX AT 3484'. E OF 1.5BPM AT 100 OL, SET 25 SX CMT H TABLISHINJECTION AT 1035'. SI. SQUEEZE 40 SX C OC AT 545'. CUT OF L DRYHOLE MARKH	ertinent markers and zones. all be filed within 30 days 3160-4 shall be filed once ted, and the operator has SALT GEL. PSI. LUG ON 21222324 WRATE 10 2122324 WRATE 10 2122324 WRATE 10 68 L 95 V Lized Technolog JUN 16 2005