API#

30-045-24837

Page 1 Revised 10/01/78

#### STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

# OIL CONSERVATION DIVISION 6

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

					R. C.		A	Well		
Operator B	URLINGTON RESOURC	Lease	CONGRESS		·	No.	4E			
Location						: ~				
of Well:	Unit E Sect	35 Twp.	029N	Rge.	011W	County	SAN JUAN			
	NAME OF	RESERVOIR OR POO	L	T	YPE OF PROD.	METH	OD OF PROD.	PR	OD. MEDIUM	
					(Oil or Gas)	(Flo	w or Art. Lift)	(	Γbg. or Csg.)	
Upper Completion	CHACRA	HACRA			Gas		Flow		Casing	
Lower Completion	DAKOTA				Gas		Flow		Tubing	
		PRE-F	LOW SHUT-IN	V PRESS	URE DATA					
Upper	Hour, date shut-in	Length of time shut-	-in	SIp	ress. psig		Stabilized? (Yes or No)			
Completion	04/19/2005	216 Ho	urs	143						
Lower Completion	04/19/2005	168 Ho	urs	380						
			FLOW TE	ST NO.	1					
Commenced	ed at (hour,date)* 04/26/2005				Zone producing (Upper or Lower) LOWER					
TIME	LAPSED TIME	IE PRESSURE			PROD. ZONE					
(hour,date)	SINCE*	Upper Completion	Lower Comp	pletion TEMP			REM	IARKS		
04/27/2005	192 Hours	143	163							
04/28/2005	216 Hours	143	42				<u> </u>	-		
Production rate	e during test					<u> </u>				
Oil	BOPD based on		Bbls. in		Hours.		Grav.		GOR	
Gas:		MCFPD; Tested thru (	Orifice or Mete	er): _						
		MID	TEST SHUT-IN	V PRFSS	URE DATA					
Upper Completion	Hour, date shut-in	Length of time shut-in		SI press. psig			Stabilized? (Yes or No)			
Lower Completion	Hour, date shut-in	Length of time shut-in		SI press. psig			Stabilized? (Yes or No)			

3221602 390

(Continue on reverse side)

### FLOW TEST NO. 2

Commenced at (hour, dat	te)**		Zone producing (Upper or Lower):				
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE TEMP.	REMARKS		
(mar, acre)	SHOL	Upper Completion	Lower Completion	1 1 EMP.	***************************************		
			,				
					-		
, .		, '					
Production rate duri	ing test						
Oil:	ВО	PD based on	Bbls. in	Hours	GOR		
				•			
Remarks:							
I hereby certify that	the information here	ein contained is true	and complete to	the best of my knowledg	ge.		
Approved	IUN - 9 20	<b>05</b> 19	· •	Operator Burlingt	on Resources		
	Conservation Divis			By Alorso	Orice a		
By Chali	Hen			Title Operations A	ssociate		
ritle SUPE	RVISOR DISTRIC	T#3	Date Wednesday, June 08, 2005				

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).