Submit 3 Copies To Appropriate District Office	State of New Mexico			Form C-103	
District I	Energy, Minerals and Natural Resources			May 27, 2004 WELL API NO. ✓	
1625 N. French Dr., Hobbs, NM 88240 District II	OH COMERNIA TION TO THE			30-025-37059	
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION			5. Indicate Type of L	ease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.			STATE	FEE X
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505			6. State Oil & Gas Le	ase No.
87505					
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A				7. Lease Name or Unit Agreement Name	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				Fred Turner Jr. 'C'	
	Gas Well Other			8. Well Number 002	
Name of Operator Amerada Hess Corporation				9. OGRID Number 495	
3. Address of Operator					
-	, TX 79360			(47530) Skaggs;Drinka	dcat Nadine;Tubb,West
4. Well Location	, 170 10000			West(62940)	ru(57000) vvarren,Abo,
Unit Letter_ E :	2280 feet from th	e North		1250 feet from th	e West line
Section 17	Township		nge 38E		ounty Lea
	11. Elevation (Show				Lean Lean
Dit on Poles	3562'	GL		Cinc.	A STATE OF THE STA
Pit or Below-grade Tank Application 0					
Pit type Depth to Groundwa				nce from nearest surface w	ater
Pit Liner Thickness: mil	Below-Grade Tank:			struction Material	
12. Check A	Appropriate Box to I	Indicate N	ature of Notice, I	Report or Other Dat	a
NOTICE OF IN	TENTION TO:		SUBS	SEQUENT REPO	RT ∩E·
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK				TERING CASING	
TEMPORARILY ABANDON	RARILY ABANDON CHANGE PLANS COMMENCE DRILLING O				ND A
PULL OR ALTER CASING	MULTIPLE COMPL		CASING/CEMENT	JOB 🛛	
OTHER:		П	OTHER:		
13. Describe proposed or comp	leted operations. (Clear	rly state all p	ertinent details, and	give pertinent dates, in	cluding estimated date
of starting any proposed we or recompletion.	rk). SEE RULE 1103.	For Multipl	e Completions: Atta	ach wellbore diagram o	f proposed completion
4/22/2005 thru 4/25/2005					
MIRU Patterson Rig. Spud well @	11:30 hrs 4/22/2005 (1	16"conductor	set & cemented @	60'). Drill from 60' to 22	26'. Survey @ 185'
= 3/4 deg. Drill to 685'. Survey @	: 645' = 3/4 deg. Drill to	1163'. Surv	ey @ 1122' = 3/4 de	g. Drill to 1510'. Surve	ev @ 1470' = 1 dea
Circulate & condition hole. Run 34 jts 8 5/8" 24# J-55 casing. Rig up BJ Lines. Pumped 500 sx Class 'C' cement +2% CACL2 + 4% @ 13.5 ppg. Tail w/250 sx Class 'C' cement w/2% CACL2 mixed @ 14.8 ppg. Had 20 bbls (94 sx) cement returns to surface.					
Bumped plug w/1150 psi. WOC 5	hrs Ninnle un and test	∠ mixed @ 14 EROP's ann	4.8 ppg. Had 20 bbl	s (94 sx) cement return	s to surface.
Drill out float eqpt. to 1510'.	me. Tuppie up una tool	3, 41111	uiai, rams and imes	to 250/1500 psi. Test (asing to 1000 psi.
				ئون ئى	z ^{ik}
				1/2/	
				18	
				186	
				100	ν ω
				Les.	(A)
				190	
				VI z	(812111213)
I hereby certify that the information	above is true and compl	ete to the be	st of my knowledge		
grade tank has been/will be constructed or	closed according to NMOC	D guidelines [, a general permit 🔲 o	r an (attached) alternative	OCD-approved plan .
SIGNATURE (MOV)	11/1000	TITLE Se	enior Advisor/Regula	ntory DA	TE_6/23/2005
Type or print name Carol J. Moore		E-mail add	dress: cmoore@hes	S.COM Telenh	one No. (432)758-6738
For State Use Only	_		_	F	05 110. (102)/ 00-0/ 00
APPROVED BY:			ROLEUM ENGINE		_
Conditions of Approval (if any):		_TITLE	FIARINE	DADA	
- ()					IUN 2 8 2005