Office <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240	State of New Mexico	Form C-103
1635 M. E II. L M. 60040	Energy, Minerals and Natural Resources	May 27, 2004
District II	•	WELL API NO.: 30 025 37240
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.	STATE X FEE
District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		
	ICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	SALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	
PROPOSALS.)	CATION FOR PERMIT" (FORM C-101) FOR SUCH	Jalmat Field Yates Sand Unit
	Gas Well Other	8. Well Number: 221
2. Name of Operator: Melrose	Operating Company	9. OGRID Number: 184860
3. Address of Operator: c/o P.O.	Pov 052 Midland TV 70702	10. Dool name of Wildow
3. Address of Operator. C/o P.O.	BOX 955, MIDIANO, TA /9/02	10. Pool name or Wildcat Jalmat (T-Y-7R)
4. Well Location		Januar (1-1-/K)
Unit Letter I : 1	980 feet from the South line and 330	foot from the Foot line
Section 10		feet from theEastline
Section 10		SE NMPM Lea County
	11. Lievation (smow whether DR, RRD, R1, OR,	
Pit or Below-grade Tank Application 🔲 o	r Closure 🗌	
Pit typeDepth to Groundw	aterDistance from nearest fresh water well	Distance from nearest surface water
Pit Liner Thickness: mil	Below-Grade Tank: Volumebbls;	Construction Material
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
		oc, report of other Data
NOTICE OF IN		UBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL W	
TEMPORARILY ABANDON DULL OR ALTER CASING		DRILLING OPNS. P AND A
FOLL OR ALTER CASING []	MULTIPLE COMPL CASING/CEN	IENT JOB X
OTHER:	☐ OTHER:	П
13. Describe proposed or comp	leted operations. (Clearly state all pertinent details	, and give pertinent dates, including estimated date
Describe proposed or comp of starting any proposed we		, and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
13. Describe proposed or comp	leted operations. (Clearly state all pertinent details	, and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
 Describe proposed or comp of starting any proposed we or recompletion. 	leted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions	Attach wellbore diagram of proposed completion
 13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held,
 13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 J/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150'	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx startite and 250sx Cl C 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx startite and 250sx Cl C 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150'	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx startite and 250sx Cl C 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx startite and 250sx Cl C 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx startite and 250sx Cl C 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx startite and 250sx Cl C 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx startite and 250sx Cl C 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx startite and 250sx Cl C 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx startite and 250sx Cl C 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx starlite and 250sx Cl C, 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 l/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held.	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx starlite and 250sx Cl C, 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 I/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held. 6-4-05: Cleaned up location, installed to the complete of the	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit. d wellhead & BOP. SI, prep to perforate & treat.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx starlite and 250sx Cl C, 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 I/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held. 6-4-05: Cleaned up location, installed to the complete of the	oleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150' Circulated 72 sx to pit.	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx starlite and 250sx Cl C, 4%
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 1/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held. 6-4-05: Cleaned up location, installed to the constructed or grade tank has been/will be constructed or the con	cleted operations. (Clearly state all pertinent details brk). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150'. Circulated 72 sx to pit. It wellhead & BOP. SI, prep to perforate & treat. above is true and complete to the best of my knowledged according to NMOCD guidelines X, a general permit	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx starlite and 250sx Cl C, 4% complete the starting of the complete the compl
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 1/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held. 6-4-05: Cleaned up location, installed to the constructed or starting grade tank has been/will be constructed or SIGNATURE	cleted operations. (Clearly state all pertinent details brk). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150'. Circulated 72 sx to pit. It wellhead & BOP. SI, prep to perforate & treat. above is true and complete to the best of my knowledged according to NMOCD guidelines X, a general permit leave. TITLE Regulatory A	edge and belief. I further certify that any pit or below- oran (attached) alternative OCD-approved plan DATE: 6-16-05
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 1/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held. 6-4-05: Cleaned up location, installed to the constructed or grade tank has been/will be constructed or the con	bleted operations. (Clearly state all pertinent details ork). SEE RULE 1103. For Multiple Completions of 401'. Ran 8 5/8", J-55, 24# casing to 400', cemer to 1500#. 5'. Logged. Ran 5 1/2", 15.5#, J-55 casing to 4150'. Circulated 72 sx to pit. In wellhead & BOP. SI, prep to perforate & treat. above is true and complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the complete to the best of my knowledged according to NMOCD guidelines X, a general permit of the complete to the c	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx starlite and 250sx Cl C, 4% complete the starting of the complete the compl
13. Describe proposed or compost of starting any proposed we or recompletion. 5-23-05: Spud 12 1/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held. 6-4-05: Cleaned up location, installed to the constructed or start the same and the constructed or significant to the same and the constructed or significant to the same and the sa	above is true and complete to the best of my knowledge of the completions of the complete to the best of my knowledge of the complete to the complete to the complete to the best of my knowledge of the complete to t	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx starlite and 250sx Cl C, 4% comented with 600 sx starlite and 250sx Cl C
13. Describe proposed or comp of starting any proposed we or recompletion. 5-23-05: Spud 12 1/4" hole, drilled to circulated 60 sx to pit. WOC. Tested 5-28-05: Reached total depth of 417 gel 3% salt, 7/10% C-15. Float held. 6-4-05: Cleaned up location, installed to the constructed or SIGNATURE Type or print name: Ann E. Ritch:	above is true and complete to the best of my knowledge of the second and the seco	Attach wellbore diagram of proposed completion ted with 330 sx Cl C w/2% CaCl, float held, cemented with 600 sx starlite and 250sx Cl C, 4% cemented with 600 sx starlite and 250sx Cl C, 4% cedge and belief. I further certify that any pit or below————————————————————————————————————