Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Energy, Minerals and Natural Resources May 27, 2004 District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 District II 30-041-20912 OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease District III 1220 South St. Francis Dr. STATE | FEE 🖂 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV 6. State Oil & Gas Lease No. 1220 S. St. Francis Dr., Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH Gato Loco BFT Com PROPOSALS.) 8. Well Number 1. Type of Well: Oil Well Gas Well Other 2. Name of Operator 9. OGRID Number Yates Petroleum Corporation 025575 3. Address of Operator 10. Pool name or Wildcat 105 S. 4th Street, Artesia, NM 88210 Jenkins; Atoka, Northwest (Gas) 4. Well Location Unit Letter 1800 feet from the South line and 900 feet from the East line Section 31 Township Range **NMPM** Roosevelt County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4184'GR Pit or Below-grade Tank Application or Closure \_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_ \_\_\_ Distance from nearest surface water \_ Below-Grade Tank: Volume \_\_ Pit Liner Thickness: bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON П REMEDIAL WORK □ ALTERING CASING □ **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS.□ PLUG AND ABANDON □ PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB OTHER: OTHER: Spud and set conductor 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/8/05 - Resumed drilling at 6:00 AM. Set 13-3/8" 48# H-40 ST&C casing at 423'. Cemented with 240 sx "C" + 2% CaCl2 + 0.25#/sx Celloflake (yld 1.35, wt 14.8). Tailed in with 200 sx "C" + 2% CaCl2 (yld 1.34, wt 14.8). Cement circulated to surface. Tested casing to 600 psi for 30 min. WOC 21 hrs 15 min. Reduced hole to 12-1/4" and resumed drilling. 6/15/05 - Set 9-5/8" 36# & 40# J-55 ST&C casing at 4010'. Cemented with 1360 sx 35:65 Poz "C" + 6% gel + 5% Salt + 1/4# Celloflake (yld 2.04, wt 12.5). Tailed in with 200 sx "C" (yld 1.34, wt 14.8). Cement circulated to surface. Tested casing to 1500 psi for 30 min. WOC 80 hrs 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines \_, a general permit \_ or an (attached) alternative OCD-approved plan \_. TITLE Regulatory Compliance Supervisor DATE June 22, 2005 Type or print name \_\_\_\_\_ Tina Huerta E-mail address: <u>tinah@ypcnm.com</u> Telephone No. <u>505-748-1471</u> For State Use Only PETROLEUM ENGINEER APPROVED BY: Conditions of Approval (if any):