This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

(2)

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1 Revised June 10, 2003

Well

Operator w	manis Exploration	and Production	<u> </u>	Lease Na	ame <u>Rosa</u>	i Unit	-	٠	NO. <u>on</u> .		
Location Of	Well: Unit Le	tter <u>D</u> S	ec _	26 Twp_	31N F	Rge <u>0</u>	6W API	# 30-0	300392543000		
	Name of Re	servoir or Pool	Type of Prod. (Oil or Gas)			Method of Prod. (Flow or Art. Lift)		Prod. Medium (Tbg. Or Csg.)			
Upper Completion	PC		695			Llow		Tha			
Lower Completion	Lower ompletion MV			6as			flow		The		
			Pre	·Flow Shut-In I	Pressure D	ata					
Upper Completion	Hour, Date, Shut-In ion 0910 6-10-05			Length of Time Shut-In			SI Press. Psig		Stabilized? (Yes or No)		
Lower Completion	Hour, Date, Shut-In 910 6-10-05			Length of Time Shut-In			SI Press. Psig		Stabilized? (Yes or No)		
Flow Test No. 1											
Commenced at (hour, date)* 0910 6-13-05 Zone producing (Upper or Lower):											
Time (Hour, Date	Time Lapsed Time Press			ure Lower Compl.	Prod. 7		Remarks				
910 6-1	6-14 24 1- 140			243 64		<i>c</i>	-				
10 b-15	- 48 42	141		244	63	3					
20 6-16	726-	138		247	62		7.		· · · · · · · · · · · · · · · · · · ·		
				·							
		 		<u></u>				1677	W.		
		 -						11 11			
oduction rat	e during test	<u> </u>						()	7		
il:BOPD based onBbls. In Hrs Grav GOR											
as: <u>3</u> 2	OMCFPI	O; Test thru (Or	ifice	or Meter):	rid.				· ,		
Mid-Test Shut-In Pressure Data											
							ess. Psig	Stabi	Stabilized? (Yes or No)		
			Le	Length of Time Shut-In			ess. Psig	Stabi	lized? (Yes or No)		

(Continue on reverse side)

			Flow To	est No	. 2			and the state of t
Commenced	at (hour, date)**			Zone	producing (U	per or Low	er):	and the same of the same
Time (Hour, Date)	Lapsed Time Since**	Pro Upper Compl.	essure Lower Comp	1.	Prod. Zone Temp.	Remarks		
	:			ś			t :	7. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.
111 30	1. <u> </u>	1 7 3 1 (v/)	4.2	. ·		r Talans		a talah di kacamatan
			· · ·			<u>."</u>		
			/ /				1. 1.	
			_ ' -	r .	÷			111, 11,000
	The second secon		tries my resident					
Production rate Dil: Jas:	BOPD based	onO; Test thru (Orifi	Bbls. In ce or Meter): _		Hrs.	Grav	GG	OR
hereby certify	that the informati	on herein contain	ed is true and c	omple	te to the best o	f my knowle	· · · · · · · · · · · · · · · · · · ·	
	Conservation Di				By	Terk	77.	,
•	CUTY OIL'S GAS IN	SPECTOR, DIST. 🚜			E-mail Addres	S _{CONT}		
	and the second of the second				Date	6-1	6-05	in the State of t

- Northwest New Mexico Packer Leakage Test Instructions
- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.

Agreement of the

- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test; shall o be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).