This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

Page 1

Revised June 10, 2003

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST Well Operator Williams Exploration and Production Lease Name Rosa Unit No. 18A Location Of Well: Unit Letter P Sec 22 Twp 31N Rge <u>06</u>W API # 30-0 300392543600 Name of Reservoir or Pool Type of Prod. Prod. Medium Method of Prod. (Tbg. 0r Csg.) (Oil or Gas) (Flow or Art. Lift) Upper

Completion Lower Completion

Pre-Flow Shut-In Pressure Data Stabilized? (Yes or No) Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Upper 6-10-05 72 415 Yes Completion <u> 9920</u> Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Lower 7920 V05 Completion 250

Flow Test No. 1 Zone producing (Upper or Lower): Commenced at (hour, date)* 920 Prod. Zone Lapsed Time Remarks Time Pressure Since* Lower Compl. (Hour, Date) Upper Compl. Temp. 920 6-14 24 62 252 920 6-15 48 256 Production rate during test

Dil: ______ BOPD based on _____ Bbls. In _____ Hrs: _ Fas: 395 MCFPD; Test thru (Orifice or Meter): 0 - 12

Mid-Test Shut-In Pressure Data Upper Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Completion Lower Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Completion

(Continue on reverse side)

Flow Test No.

| | | | Flow Test P | | | | |
|--|---------------------------|--|------------------------|---------------------|---|--|-----------------|
| Commenced a | at (hour, date)** | 16 1 1021 0 1 1 | Zo | | oper or Lower): | e e la | ومحاد كالامتياد |
| Time (Hour, Date) | Lapsed Time Since** | Pre | essure Lower Compl. | Prod. Zone | Remarks | Page | |
| 24.52 | n n | | | | ٠, ٠, . , , , , , , , , , , , , , , , , | | , |
| | | | | | | t tufe | |
| | | | | | - | · · · · · · · · · · · · · · · · · · | |
| a see see o | | | | ·· - | | : ` | m Village Ku |
| | | | | | | N. | g the Objection |
| | | | | | | 9 T. A. L. | |
| roduction rate il:as: emarks: | BOPD based | on O; Test thru (Orifi | Bbls. Inice or Meter): | Hrs. | Grav. | GOR | |
| hereby certify | | and the same of th | ed is true and comp | lete to the best of | f my knowledge | | |
| pproved ew Mexico Oil | JUN 20 Conservation Di | | 20 | Operator | Sippe | Tal | lus |
| Chal | 1/2/ | | | Title | Tech | | 1 |
| tle | BEPUTY OIL & G | AS INSPECTOR, DIS | T. 89 | E-mail Address | S | | 1 × × · |
| i e sa | | Charles of the said | Vor Maria Boles Yask | Date | 6-16- | 05 | |

- MOLITIMEST MEM MEXICO LACKEL Teakage Test instructions
- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).