## STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

7422002

387

## OIL CONSERVATION DIVISION

API#

30-045-23320

Page 1 Revised 10/01/78

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

							Well		
Operator E	BURLINGTON RE	SOURCES	OIL & GAS CO.		Lease	THOMPSON	- Line	Control Control	No. <b>7A</b>
Location									
of Well:	Unit F		34 Twp.	031N	Rge.	012W	County	SAN JUAN	
	N.	AME OF R	ESERVOIR OR POO	L	T	YPE OF PROD.	METH	IOD OF PROD.	PROD. MEDIUM
	<u> </u>				ļ	(Oil or Gas)	(Flo	w or Art. Lift)	(Tbg. or Csg.)
Upper Completion	FRUITLAND					Gas		Flow	Tubing
Lower Completion MESAVERDE						Gas		Artificial	Tubing
	- <del>,</del>		PRE-F	LOW SHUT-IN	PRESS	URE DATA			
Upper	Hour, date shut-		Length of time shut-in		SI press. psig			Stabilized? (Yes or No)	
Completion	05/27/2005		120 Hours		210				
Lower Completion	05/27/2005		72 Hours			262			
				FLOW TES	T NO.	1			
	l at (hour,date)*		05/30/2005			Zone producing (Upper or Lower) LC			WER
TIME	LAPSED TIME		PRESSURE			PROD. ZONE			
(hour,date)	SINCE*		Upper Completion Lower Comple		tion	TEMP	ļ <u> </u>	REM	ARKS
05/31/2005	96 Hours		210	135					
06/01/2005	120 Hou	rs	210	132					
	-								
<del>-</del>									
						-			
Production rate	during test								
Oil	BOPD based on		Bbls. in		Hours.		Grav.		GOR
Gas:		N	ACFPD; Tested thru (	Orifice or Meter)	:				
			- , <del> 4</del> (		_				
				TEST SHUT-IN I	PRESSI	URE DATA			
Upper Completion	Hour, date shut-	ur, date shut-in  Length of time shut-in		SI press. psig			Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in		Length of time shut-in		SI press. psig			Stabilized? (Yes or No)	

(Continue on reverse side)

FLOW TEST NO. 2

mmenced at (hour, d	late)**			Zone producing (Upper or Lawer):				
TIME	LAPSED TIME	PRESSURE		PROD. ZONE	in the second se	EMARKS		
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	M	EMM1//		
•	1				•	·		
·			<b>.</b>		ι			
	,	,	2000					
				+	<u>.</u>			
		. ,						
						,,,,		
			. ''			·-		
	+	+						
ıs:		MCFPI	D: Tested thru (Orif	ice or Meter):				
marks:								
	. i'							
ereby certify the	at the information he	rein contained is true	and complete to th	e best of my knowledg	e.			
nroved	<b>利用 - 8 2</b>	2005 1	9	Operator Burlingt	on Resources			
	oil Conservation Div			120	7			
/ /	1	101011	<i>y</i> * 1	By Mores	lton.			
	l Bern			<b>-</b>	0			
( man	L Jellin		· '	Title Operations A	ssociate			
				•	,			
tle SUP	ためいばしじ いばんし	1CT # 3		Date <u>Thursday, Ju</u>	00.000	,		

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. I, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aziec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).