## This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

## NEW MEXICO OIL CONSERVATION DIVISION

Page 1

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Revised June 10, 2003

in Southeast Nev				<i>A</i> 1	Well						
Operator	XTO		Lease Name Aztec			No. <u>8</u>					
Location Of W	Vell: Unit Letter _	M SecO	8 Twp 30 N	) Rge	W API # 30-0 <u>4</u>	5 - 24695					
	Name of Reservoir or Pool		Type of Prod. (Oil or Gas)		Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)					
Upper Completion	Pictured Cliffs Formington Sand		Ga 5		Flow	TBG					
Lower Completion	Mesa Verde		605		Flow	TBG					
Pre-Flow Shut-In Pressure Data											
Upper Completion		e 23-05	Length of Time Shut-In		SI Press. Psig	Stabilized? (Yes or No) Ye S					
Lower Completion	Hour, Date, Shut-	,		Shut-In	SI Press. Psig	Stabilized? (Yes or No) Yes					
Flow Test No. 1											
Commenced at (hour, date)* 1 July 05 @ 12:30 Zone producing (Upper or Lower): Lower											
Time (Hour, Date)	Lapsed Time Pressu Since* Upper Compl. L		sure Prod. Zo Lower Compl. Temp								
12:30 1 July 05		183	440			····					
12:45 1 July 05	15 min	1 83	215		GWIII KIS TATA						
1:00 1:15	15m:n	183	200		Co Control 2000						
1:15 1:30 1:30	15 min	183	175								
1:30 1 July 0 S 1:50	15 m:n	183	175	175							
1501405	20 min	183	145		66 66 15 36 July 1						
Production rat	e during test										
Oil:         Oil:         Grav.         GOR											
Gas: MCFPD; Test thru (Orifice or Meter):											
			d-Test Shut-In P								
Upper Completion			Length of Time Shut-In		SI Press. Psig	Stabilized? (Yes or No)					
Lower Completion	Hour, Date, Shut-	Length of Time S			Stabilized? (Yes or No)						
(Continue on reverse side)											

Flow Test No.

<u> </u>	4 /1 1-4-144	· · · · · · · · · · · · · · · · · · ·	PIOW 1 Ca		· · · · · · · · · · · · · · · · · · ·			
	t (hour, date)**	,	Zone producing (U		the same of the same			
Time (Hour, Date)	Lapsed Time Since**		ssure Lower Compl	Prod. Zone Temp.	Remarks			
	, <u>.</u>							
		·	,					
				, ti				
				. 3				
Production rate								
)11:	BOPD based	on	Bbls. in	Hrs	Grav	GOR		
Remarks:	MCFF	D, Test till (Off						
hereby certify	that the informat	tion herein contai	ned is true and c	omplete to the best	of my knowledg	ė.		
Approved	JUL 1 4	2005	20	. 10				
New Mexico O	il Conservation I	Division	By David & Sandy					
By Cha	hot			Title Pumper:				
SUPERVISOR DISTRICT # 3				E-mail Address				
	-			Date Ju	ly 5, 200	o 5		

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).