

New Mexico Oil Conservation Division, District I
1625 N. French Drive
Hobbs, NM 88240

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

5. Lease Designation and Serial No.

NM058408B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

John's B. Fed #6

9. API Well No.

30-025-37212

10. Field and Pool, or Exploratory Area

Maljamar, Grayburg-San Andres

11. County or Parish, State

LEA, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Chisos Ltd.

3. Address and Telephone No.

670 DONA ANA, SW DEMING, NM 88030

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SE SE SEC. 26 T17S R32E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other

SURFACE CASING

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

T.D. WELL @ 1223.00', CIRCULATED TO CONDITION FOR CASING, RAN 1204' OF 8 5/8" NEW J-55 STC24" CASING w/ 6 CENTRALIZERS TO A DEPTH OF 1223'. CEMENTED w/ 378 SACKS CLASS C CEMENT + 6% bwoc Bentonite + 2% bwoc Calcium Chloride. 25 lbs/sack Celb Flake + Tail cement 200 SACKS CLASS C CEMENT w/ 2% bwoc Calcium Chloride @ 14.8 ppg, displaced w/ 78 BBLs FRESH WATER, CIRCULATED 117 SACKS CEMENT TO PIT, Bump plug to 800#.

ACCEPTED FOR RECORD

AUG 11 2005

GARY COURLEY
PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct

Signed

Jesse Rohm

Title

Drilling Consultant

Date

7-20-05

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side