STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

5334502

## OIL CONSERVATION DIVISION

API#

30-039-22107

Page 1 Revised 10/01/78

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator B	URLINGTON RESOURCE	S OIL & GAS CO.		Lease	SAN JUAN 27-	5 UNIT		Well No. 5A	
Location									
of Well:	Unit J Sect	34 Twp.	027N	Rge.	005W	County	RIO ARRIBA		
	NAME OF	RESERVOIR OR POOL	,	TY	PE OF PROD.	METH	OD OF PROD.	PROD. MEDIUM	
					(Oil or Gas)	(Flov	v or Art. Lift)	(Tbg. or Csg.)	
Upper Completion	PICTURED CLIFFS	PICTURED CLIFFS			Gas	'	Flow	Tubing	
Lower Completion	MESAVERDE			Gas	Flow		Tubing		
	1000	PRE-FI	LOW SHUT-IN	PRESS	URE DATA	<b>-</b>			
Upper Hour, date shut-in Length of time shut-in SI pres		ress. psig Stabilized? (Ye			es or No)				
Completion	06/24/2005	120 Hou	ırs		210				
Lower Completion	06/24/2005	72 Hou	rs	230					
			FLOW TES	T NO.	1				
Commenced	at (hour,date)*	06/27/2005			Zone producing (Upper or Lower) LOW			WER	
TIME	LAPSED TIME	PRES	SURE		PROD. ZONE				
(hour,date)	SINCE*	Upper Completion	Lower Comple	etion	TEMP_	TEMPREN		ARKS	
06/28/2005	96 Hours	210	170			Mesa Verde on.			
06/29/2005	120 Hours	210 160							
						PC si	de on.		
				,					
Production rate	auring test								
Oil	BOPD based on _	Bbls. in		Hours.		Grav		GOR	
Gas:		MCFPD; Tested thru (0	Orifice or Meter	<b>)</b> :					
				_					
		MES	PEOT OUT IN	npree	UDE DATA				
Upper Completion	Hour, date shut-in	Length of time shut-	PRESSURE DATA  SI press. psig			Stabilized? (Ye	es or No)		
Lower Completion	Hour, date shut-in	Length of time shut-in		SI press. psig			Stabilized? (Ye	es or No)	

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, da	ite)**	-		Zone producing (Upper or Lower):				
TIME	LAPSED TIME	PRES	SURE	PROD. ZONE	REMARKS			
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	NEMARKS			
				<u>.</u>				
			·,	. ,				
,				-				
Production rate dur	ring test	•	,					
	_	OPD based on	Bbls. in	Hours	GravGOR			
Gas:	<u> </u>	MCFPI	D: Tested thru (Orifi	ce or Meter):	, r			
		·			· · · · · · · · · · · · · · · · · · ·			
-				•.				
I hereby certify that	t the information her	ein contained is true	and complete to the	best of my knowledg	Je			
	AUG -1 2	2 <b>በበ</b> 5	ı	perator Burling				
·	l Conservation Divis			Olors	Pries			
By A	Villan	erra		Title Operations Associate				
	OIL & GAS INSPE	TOP DICT BE						
Title		- 1010 DIST.	Date Thursday, July 28, 2005					

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

  24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).