STATE OF NEW MEXICO **ENERGY and MINERALS** DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

OIL CONSERVATION DIVISION

API# 30-039-22797

Page 1 Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAK

Operator B	perator BURLINGTON RESOURCES OIL & GAS CO.					(Jicarilla A		Well No. <u>5A</u>	
Location									
of Well:	Unit K Sect	13 Twp.	025N	Rge.	004W	County	RIO ARRIBA	2000 11001111	
	NAME OF I	RESERVOIR OR POO	L	1 13	(PE OF PROD. (Oil or Gas)	1	IOD OF PROD. w or Art. Lift)	PROD. MEDIUM	
Upper Completion	PICTURED CLIFFS				Gas			(Tbg. or Csg.) Tubing	
Lower Completion	MESAVERDE				Gas Flow		Flow	Tubing	
		PRE-F	LOW SHUT-IN	PRESS	URE DATA				
Upper Completion	Hour, date shut-in 07/17/2005	Length of time shut-in 120 Hours		SI press. psig 286		Stabilized? (Yes or No)		es or No)	
Lower Completion	07/17/2005	72 Hoi	ırs		427	427			
			FLOW TES	T NO.	<u> </u>				
	d at (hour,date)* 07/20/2005				Zone producing	(Upper or	Lower) LO	WER	
TIME	LAPSED TIME		SSURE		PROD. ZONE				
(hour,date)	SINCE*	Upper Completion	Lower Comple	etion	TEMP	REMARKS			
07/21/2005	96 Hours	291	52		UPPER ZONE CSG		286		
07/22/2005	120 Hours	294	294 45			UPPE	UPPER ZONE CSG. 291		
				_		UPPER ZONE CSG. 294			
Production rate	e during test								
Oil	BOPD based on	Bbls. in		Hours.		Grav.		GOR	
Gas:		MCFPD; Tested thru (Orifice or Meter):					
			TEST SHUT-IN	PRESS	URE DATA				
Upper Completion	Hour, date shut-in	Length of time shut-in		SI press. psig			Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in	Length of time shut	-in	SIp	oress. psig		Stabilized? (Yes or No)		

274601

323

(Continue on reverse side)

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

FLOW TEST NO. 2

Commenced at (hour, da	ite)**		Zone producing (Upper or Lower):							
TIME	LAPSED TIME	PRESSURE		PROD. ZONE						
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS					
				, .	, -					
	a *									
		, , , , ,			, , , , , ,	· · · · · · · · · · · · · · · · · · ·				
· · · · · · · · · · · · · · · · · · ·				4 .						
			,							
Production rate dur	ing test									
Oil:BOPD based onBbls. ir				Hours	Grav.	GOR				
Gas:		MCFPE): Tested thru (Or	rifice or Meter):						
Remarks:		,		1, 1	·					
			(·						
	the information here	5	and complete to (the best of my knowled Operator Burling	1					
New Mexico Oi	Conservation Divis	ion		By Alors	ain					
ву	Villano	eva		Title Operations	Associate					
Title Date Thursday, July 28, 2005										

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except ...

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).