30-045-06083

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

								Well		
Operator B	BURLINGTON RESOURCES OIL & GAS CO.				HUERFANO U	INIT	IT		No. <u>99</u>	
Location										
of Well:	Unit C Sect	02 Twp.	026N	Rge.	010W	County	SAN JUAN			
	NAME OF	RESERVOIR OR POO	L	T	PE OF PROD.	METI	HOD OF PROD.	PR	OD. MEDIUM	
					(Oil or Gas)		(Flow or Art. Lift)		Tbg. or Csg.)	
Upper Completion	GALLUP				Gas	Artificial			Tubing	
Lower Completion	DAKOTA	***			Gas	Flow			Tubing	
		PRE-F	LOW SHUT-IN	PRESS	URE DATA					
Upper	Hour, date shut-in	Length of time shut-in		SI press. psig		Stabilized? (Ye		es or No)		
Completion	07/15/2005	120 Ho	120 Hours		130					
Lower Completion	07/15/2005	72 Hou	ırs		339					
			FLOW TES	T NO.	1		·			
Commenced	at (hour,date)*	07/18/2005			Zone producing	(Upper or	Lower) LO	WER		
TIME	LAPSED TIME	PRES	SSURE		PROD. ZONE				·	
(hour,date)	SINCE*	Upper Completion	Lower Comple	tion	ТЕМР	REMARI				
07/19/2005	96 Hours	130	210			Dakota opened for flow				
07/20/2005	120 Hours 130 242		242			B-valve opened,dakota went down to 87p			down to 87psi	
						Test	approved by Ch	arley at	OCD Dakota	
								\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	1 0 h	
				-			8 0	File	2005	
							10	DiST	3005 CE CONTROL OF CON	
Production rate	during test					_l.	- FX			
Oil	BOPD based on	Bbl s. ii	n	Hours.		Grav.		A COOR	5.65.85 15.36.8	
			·							
Gas:		MCFPD; Tested thru (Orifice or Meter)	»:						
		MID-	TEST SHUT-IN I	PRESSI	URE DATA					
Upper Completion	Hour, date shut-in	Length of time shut-in		SI press. psig			Stabilized? (Yes or No)			
Lower Completion	Hour, date shut-in	Length of time shut-in			ress. psig	Stabilized? (Yes or No)				
5304702 353	J		(Continue on re	everse s	ide)	<u> </u>				

FLOW TEST NO. 2

Commenced at (hour, dat	le)**		5 1	Zone producing (Upper or Lower):					
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE			PROD. ZONE TEMP.	REMARKS			
		Upper Completion	Lower Completic	on	TEMP.	The state of the s	 		
						, ,			
			, , ;						
							į		
			,						
					1				
	•								
Gas:			D: Tested thru (C			GravGOR	·.		
Approved	the information her AUG 16		and complete to	O B	perator Burling	ton Resources			
Title SUPERVIS	SOR DISTRICT #	3	· · ·	D	ate Monday, Au	gust 15, 2005			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note; if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 excent

•

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).