

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.

30-025-36086

Indicate Type of Lease

STATE ☒

FEE ☐

State Oil & Gas Lease No.

B-1518

### SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

Lease Name or Unit Agreement Name

Eureka 9 State Com

Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

Name of Operator  
Mewbourne Oil Company 14744

Well No.

1

Address of Operator  
PO Box 5270, Hobbs, N.M. 88241

Pool name or Wildcat

North Vacuum Atoka / Morrow

Well Location

Unit Letter C 660 Feet From The North Line and 1650 Feet From The West Line

Section 9 Township 17S Range 35E NMPM Lea County

Elevation (Show whether DF, RKB, RT, GR, etc.)

3984' GL

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

#### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

#### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ANBANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

02/06/03...TD'ed 8 3/4" hole @ 12850'. Ran logs. Decision made to P&A. Contacted OCD for plugging orders.  
Plugged well as follows:

1st plug: 12700-12800'. 35 sks 'H' w/ Ret. Mixed @ 15.6 #/g w/ 1.18 yd.

2nd plug: 11744-11844'. 35 sks 'H' w/ Ret. Mixed @ 15.6 #/g w/ 1.18 yd.

3rd plug: 9762-9862'. 35 sks 'H' w/ Ret. Mixed @ 15.6 #/g w/ 1.18 yd.

4th plug: 7722-7822'. 35 sks 'H' w/ Ret. Mixed @ 15.6 #/g w/ 1.18 yd.

5th plug: 4769-4869'. 50 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g w/ 1.32 yd. WOC. Tagged @ 4776'.

6th plug: 400-500'. 50 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g w/ 1.32 yd. WOC. Tagged @ 400'.

7th plug: Surface-30'. 10 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g w/ 1.32 yd.

02/09/03...Install P&A Marker. Well Plugged @ 0600 am. Release equipment.

Approved as to plugging of the Well Bore.  
Liability under bond is retained until  
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE District Manager

DATE 02-17-03

TYPE OR PRINT NAME N.M. Young

TELEPHONE NO. 505-393-5905

(This space for State Use)

APPROVED BY

TITLE

PETROLEUM ENGINEER

DATE

APR 07 2003

CONDITIONS OF APPROVAL, IF ANY: